





APC Smart-UPS 3kVA RM 120V **SHIPBOARD**

SMX3000RMX93

Overview

Lead time	Usually in Stock

Main	
Main Input Voltage	120 V
Other Input Voltage	100 V
Main Output Voltage	120 V
Other Output Voltage	100 V
Rated power in W	2700 W
Rated power in VA	2880 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA L5-30P
output connection type	3 NEMA 5-15R
Number of rack unit	4U
Cable length	8 ft (2.4 m)
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User's documentation in electronic format

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Battery charger power	245 W rated

General

Number of power module

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	TAA Compliant
Redundant	No

Physical

Colour	Black
Height	17.008 in (43.2 cm)
Width	7.008 in (17.8 cm)
Depth	19.02 in (48.3 cm)
net weight	85.19 lb(US) (38.64 kg)
mounting location	Front
Mounting preference	Lower
mounting mode	Rack-mounted
Two post mountable	1
USB compatible	Yes

Input

Input voltage limits	70153 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	2880 VA
Maximum configurable power in W	2700 W
Transfer time	2-4 ms
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	BSMI
Equipment protection policy	Lifetime: \$150000

Environmental

Acoustic level	55 dBA
heat dissipation	276 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	32.0000000000104.0000000000 °F (040 °C)
Ambient air temperature for storage	5.0000000000113.0000000000 °F (-1545 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Free slots 1

Alarm Alarm Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Noise suppression Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.0 in (33 cm)
Package 1 Width	23.1 in (58.8 cm)
Package 1 Length	26.1 in (66.3 cm)
Package 1 Weight	105.006 lb(US) (47.63 kg)

Contractual warranty

Warranty 3 Years

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information