

Product data sheet

Specifications



APC Smart-UPS RT 2200VA 230V - Marine

SURTD2200XLIM

Overview

Presentation	High availability, ruggedized power protection for shipboard and other transportation applications.
Lead time	Usually in Stock


Main

Main Input Voltage	230 V
Product or Component Type	Filter
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Kw Rating	1540 W
rated power in VA	2200 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
Number of rack unit	3U
Cable length	8.2 ft (2.5 m)
Number of cables	1
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Smart UPS signalling RS-232 cable User Manual

Batteries & Runtime

Run Time	View Runtime Graph
Battery Type	Lead-Acid battery
Extendable Run Time	1
Included Battery Modules	2
Typical recharge time	2.5 h
RBC Quantity	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Battery life	3...5 year(s)
Replacement battery	APCRBC140 
Battery Charge Power (Watts)	382 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Topology	Double Conversion Online

Physical

color	Black
Height	17.01 in (43.2 cm)
Width	5.12 in (13 cm)
Depth	25.98 in (66 cm)
Net Weight	120.26 lb(US) (54.55 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Efficiency at full load	180...280 V
Input Frequency	50/60 Hz +/- 5 Hz auto-sensing

Output

Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	3 : 1
Harmonic distortion	Less than 3%
Maximum configurable power in VA	2200 VA
Max Configurable Power (Watts)	1540 W
Wave type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product Certifications	CE DNV KCC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	55 dBA
Online Thermal Dissipation	609 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32...131 °F (0...55 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
IP degree of protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Emergency Power Off (EPO)	Yes
Free slots	0
Pre-Installed SmartSlot™ Cards	Dry contact I/O smartslot card
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	555 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

GTIN	731304286929
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.66 in (34.7 cm)
Package 1 Width	23.74 in (60.3 cm)
Package 1 Length	38.58 in (98 cm)
Package 1 Weight	140.30 lb(US) (63.64 kg)

Contractual warranty

Warranty	2 years repair or replace, optional extended warranties available, optional on-site services available
----------	--



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

WEEE

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Take-back

Yes