

4XEM™ **Product Data Sheet**

USB-C 4-in-1 Wireless HDMI Hub



Your all-in-one solution for seamless 4K display, ultra-fast connectivity, and powerful 100W charging, whether wired or wireless.


Key Features



4-Port
Wireless Hub



100W Power
Delivery



Bus-powered
USB-C connector



Video Switch
button



Wide OS
Compatibility



98FT Transmission
Distance (barrier free)

Technical Highlights

SKU Name	4X4N1HDMIWLHUB
Warranty	1 Years
Ports	2x USB-C 5Gbps 1x USB-A 5Gbps 1x HDMI 4K 1x USB PD charging
Total Power	PD 100W

Application(s)

Designed for professionals, educators, and teams, this hub simplifies 4K display, collaboration, and device connectivity.

Visit **4XEM.com**

Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 ext.113 bhegarty@4xem.com

4XEM™ Product Data Sheet

Technical Specifications

Warranty Information	Warranty	1 Year
Hardware	Operating Mode Host Interface Bus Type AV Output Audio Support Power Chip ID Industry Standards	Active USB-C HDMI HDMI Yes Yes AM8360D+GSV220IS+GL3510+AW3410S+SC8723+2*AM942I+AM8268D USB 3.0, USB 2.0 PD 3.0 HDMI
Connector(s) & Performance	Host Connector Ports Maximum Resolution Maximum Wireless Resolution Audio Specifications Transmission Distance Delay time	USB-C 2x USB-C 5Gbps 1x USB-A 5Gbps 1x HDMI 4K 1x USB PD charging HDMI 4K @ 60Hz (3840*2160/60Hz) 1920*1080P @ 60Hz 32/44.1/48khz 30M (barrier free) 100ms
Software	OS Compatibility	Windows 7 or later Mac OS 10.10 or later Android
Power	Power Source Standby Power Consumption Active Power Consumption Charging Capabilities	Bus-Powered Transceiver: 1.93W +/- 5% Receiver: 1W +/- 5% Transceiver: 3.35W +/- 5% Receiver: 1.2W +/- 5% PD3.0 100W 20V 5A Max
Physical Characteristics	Color Button Cable Jacket Type Transceiver Length Transceiver Width Transceiver Height Receiver Connector Length Receiver Connector Width Receiver Connector Height Weight of Product	Black Wired and wireless video switch Green light indicates it is in wired display mode White light indicates it is in wireless display mode PVC 3.54 in [90 mm] 2.16 in [55 mm] 0.59 in [15 mm] HDMI: 1.19 in [30.3 mm] USB: 1.08 in [27.5 mm] 0.72 in [18.5 mm] 0.39 in [10 mm] 2.82 oz [80 g]
Environmental	Humidity Operating Temperature Storage Temperature	45%-90%RH 0°C to 40°C (32°F to 104°F) -20°C to 60°C (4°F to 140°F)
Packaging Information	Packaging Type Package Height Package Width Package Length Shipping (Package) Weight	Box 1.18 in [30 mm] 7.87 in [200 mm] 4.72 in [120 mm] 5.29 oz [150 g]
What's in the Box	Included in Package	1 - USB-C 4-in-1 Hub/Transmitter 1 - USB-A to HDMI Receiver
Notes	System Requirements Notes	Plug and play, no driver, ethernet or wifi required Dual Display not supported