

## 5,000 ANSI LUMENS 4K UHD LAMP-FREE LASER INSTALLATION PROJECTOR | LS740-4K


### Key Features

---


- **4K CLARITY IN AMBIENT LIGHTING:** True 4K resolution and 5,000 ANSI lumens deliver crisp, vibrant visuals even in rooms with ambient lighting.
- **FLEXIBLE MOUNTING OPTIONS:** A 1.6x optical zoom, H/V keystone and 360-degree projection support effortless ceiling, floor or portrait setups.
- **MAINTENANCE-FREE LIFESPAN:** The latest laser phosphor technology provides up to 30,000 hours of operation.
- **REDUCED ENERGY COSTS:** Consumes up to 49% less power than traditional lamp models, lowering utility bills and total cost of ownership.
- **REMOTE MANAGEMENT MADE EASY:** Centralized RJ45 LAN connectivity allows IT teams to seamlessly monitor, control and manage devices remotely.
- **LONG-LASTING PERFORMANCE:** An IP6X-rated sealed optical engine blocks dust intrusion to ensure consistent image quality with no upkeep required.



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



4K UHD (3840 x 2160)  
**RESOLUTION**



4K UHD High-Brightness  
Laser Projector

### Product Description

---

The ViewSonic LS740-4K is a high-performance, low-maintenance projector built for exceptional versatility across educational, corporate and entertainment spaces. Whether it's deployed in a classroom, conference room or home theater, this lamp-free projector delivers 5,000 ANSI lumens at 4K UHD resolution. These vibrant visuals hold up beautifully against ambient light. For golf enthusiasts, a dedicated Golf Mode optimizes color accuracy to make fairways and putting surfaces look remarkably lifelike. Powered by the latest laser phosphor technology, this 4K projector provides up to 30,000 hours of maintenance-free operation with no lamp replacements needed. Compared to traditional lamp models, the LS740-4K reduces energy consumption by up to 49%. For schools and businesses, those savings on energy and maintenance add up to a meaningfully lower total cost of ownership. To accommodate a wide range of room layouts, a 1.6x optical zoom provides exceptional placement flexibility while 360-degree projection supports effortless ceiling, floor or portrait installations. Inside the projector, a high-contrast 0.65-inch DMD chip keeps text razor-sharp and video content crystal clear. The LS740-4K features an IP6X-rated sealed optical engine that blocks dust to ensure consistent image quality without the need for a filter.

# Specifications

| More Information                    |                                            |
|-------------------------------------|--------------------------------------------|
| UPC                                 | 766907041897                               |
| Light Source                        | Laser                                      |
| Display Resolution                  | 4K (3840x2160)                             |
| Display Resolution                  | 3840 x 2160                                |
| Brightness (Lumens)                 | 5,000 ANSI                                 |
| Screen Size                         | 30 - 300 in. / 0.76 - 7.62 m               |
| Throw Distance                      | 0.93m - 14.88m (100"@3.1m)                 |
| Throw Ratio                         | 1.4 - 2.24                                 |
| Offset                              | 124%+/-10%                                 |
| Keystone                            | Vertical (± 30º) / Horizontal (± 30º)      |
| Lens                                | 1.6x optical zoom                          |
| Light Source Life, Normal (hours)   | 20000                                      |
| Light Source Life, SuperEco (hours) | 30,000                                     |
| Color Depth                         | 1.07 Billion Colors                        |
| Dynamic Contrast Ratio              | 3,000,000:1                                |
| Aspect Ratio                        | 16:9                                       |
| Input Lag                           | 4.2ms                                      |
| Lens Shift                          | N/A (Digital Zoom: 0.8x-2.0x)              |
| Frequency Horizontal                | 15K-150KHz                                 |
| Frequency Vertical                  | 24-240Hz                                   |
| PC Resolution (max)                 | 4K UHD (3840 x 2160)                       |
| PC Resolution (min)                 | VGA (640 x 480)                            |
| Mac® Resolution (max)               | 4K UHD (3840 x 2160)                       |
| Mac® Resolution (min)               | VGA (640 x 480)                            |
| USB 2.0 Type A                      | 1 (5V/1.5A) Power, Service                 |
| Ethernet LAN (RJ45)                 | 1                                          |
| 3.5mm Audio Out                     | 1                                          |
| Control (RS232)                     | 1                                          |
| HDMI 2.0 In                         | 2                                          |
| Internal Speakers                   | 15W (x1)                                   |
| Audible Noise (Normal)              | 32dB                                       |
| Audible Noise (Eco)                 | 27dB                                       |
| Voltage                             | Input: 100~240V & Output: 19.5VDC / 11.79A |

|                              |                                                                                                                                                             |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Consumption (typical)</b> | 165W                                                                                                                                                        |
| <b>Stand-by</b>              | <0.5W                                                                                                                                                       |
| <b>Temperature</b>           | 32-104º F (0 - 40º C)                                                                                                                                       |
| <b>Normal</b>                | 32dB                                                                                                                                                        |
| <b>Eco-Mode</b>              | 27dB                                                                                                                                                        |
| <b>Net (lbs)</b>             | 6.83                                                                                                                                                        |
| <b>Gross (lbs)</b>           | 10.58                                                                                                                                                       |
| <b>Net (kg)</b>              | 3.10                                                                                                                                                        |
| <b>Gross (kg)</b>            | 4.80                                                                                                                                                        |
| <b>Packaging (in.)</b>       | 15.7x11x6.1                                                                                                                                                 |
| <b>Physical (in.)</b>        | 11.3x8.5x5.1                                                                                                                                                |
| <b>Packaging (mm)</b>        | 400x280x155                                                                                                                                                 |
| <b>Physical (mm)</b>         | 286x216x129                                                                                                                                                 |
| <b>Regulations</b>           | cTUVus, CE, FCC, Laser                                                                                                                                      |
| <b>Package Contents</b>      | Projector, power cable, remote control, Quick Start Guide                                                                                                   |
| <b>Warranty</b>              | Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). |
| <b>Recycle/Disposal</b>      | Please dispose of in accordance with local, state or federal laws.                                                                                          |

UPC: 766907041897



## Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)