

4XEM's USB-C Triple Display 4K Docking Station with Power Delivery (1 VGA/HDMI/DP)

4XEM Part- 4XUMD04



Experience the ultimate in productivity and convenience with our USB Type C Triple Display with Power Delivery. This sleek and powerful device features a 1x USB-C 3.1 Host Connector, 1x HDMI 1.4 (10.2 Gbps) Port, 1x VGA Port, 2x USB 2.0 Type-A Ports, 1x RJ45 Gigabit Port, 1x SD Card Reader Version 2.0, 1x Micro-SD Card Reader Version 2.0, and a 1x 4-Pole TRRS Phono Jack (Audio In/Out Combo).

Connect to three displays for the ultimate viewing experience, with the HDMI and VGA ports providing high-quality visuals at 10.2Gbps. The USB Type C Triple Display also features fast and efficient data transfer with USB 2.0 Type-A Ports, and lightning-fast internet connection speeds with the RJ45 Gigabit Port.

The Power Delivery feature allows you to charge your laptop while using the dock, and the SD Card Reader Version 2.0 and Micro-SD Card Reader Version 2.0 provide easy access to your files. The 4-Pole TRRS Phono Jack (Audio In/Out Combo) ensures seamless audio input and output for all your devices.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com**



Warranty Information	Warranty	2 Years
Features/Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Power Delivery Lock Slot Industry Standards Chipset ID	Yes 3 3 N/A Yes Yes Yes PD Pass-through No HDMI 1.4 DisplayPort 1.2 Power Delivery (PD 3.0) Secure Digital (SD v2.0) VIA Labs - VL103 VIA Labs - VL104 Synaptics - VMM3332 Realtek - RTL8153B Realtek - ALC4030 Genesys Logic - GL823K
Connector(s)	Host Bus Type Host Connectors Host Connector Cable Connector Type(s)/Rate(s)	USB 3.1 Gen 1 (5Gbps) USB Type-C Fixed Attached 1x DisplayPort 1.2a (HBR2: 5.4Gbps x2) 1x HDMI 1.4 (10.8 Gbps) 1x VGA 2x USB Type-A (5Gbps) 2x USB Type-A (480Mbps) 1x RJ-45 (10/100/1000Mbps) 1x SDHC Card Reader (25 MB/s) 1x MicroSDHC Card Reader (25 MB/s) 1x 4-Pole TRRS Phono Jack (Audio In/Out Combo)
Performance	Maximum Digital Resolutions Maximum Analog Resolutions Audio Specifications	Single Monitor: 4K UHD - 3840 x 2160 @ 30Hz Dual Monitors: FHD - 1920 x 1080 @ 60Hz each Triple monitors: 1600 x 900 @ 60Hz each Single Monitor: FHD - 1920 x 1080 @ 60Hz Dual Monitors: FHD - 1920 x 1080 @ 60Hz Triple monitors: 1600 x 900 @ 60Hz 2-ch Stereo
Software	OS Compatibility	Windows 7, 8, 8.1, 10 Mac OSX Linux
Power	Power Source Power Adaptor Style Power Consumption Input Voltage Power Delivery	Bus Powered N/A 15W (Full Load withput PD) N/A PD Pass-through - Max 100W in/85W out
Physical Characteristics	Colour Shell Material Host Cable Length Buttons/Switches LED Indicators Power Cable Length Product Height Product Width Product Length Weight of Product	Black Plastic 20.0 in [508 mm] None Power: Blue N/A 0.79 in [20.0 mm] 8.27 in [210 mm] 2.30 in [58.5 mm] 8.11 oz [230 g]
Environmental	Operating Temperature Storage Temperature	32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing) 14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Box 8.86 in [225 mm] 3.68 in [93.5 mm] 1.06 in [27 mm] 11.57 oz [328 g]
What's in the Box	Included in Package	1x USB 3.1 Type-C Docking Station 1x User Manual
Notes / Special Requirements	Notes	"Host must support DP Alt mode for video output. Host must support PD 3.0 for upstream charging. This device uses 2 data lanes for DP Alt mode and 2 remaining data lanes for other dock functions. Maximum video bandwidth cannot exceed 8.64 Gbps (10.8Gbps incl. overhead). Some graphics chipsets support only a limited number of active displays resulting in one or more of the displays connected to the 4XUMD04 left blank - Active displays can be changed in the display settings of your operating system."

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

