



SPECIFICATION

Panel Size 23.6" (60cm) Panel Resolution 1920 x 1080 (FHD) Refresh Rate 144Hz Response time 1ms Panel Type Samsung VA Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 DCR 10000000:1 Active Display Area (mm) 521:3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1 x DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 100 × 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz Power Consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° <		
Refresh Rate144HzResponse time1msPanel TypeSamsung VABrightness (nits)250 nitsViewing Angle178 ° (H) / 178 ° (V)Aspect Ratio16:9Curvature1500RContrast Ratio3000:1DCR10000000:1Active Display Area (mm)521.3952(H) x 293.2848(V)Pixel Pitch (H x V)0.27156(H) x 0.27156(V)Surface TreatmentAnti-glareDisplay Colors16.7MVideo ports1 x DP (1.2a) 2 x HDMI (1.4b)Audio ports1 x Earphone outKensington LockYesVESA Mounting100 × 100 mmControl5-way OSD navigation joystickPower Consumption35WSignal Frequency55.3 to 162KHz (H) 48 to 144Hz (V)Adjustment (Tilt)-5° ~ 20°Dimension (W x H x D)536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inchWeight (NW / GW)3.4kg / 5kgFrameless DesignYes	Panel Size	23.6" (60cm)
Number Number Number Number Response time Ims Panel Type Samsung VA Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power Consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° <t< th=""><th>Panel Resolution</th><th>1920 x 1080 (FHD)</th></t<>	Panel Resolution	1920 x 1080 (FHD)
Panel Type Samsung VA Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 DCR 10000000:1 Active Display Area (mm) 521.3952(H) × 293.2848(V) Pixel Pitch (H x V) 0.27156(H) × 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1 × DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 100 × 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power Consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design <t< th=""><th>Refresh Rate</th><th>144Hz</th></t<>	Refresh Rate	144Hz
Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1 x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes	Response time	1ms
Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes	Panel Type	Samsung VA
Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16:7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Brightness (nits)	250 nits
Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Viewing Angle	178° (H) / 178° (V)
Contrast Ratio 3000:1 DCR 100000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Aspect Ratio	16:9
DCR 10000000:1 Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Curvature	1500R
Active Display Area (mm) 521.3952(H) x 293.2848(V) Pixel Pitch (H x V) 0.27156(H) x 0.27156(V) Surface Treatment Anti-glare Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Contrast Ratio	3000:1
Pixel Pitch (H x V) $0.27156(H) \times 0.27156(V)$ Surface TreatmentAnti-glareDisplay Colors $16.7M$ Video ports $1x DP (1.2a)$ $2x HDMI (1.4b)$ Audio ports $1x Earphone out$ Kensington LockYesVESA Mounting $100 \times 100 \text{ mm}$ Control 5 -way OSD navigation joystickPower TypeExternal Adaptor 19V 3.42APower consumption $35W$ Signal Frequency $55.3 \text{ to } 162KHz (H)$ $48 \text{ to } 144Hz (V)$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Dimension (W x H x D) $536.7 x 429 \times 225.4 \text{ mm} / 21.13 x 16.89 x 8.87 \text{ inch}$ Weight (NW / GW) $3.4kg / 5kg$ Frameless DesignYesNoteDisplay Port: 1920 x 1080 (Up to 144Hz)	DCR	10000000:1
Surface TreatmentAnti-glareDisplay Colors16.7MVideo ports1x DP (1.2a) 2x HDMI (1.4b)Audio ports1x Earphone outKensington LockYesVESA Mounting100 x 100 mmControl5-way OSD navigation joystickPower TypeExternal Adaptor 19V 3.42APower Input100~240V, 50~60HzPower consumption35WSignal Frequency55.3 to 162KHz (H) 48 to 144Hz (V)Adjustment (Tilt)-5° ~ 20°Dimension (W x H x D)536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inchWeight (NW / GW)3.4kg / 5kgFrameless DesignYesNoteDisplay Port: 1920 x 1080 (Up to 144Hz)	Active Display Area (mm)	521.3952(H) x 293.2848(V)
Display Colors 16.7M Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Pixel Pitch (H x V)	0.27156(H) x 0.27156(V)
Video ports 1x DP (1.2a) 2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Surface Treatment	Anti-glare
2x HDMI (1.4b) Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Display Colors	16.7M
Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Video ports	
Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)		
VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	•	1x Earphone out
Control 5-way OSD navigation joystick Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)		Yes
Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	VESA Mounting	100 x 100 mm
Power Input 100~240V, 50~60Hz Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Control	5-way OSD navigation joystick
Power consumption 35W Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Power Type	External Adaptor 19V 3.42A
Signal Frequency 55.3 to 162KHz (H) 48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Power Input	100~240V, 50~60Hz
48 to 144Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Power consumption	35W
Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Signal Frequency	
Dimension (W x H x D) 536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)		
Weight (NW / GW) 3.4kg / 5kg Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	Adjustment (Tilt)	
Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 144Hz)	. ,	536.7 x 429 x 225.4 mm / 21.13 x 16.89 x 8.87 inch
Note Display Port: 1920 x 1080 (Up to 144Hz)	3 ()	3.4kg / 5kg
	Frameless Design	Yes
HDMI: 1920 x 1080 (Up to 144Hz)	Note	
		HDMI: 1920 x 1080 (Up to 144Hz)

FEATURE



144Hz High Refresh Rate



Experience smooth gaming with a blazing fast 144Hz refresh rate, that gives you the upperhand in fast moving games.



Frameless Design

With the narrow bezel, you will not even notice the monitor at all in the heat of the moment.



Wide Color Gamut

Game colors and details will look more realistic and refined, to push game immersion to its limits.

Radeon FreeSync™

Puts an end to choppy gameplay and broken frames with fluid, artifact-free performance at virtually any framerate.

1ms Fast Response Time 1_{ms}


Eliminate screen tearing and choppy frame rates with 1ms response time.

Curved Gaming



MSI Curved Gaming Monitor will give you the most immersive and competitive edge you need to take down your opponents.

CONNECTIONS



Gen

