

HP L1955 Flat Panel Monitor



The HP L1955 Flat Panel Monitor is a high-performance 19-inch flat panel monitor for workstation and business PC users. By providing a combination of advanced features and space-saving design, the L1955 offers exceptional flexibility and performance to any business environment.

Advanced features

The HP L1955 delivers superior clarity with an extra bright screen, 1000:1 high contrast ratio, superior image processing and 176-degree viewing angles. An anti-glare coating and flicker-free TFT image presentation help eliminate glare, eyestrain, and fatigue.

User-friendly features

The combination of the height-adjustable base (14 cm) and the 90-degree pivot capability for portrait or landscape viewing makes it easy to achieve comfortable eye contact with the screen. Direct access keys on the front of the monitor allow users to quickly access display settings or switch video inputs. Super-thin bezels (13 mm) on the left and right sides of the screen enable users to "tile" several panels together for panoramic viewing of large data displays on trading floors or other data-intensive environments.

Increased functionality and performance

An optional HP Desktop Access Center (sold separately), which fits just under the base of the monitor, offers integrated microphone/headset jacks, dual-function headset for phone/PC support, a MultiBay slot for adding an optical drive, and four USB ports for easy integration of third-party digital solutions. An optional HP Flat Panel Speaker Bar (sold separately) attaches seamlessly to the bezel, adding full multimedia support features.

Quality and reliability

HP monitors meet the highest levels of quality and reliability - each model is tested and qualified to assure backward and forward compatibility with current or planned HP workstations and desktops.

High-performance 19-inch flat panel monitor with advanced features for workstation and PC users.



HP L1955 Flat Panel Monitor

Type	Active matrix TFT (thin film transistor) Anti-glare and anti-static coatings
Viewable image area	19 inches diagonal
Viewing angle	176° horizontal, 176° vertical
Brightness	250 nits
Contrast ratio	1000:1
Response rate	16 ms
Dot/Pixel pitch	0.294 mm
Colour depth support	16.7 million colors
Maximum pixel clock speed	140 MHz
Frequency	Horizontal frequency: 30-82 kHz, Vertical frequency: 56-75 kHz
Self powered USB 2.0 hub	One upstream, four downstream ports (cable included)
Resolution	1280 x 1024 @ 60 Hz (native), all VESA modes up to 1280 x 1024 @ 75 MHz
Input signal	Two connectors: one 15-pin mini D-sub analog VGA, and one DVI (VGA analog or digital)
Video cable	VGA to VGA, DVI-D to DVI-D and DVI-I to VGA
User controls (on-screen display)	Size and positioning, contract, brightness, clock, clock phase, selectable color temperature, input selection, reset, individual color contract, full-screen resolution
Power supply	Auto-ranging, 90 to 265 VAC, Internal power supply, 47.5 to 63 Hz (built-in power supply)
Power consumption	60 watts maximum, 40 watts typical
Power Consumption, Standby	2 watts
Bezel width	13 mm left and right, 14 mm top, and 15 mm bottom
Dimensions (W x D x H)	Without stand: 404 x 79 x 335 mm, with stand: 404 x 211 x 427 (minimum) to 566 (maximum) mm
Weight	With stand: 7.5 kg, without stand: 4.75 kg
Base features	-5° to 35° vertical tilt, ±50° swivel, 90° pivot/landscape rotation, 5.1 in (13 cm) height adjust, detachable "quick release" base
Operating temperature	5 to 35°C
Non-operating temperature	-20 to 60° C
Operating humidity	20 to 80% RH
Non-operating humidity	5 to 95% RH
Options	HP Desktop Access Center—Optional, features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs HP Flat Panel Speaker Bar—Optional, powered directly by the monitor, seamlessly attaches to the monitor's bezel to bring full multimedia support to select HP flat panel monitors, features dual speakers with full sound range, external jack for headphones. Part number PF804AA. For more information, refer to the product's QuickSpecs.
Certifications, compliances	Australian ACA approval, Canadian requirements/CSA, CE Marking, China CCC approval, CISPR requirements, Eastern European approvals, Energy Star compliant, FCC approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 compliant (Pixel Defect Guidelines), Mexican NOM approval, MPR-II compliant, PC2001 compliant, PC99 certified, S. Korean MIC, approval, Taiwan BSMI approval, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI approvals, Microsoft® Windows® certification
Warranty	Limited three years parts, labor, and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. Consult HP Customer Service for details.

© 2004 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information, please visit www.hp.com/eur/monitors

5982-8666EEE, October 2004

