



Protect It! 6-Outlet Surge Protector, 6 ft. Cord, 900 Joules, Diagnostic LED, Black Housing

MODEL NUMBER: TLP606B











Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise.

Description

Perfect for your home or office workstation, the TLP606B Protect It!® 6-Outlet Surge Protector features a surge protection rating of 900 joules to defend your sensitive electronic components against strong surges and spikes.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP606B protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into six NEMA 5-15R outlets, one of which is placed at the end to accept a bulky transformer without blocking adjacent outlets. An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in case of overload. The lighted on/off switch provides one-touch control over connected equipment. A diagnostic LED confirms your connected equipment is protected. The six-foot (1.8-meter) AC power cord with NEMA 5-15P plug reaches nearby outlets to fit easily into your workstation or home theater setup. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

Features

900-Joule Surge Protection for Home or Office ElectronicsProtects your computer, printer, scanner, router, modem and other small home electronics against even the strongest surges and spikesRecommended for any desktop, network or home electronics application requiring AC line protectionFull normal mode (H-N) and common mode (N-G/H-G) line surge suppressionFilters out disruptive EMI/RFI line noise that can cause equipment damage or data lossExceeds IEEE 587 Category A and B surge suppression specifications

6 Outlets Accept Wide Range of Electronic Devices6 NEMA 5-15R AC outlets accept most computers and peripheralsSpecial end outlet designed for bulky transformers without blocking other outlets

Premium Safety FeaturesLighted on/off switch provides one-touch control over connected equipmentAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LED confirms protection status at a glanceConforms to current UL 1449 5th Edition safety standards

Fits Effortlessly Into Your Workstation6 ft. AC power cord with NEMA 5-15P plug reaches nearby outletsKeyhole slots on bottom panel provide convenient wall or desk mounting optionsBlack plastic housing designed for long life

Highlights

- 6 NEMA 5-15R outlets—one designed for a bulky transformer
- 900-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 6 ft. AC power cord with NEMA 5-15P plug

Package Includes

- TLP606B Protect It! 6-Outlet Surge Protector, Black Housing
- Owner's manual





Backed by Ultimate Lifetime Insurance\$20,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

Specifications

OVERVIEW		
UPC Code	037332138293	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	35500	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(2) Yes	
Outlet Orientation	Single row of 6 outlets	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LED Details	Built-in LED confirms suppressor "protection present" (green) status	
SURGE / NOISE SUPPRESSION		





AC Suppression Joule Rating AC Suppression Response Time Protection Modes Includes full normal mode (H+N) and common mode (N-G / H-G) line suppression Includes full normal mode (H+N) and common mode (N-G / H-G) line suppression EMI / RFI Filtering Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coav) Protection No Network (Ethernet) Protection No PHYSICAL Material of Construction Plastic Power Card Color Black Housing Color Black Mounting Holes or Stots Slot or Hole Mount Measurement (Conter to Centre) Centre to Content Content or Control Shipping Dimensions (twid / in.) Shipping Dimensions (twid / in.) Shipping Dimensions (twid / in.) Shipping Weight (Ibs.) Unit Dimensions (fived / in.) 1.20 Shipping Weight (Ibs.) 1.01 Unit Weight (Ibs.) 1.01 Unit Weight (Rg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial CAN/CSA-C22.2 No. 289.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1383 TANARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 289.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1383			
Protection Modes Includes full normal mode (H-N) and common mode (N-G /H-G) line suppression UL1449 Let Through Rating 500V EM / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone(DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Carlete Measurement (Center to 28.5mm Receptacle Color Black Shipping Dimensions (fived / in.) 12.50 x 1.60 x 5.00 Shipping Weight (bs.) 1.20 Shipping Weight (bs.) 1.20 Link Unit Meight (bs.) 1.01 Unit Weight (bs.) 1.01 Unit Weight (bs.) 1.01 Unit Weight (bs.) 1.01 Unit Weight (bs.) 0.48 FEATURES & SPECIFICATIONS Rotable Outlets No Antimicrobial STANDARDS & COMPLIANCE Interpretation of the suppression of the suppression Interpretation of the suppr	AC Suppression Joule Rating	900	
UL-1449 Let Through Rating 500V EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to 28.5mm Receptacle Color Black Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Weight (lbs.) 1.20 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / on.) 27.43 x 4.70 x 3.12 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	AC Suppression Response Time	< 1 ns	
EMI / RFI Filtering	Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
Automatic Shur-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Mounting Holes or Slots Yes Slot of Hole Mount Measurement (Center to Center) Cullets Measurement (Center to Center) Cullets Measurement (Center to Center) Receptacle Color Black Shipping Dimensions (hwd / in) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / in) 1.20 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / orn) 27.43 x 4.70 x 3.12 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	UL1449 Let Through Rating	500V	
DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Distance between slots = 101 mm; Distance between slot height = 28 mm (Center) Outlets Measurement (Center to Center) Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / orn) Shipping Weight (fbs.) 1.20 Shipping Weight (fbs.) Unit Dimensions (hwd / orn) 27.43 x 4.70 x 3.12 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	EMI / RFI Filtering	Yes	
Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Slot or Hole Mount Measurement (Center to Center) Dutlets Measurement (Center to Center) 28.5mm Receptacle Color Black Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No	Automatic Shut-Off	Yes	
Network (Ethernet) Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Center) Receptacle Color Black Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / in.) 11.024 x 1.850 x 1.300 Unit Weight (lbs.) 1.01 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection No PHYSICAL Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Quilets Measurement (Center to Center) Receptacle Color Black Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / in.) 11.024 x 1.850 x 1.300 Unit Unit Weight (lbs.) 1.01 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Cable (Coax) Protection	No No	
PHYSICAL Material of Construction Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Eenter) Center of Black Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) 1.20 Shipping Weight (kg) Unit Dimensions (hwd / cm) 11.024 x 1.850 x 1.300 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotandards Ro	Network (Ethernet) Protection	No No	
Material of Construction Plastic Power Cord Color Black Housing Color Black Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between slots = 101 mm; Distance between slot height = 28 mm Qutlets Measurement (Center to Center) 28.5mm Receptacle Color Black Shipping Dimensions (hwd / in.) 12.50 x 1.60 x 5.00 Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No	Telephone/DSL Protection	No No	
Power Cord Color Housing Color Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between slots = 101 mm; Distance between slot height = 28 mm Outlets Measurement (Center to Center) Receptacle Color Black Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) 1.20 Shipping Weight (kg) Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial Rotatable Solve Measurement (Center to Center) Distance between slot height = 28 mm Distance between slot h	PHYSICAL		
Housing Color Mounting Holes or Slots Slot or Hole Mount Measurement (Center to Center) Distance between slots = 101 mm; Distance between slot height = 28 mm Cutlets Measurement (Center to Center) Receptacle Color Black Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) 1.20 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Material of Construction	Plastic	
Mounting Holes or Slots Slot or Hole Mount Measurement (Center to Center) Distance between slots = 101 mm; Distance between slot height = 28 mm Qutlets Measurement (Center to Center) Receptacle Color Black Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) 1.20 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No STANDARDS & COMPLIANCE	Power Cord Color	Black	
Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Receptacle Color Shipping Dimensions (hwd / in.) Shipping Weight (lbs.) Unit Dimensions (hwd / in.) Unit Weight (lbs.) Unit Weight (lbs.) I.01 Unit Weight (kg) O.46 FEATURES & SPECIFICATIONS Rotable Outlets No STANDARDS & COMPLIANCE	Housing Color	Black	
(Center to Center) Detailed between six is a 1 to 1 min, bistance between six insgin 2 to 1 min, bistance between six in six insgin 2 to 1 min, bistance between six in six in s	Mounting Holes or Slots	Yes	
Receptacle Color Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / cm) 11.024 x 1.850 x 1.300 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Slot or Hole Mount Measurement (Center to Center)	Distance between slots = 101 mm; Distance between slot height = 28 mm	
Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / in.) 11.024 x 1.850 x 1.300 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Outlets Measurement (Center to Center)	28.5mm	
Shipping Dimensions (hwd / cm) 31.75 x 4.06 x 12.70 Shipping Weight (lbs.) 1.20 Shipping Weight (kg) 0.54 Unit Dimensions (hwd / in.) 11.024 x 1.850 x 1.300 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Receptacle Color	Black	
Shipping Weight (lbs.) 1.20	Shipping Dimensions (hwd / in.)	12.50 x 1.60 x 5.00	
Shipping Weight (kg) 0.54 Unit Dimensions (hwd / in.) 11.024 x 1.850 x 1.300 Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Shipping Dimensions (hwd / cm)	31.75 x 4.06 x 12.70	
Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Shipping Weight (lbs.)	1.20	
Unit Dimensions (hwd / cm) 27.43 x 4.70 x 3.12 Unit Weight (lbs.) 1.01 Unit Weight (kg) 0.46 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Shipping Weight (kg)	0.54	
Unit Weight (lbs.) Unit Weight (kg) FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Unit Dimensions (hwd / in.)	11.024 x 1.850 x 1.300	
Unit Weight (kg) FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Unit Dimensions (hwd / cm)	27.43 x 4.70 x 3.12	
FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Unit Weight (lbs.)	1.01	
Rotatable Outlets No Antimicrobial No STANDARDS & COMPLIANCE	Unit Weight (kg)	0.46	
Antimicrobial No STANDARDS & COMPLIANCE	FEATURES & SPECIFICATIONS		
STANDARDS & COMPLIANCE	Rotatable Outlets	No	
	Antimicrobial	No	
Product Certifications CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363	STANDARDS & COMPLIANCE		
	Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; UL 1449; UL 1363; UL Listed	
Product Compliance RoHS	Product Compliance	RoHS	





WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.