LFD - SIGNAGE DISPLAYS

INFORMATION




75" 4K UHD Most powerful professional digital signage display with a brightness of 800cd/m².

The ProLite LH7566UHSB-B1AG is a 75" 4K UHD digital signage powerhouse designed to elevate your business's visual communication. With Android 14 OS, iiSignage² (CMS), iiControl (DMS), and iiShare (Wireless Presentation), managing content is effortless. It's WiFi enabled for remote content delivery and offers reliable 24/7 operation. Perfect for retail, corporate, hospitality, or restaurant settings, this display ensures a captivating audience experience with its versatile design and high brightness of 800cd/m².



Android OS

Thanks to Android OS, you can easily customize the display to your needs by installing applications directly to it.



iiSignage²

iiSignage² is our digital signage content management platform to easily show and control your content and to manage your displays in a secure way. The Content Management System (CMS) gives you total control of your messaging and advertising remotely and safely.



Signal FailOver

FailOver is a feature which automatically detects input sources. When there is no signal on the default input it will automatically switch to the next available input. FailOver allows customers to prioritize a number of inputs (incl. Browser, Media Player and Custom) and ensures your content is always actively displayed, assuring active content at all times.



Flexible Orientation

With the option to switch between landscape and portrait mode, these displays let you get creative with any space. Whether it's messaging, ads, videos, or safety info, you can tailor your content to grab attention exactly how you want.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	Thin bezel
Diagonal	75", 189.5cm
Panel	VA, Anti-Glare coated glass, matte finish, haze 25%
Native resolution	3840 x 2160 @60Hz (8.3 MegaPixels 4K UHD)
Aspect ratio	16:9
Panel brightness	800 cd/m²
Static contrast	5000:1
Response time (GTG)	6.5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07G (8 Bits+FRC) (NTSC 72%)
Horizontal Sync	57 - 62kHz
Viewable area W x H	1650.24 x 928.26mm
Bezel width (sides, top, bottom)	12.8mm, 12.8mm, 12.8mm
Pixel pitch	0.429mm
Bezel colour and finish	black, matte

02 INTERFACES / CONNECTORS / CONTROLS

Digital signal input	HDMI x2 (v.2.0, max. 3840x2160 @60Hz) USB-C x1 (DP Alt, 15W PD)
Monitor control input	RS-232c x1 (2.5mm sub-mini jack) RJ45 (LAN) x1 IR x1 (3.5mm stereo mini)
Audio output	Mini jack x1 (3.5mm) Speakers 2 x 10W
Monitor control output	RS-232c x2 (2.5mm) IR loop through x1 (3.5mm)
HDCP	v.1.4 & 2.0
USB ports	x2 (v.2.0)

03 FEATURES

Integrated software	Android 14 OS, iiSignage², iiControl, iiShare, EShare, FailOver, TeamViewer, PDF & Media Player, iiBrowser, File manager
WiFi	yes (Wifi 5 @ 2.4G/5G)
Hardware	SOC: MT9679, CPU: A73*4, GPU: G52 MC1, RAM: 4GB, ROM: 32GB
Extra	Wall mounting kit included (VESA 500x500mm)
Max. non-stop operating time	24/7
Anti image retention	yes
Media playback	yes

Water and dust protection	IP5X (front)
Housing (bezel)	plastic

04 GENERAL

OSD languages	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL, SV, FI, DA, NB
Control buttons	Power Indicator, Power button, Remote Sensor
User controls	network (status, Wifi, ethernet, hotspot), picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temp., colour control, picture reset), audio (balance, treble, bass, volume, audio out, max. volume, min. volume, mute, audio out sync, speaker setting, audio reset), OSD setting (OSD timeout, OSD H-Position, OSD V-position, OSD transparency, information OSD), general (logo and animation, wallpaper, no signal image, schedule, off timer), screen (zoom mode, custom zoom, system rotation, screen reset), device (power on status, RS232 routing, IR control, power saving, panel saving, monitor info, other), channel (boot on source, rename input channel, auto source switching, signal lost detection, HDMI version), system (language, system update, setting reset, factory reset, Android setting), admin (menu lock, meeting room, HDMI CEC, screen share, Miracast standby, log export)

05 MECHANICAL

Orientation	landscape, portrait
Fanless design	yes
VESA mounting	500 x 500mm
Operation temperature range	0°C - 40°C
Storage temperature range	- 10°C - 60°C
MTBF	50.000 hours (excluding backlight)

06 ACCESSORIES INCLUDED

Cables	power (1.8m), HDMI (1.8m), RS-232c (1.8m)
Guides	quick start guide, safety guide
Other	Wall mount bracket, Wall mount guide, Screws, Screw anchors, Stickers for screw holes
Remote control	yes (batteries included)

07 POWER MANAGEMENT

Energy Star 8.0 (POn at 230V)	147.8W
Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	219W typical, 0.5W stand by, 0.3W off mode

08 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH (UKCA, RoHS2.0, PFOS)

Energy efficiency class (Regulation (EU) 2017/1369)	G
REACH SVHC	above 0.1%: Lead

09 DIMENSIONS / WEIGHT


Product dimensions W x H x D	1679 x 957.1 x 69mm
Box dimensions W x H x D	1840 x 177 x 1112mm
Pallet volume	12pcs
Pallet dimensions W x H x D	1850 x 1072 x 1112mm
Weight (without box)	28kg
Weight (with box)	39.63kg
EAN code	4948570128242

10 EU ENERGY EFFICIENCY LABEL

Manufacturer	iiyama
Visible screen diagonal	189cm; "; (75" segment)
ON mode power consumption	219W
Annual energy consumption	277kWh/annum*
Power in OFF Mode	0.5W off mode

GALLERY





















© IIYAMA CORPORATION. ALL RIGHTS RESERVED