Data sheet

HP L5015tm Touch Monitor

Add a little touch to your business.





Complete your desktop solution with the HP L5015tm Touch Monitor, a durable, interactive touchscreen display in a sleek, thin form factor that integrates easily into your point of sale (POS), hospitality, educational, banking, manufacturing, and kiosk environments.



Efficient, durable touch

Slim, compact design

Interact with the screen with a pen, credit card, finger or fingernail. The Acoustic Pulse Recognition (APR) technology identifies screen taps by sound. The sturdy design is a damage-resistant alternative to earlier film-coated display screens.

Deploy the monitor wherever you need an interactive solution. The small, thin footprint fits in a range of settings, and the stand can be removed for wall-mount setups.¹ Save space and money by eliminating the need for a separate keyboard and mouse.



Keep working with your familiar, established, business-specific applications on the 15-inch diagonal screen that has a 1024 x 768 native resolution² and familiar 4:3 aspect ratio.

Global reassurance

Rest assured that your IT investment is supported by a three-year standard limited warranty. To extend your protection beyond the standard limited warranties, select optional HP Care Pack Services.3

HP L5015tm Touch Monitor

Specifications

-p	
Diagonal size	15-inch
LCD technology	Active matrix TFT LCD with LED backlighting
Aspect ratio	4:3
Active display area	228.1 x 304.1 mm (8.98 x 11.97 in)
Native Resolution	1024 x 768
Colors	16.2 million with FRC technology
Brightness (typical)	with APR touch: 225 nits
Response time	16 msec
Viewing angle (typical)	Horizontal: +/-80° or 160° total Vertical: +/-70° or 140° total
Contrast ratio (typical)	700:1
Dimensions (HxWxD) Dimensions (with stand)	416 x 228 x 455 mm (16.4 x 9.0 x 17.9 inches) 319 x 197 x 358 mm (12.5 x 7.8 x 14.1 inches)
Weight	Unpackaged: 4.3 kg/9.5 lb Packaged: 7.3 kg/16.0 lb
Tilt	-5° to +70° from vertical
Touch interface	USB 2.0
Power supply	Internal AC; optional external DC brick
Temperature	Operating: 32°F to 104°F (0°C to 40°C) Storage: -4°F to -140°F (20°C to 60°C)
Humidity	Operating: 20%-80% Storage: 10%-90%
Operating system compatibility	Windows Embedded 8.1 Industry Pro Retail (32/64-bit) Windows 8.1 Professional (32/64-bit) Windows 7 Professional (32/64-bit) Windows Embedded POSReady 7 (32/64-bit)
Mounting option	100 X 100 VESA mount
Option kit contents	HP L5015tm Touch Monitor, USB 2.0 cable, Power cable, VGA cable, VESA Mounting Adapter, and HP Retail System Software and Documentation CD
Service and support ³	Your HP Peripheral Limited Warranty is a three (3) year parts replacement warranty. Optional HP Care Packs are available to extend your protection beyond the standard limited warranty.

- 1. Mounting hardware sold separately.
- 2. All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
- 3. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit hp.com/go/cpc. HP Services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Sign up for updates hp.com/go/getupdated

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



h