



BP72V60ART2U | EXTENDED BATTERY MODULE



Extend battery runtime for UPS systems during power outages.

The CyberPower BP72V60ART2U rack/tower convertible Extended Battery Module (EBM) for Smart App Online UPS systems OL2200RTXL2U, OL2200RTXL2UN, OL3000RTXL2U, OL3000RTXL2UN, OL3000RTXL2UHV and OL3000RTXL2UHVN extends battery runtimes during power outages. This EBM takes 2U of rack space and can be installed as a tower to match the UPS form factor. It also has a built-in battery charger, providing Fast Charge Technology to quickly restore the backup power supply to full capacity.

Up to ten EBMs can be added to the UPS, and the module's DC plug-and-play power connectors allow for daisy-chaining additional EBMs to a UPS system. The BP72V60ART2U typically has a UPS charging time of 4 hours, regardless of whether one or ten EBMS are installed, and comes with a three-year warranty.

TYPICAL APPLICATIONS

- OL2200RTXL2U
- OL2200RTXL2UN
- OL3000RTXL2U
- OL3000RTXL2UN
- OL3000RTXL2UHV
- OL3000RTXL2UHVN

TYPICAL APPLICATIONS

- Corporate and Enterprise Servers
- Network and Storage Devices
- Edge Closets
- PBX and VoIP Installations

Features

- Output: 72V/60A
- Typical recharge time: 4 hours (0-90%)
- Battery type & quantity: 12V/9AH (12)
- Form factor: Rack/Tower
- Hot swappable: Yes
- Fast Charge Technology: Yes

SPECIFICATIONS

GENERAL

Amperage	60A
DC Voltage	72 VDC


BATTERY

Built-in Charger	Yes
Battery Quantity	12
Typical Charge Time	4 Hours (0-90%)

BATTERY - CONT.

Expansion Ready (Daisy-Chain)	Yes
Battery Size	12 V / 9 Ah
Replacement Battery Cartridge	(2) RB1290X6B
Hot Swappable	Yes
User Replaceable Battery	Yes

BP72V60ART2U | EXTENDED BATTERY MODULE



SPECIFICATIONS - CONT.

PHYSICAL

Rack Size	2U
Mounting Hardware	Included
Enclosure Construction	Steel
Physical Dimensions - (WxHxD) (cm)	43.18 x 8.89 x 59.94 (cm)
Physical Dimensions - (WxHxD) (in)	17 x 3.5 x 23.6 (in)
Physical Dimensions - (WxHxD) (mm)	432 x 89 x 599 (mm)
Weight (kg)	43.91
Weight (lb)	96.8
Shipping Dimensions - (WxHxD) (in)	22.5 x 9.5 x 34.63 (in)
Shipping Dimensions - (WxHxD) (mm)	571.5 x 241.3 x 879.6 (mm)
Shipping - Weight (kg)	53.21
Shipping - Weight (lb)	117.3
Shipping Dimensions - (WxHxD) (cm)	57.15 x 24.13 x 87.96 (cm)

ENVIRONMENTAL

Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Relative Humidity	0% - 90% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5°F to 113°F / -15°C to 45°C
Storage Relative Humidity	0% - 95% non-condensing
Storage Elevation	0-50000 feet (0-15000 meters)

CERTIFICATIONS

Safety	UL 1778 CSA C22.2 NO.107.3 FCC Part 15 Class A
Environmental	RoHS Compliant

WARRANTY

Product Warranty	3 Year Limited Warranty
Extended 2-Year Warranty	WEXT5YR-BP2