

6ft (1.8m) High Speed HDMI Cable with Gripping Connector, Ultra Flexible HDMI Cable, 4K 60Hz/1440p 144Hz w/HDR10/ARC, 18Gbps, High Flex Braided HDMI Cord

Product ID: HDMI2G-FLEX-4K60-6F



Connect the gripping HDMI connector to the display for added retention and a secure connection in conference rooms, hot-desking spaces, and other shared AV environments. The standard HDMI connector remains on the source side for frequent plugging and unplugging, helping reduce unnecessary wear on laptops, docking stations, meeting room PCs, and other source devices. Gold-plated connectors preserve signal integrity, resist corrosion, and are rated for 10,000+ insertions for long-term, reliable use.

Route this HDMI cord easily around corners, behind user workstations, displays, through AV panels, and into concealed or hard-to-access HDMI ports with an ultra-flexible jacket designed for frequent bends and tight installations. The cable combines a ultra-soft, low-memory silicone inner layer with a braided nylon exterior, supporting clean cable runs in enterprise AV racks, conference rooms, workstations, and wall-mounted display setups without compromising durability.

Drive sharp 4K UHD video, fast refresh rates, and high-resolution visuals on UHD displays, workstations, video walls, and AV installations. This flexible High Speed HDMI Cable supports full HDMI 2.0 features:

- Resolutions up to 4K 60Hz using a compatible HDMI source and display
- Supports high refresh rates including 1440p 144Hz and 1080p 240Hz
- 21:9 Aspect Ratio support for cinematic viewing experiences
- High Dynamic Range (HDR10) for higher contrast ratio and vibrant picture quality
- High-Bandwidth Digital Content Protection (HDCP) 2.2 for a secure connection between source and display
- Audio Return Channel (ARC) for sending audio from the TV back to an AV receiver or soundbar
- Up to 32 Uncompressed Digital Audio Channels
- HDMI Ethernet Channel (HEC) for network connectivity over HDMI

- Backward compatible with previous HDMI versions

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Certifications, Reports and Compatibility



Applications

- Help prevent accidental disconnections at the display with a gripping HDMI connector designed for added retention. Ideal for mounted HDMI displays.
- Ensure years of reliable HDMI connectivity with an ultra-flexible cable designed for long-term durability in high-use environments
- Keep an HDMI connection readily available in conference rooms, huddle spaces, and shared AV environments
- Quick ID connector markings and easy-grip strain reliefs simplify cable identification, connection, and removal

Features

- Built to Bend, Made to Last: Ultra-flexible, slim HDMI cable with a dual-layer construction features a soft, low-memory silicone inner jacket and a braided nylon exterior for lasting durability and easy routing in meeting rooms and AV installations
- Deliver Full HDMI Performance: Connect this High Speed HDMI Cable for HDMI 2.0 performance and backward compatibility; Ensure sharp 4K 60Hz video with HDR10, Dolby Vision, HDCP 2.2, 32-ch audio, 7.1 TrueHD, and ARC support
- Secure Display-Side Connectivity: Attach gripping HDMI connector to display for added retention in shared workspaces such as meeting rooms and hot desks; Use standard connector at the source to help reduce wear on PCs, laptops, and docking stations
- Identify Specs Instantly: HDMI spec markings on each Quick ID connector remove guesswork and confirm feature support at-a-glance; Use this flexible HDMI cord in high-density installations where fast cable identification is critical for troubleshooting
- The IT Pro's Choice: Our digital display cables are rigorously lab-tested for signal integrity, durability, and compatibility across HDMI, DisplayPort, USB-C, and legacy interfaces; Backed by free lifetime 24/5 multi-lingual technical assistance

General

UPC 065030929202

Warranty Lifetime

Physical & Environmental

Color	Black & Silver
Material	ABS
Connector Style	Straight
Cable Length	6.0 ft [1.8 m]
Cable OD	0.2 in [4.6 mm]
Product Length	6.1 ft [1.8 m]
Product Width	0.8 in [20.5 mm]
Product Height	0.4 in [11 mm]
Weight of Product	2.3 oz [65 g]
Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	-20C to 70C (-4F to 158F)
Humidity	10%RH ~ 90%RH

Performance

HDR Support	HDR10
Maximum Data Transfer Rate	18 Gbps
Audio Specifications	HDMI - 32 Channel Audio HDMI - 7.1 Channel Audio
Maximum Digital Resolutions	8-bit 4:4:4 Up to 5K 30Hz / 4K 60Hz / 1440p 144Hz / 1080p 240Hz 10-bit 4:4:4 Up to 5K 30Hz / 4K 30Hz / 1440p 75Hz / 1080p 144Hz
Video Revision	HDMI 2.0

Hardware

Active or Passive Adapter	Passive
Connector Plating	Gold
Cable Jacket Material	Silicone with Braided Nylon
Cable Shield Material	Aluminum-Mylar Foil with Braid

Packaging & In-the-Box

Included in Package	1 - Ultra-Flexible HDMI Cable
Package Width	2.4 in [60 mm]
Package Depth	6.2 in [15.8 cm]
Package Height	1.2 in [30 mm]
Shipping (Package) Weight	3.3 oz [92.9 g]

Connector(s)

Connector 1 (Quantity)	1
Connector 1	HDMI
Connector 2 (Quantity)	1
Connector 2	HDMI

****Product appearance and specifications are subject to change without notice.***