

GCL1916WKITU

18.5" Widescreen Short Depth 16-Port LCD KVM Switch w/16x USB KVM Cables




- Integrated LCD KVM console with 18.5" widescreen LCD monitor in a single rail housing with top and bottom clearance for smooth operation in a 1U high system rack
- Integrated 16-port VGA KVM Switch with included cables
- Control up to 128/256 computers by cascading up to 2 levels with IOGEAR's GCS1716
- LCD monitor supports resolution of 1366 x 768 @60Hz
- Short depth design allows for rack-mounting in narrow spaces

16-Port Widescreen Short Depth LCD KVM Switch

IOGEAR's GCL1916WKITU is an integrated LCD console with a 16-port KVM (keyboard, video, and mouse) switch with 16 USB KVM cables that offers secure access to 16 VGA, USB or PS/2 computers. The KVM supports both PS/2 and USB keyboards and mice for the connected computers and supports USB peripheral devices for the attached computers.

- Integrated LCD KVM console with 18.5" widescreen LCD monitor in a single rail housing with top and bottom clearance for smooth operation in a 1U high system rack
- Integrated 16-port VGA KVM Switch with included cables
- Control up to 128/256 computers by cascading up to 2 levels with IOGEAR's GCS1716
- LCD monitor supports resolution of 1366 x 768 @60Hz
- Short depth design allows for rack-mounting in narrow spaces
- Supports VGA video input; supports an external console with USB/VGA connectors
- Built-in USB Type-A port on front panel for peripheral sharing HID devices
- Dual Interface - Supports computers with PS/2 or USB Keyboards and Mice
- Auto PS/2 and USB interface detection
- Keyboard and mouse emulation (PS/2 and USB) for smooth switching and simultaneously booting multiple computers even when the console's focus is elsewhere
- Console lock design enables the console drawer to remain securely locked away in position when not in use
- Computer selection via pushbuttons, hotkeys, and multilingual On Screen Display (OSD)
- Broadcast mode - enables to send commands from the console to all connected computers to perform simultaneous operations
- Two level password security - only authorized users can view and control computers
- Auto Scan Mode - enables continuous monitoring of user-selected computers
- Multilingual keyboard mapping supports English (US), English (UK), French, German, German (Swiss), Hungarian, Italian, Japanese, Korean, Russian, Spanish, Swedish, and Traditional Chinese
- Standard rack mount kit included
- Plug-n-Play
- Firmware Upgradable
- Hot Pluggable





Requirements

Computers:

- VGA, SVGA, or MultiSync video graphics card with an HDB-15 port
- USB or PS/2 mouse and keyboard ports (6-pin mini DIN) or 1 USB port

Package Contents

- 1 x 16-Port 18.5" Widescreen Short Depth LCD KVM Switch
- 8 x USB KVM Cable (6ft - G2L5202U)
- 8 x USB KVM Cable (10ft - G2L5203U)
- 1 x PS/2 KVM Cable
- 1 x Firmware Upgrade Cable
- 1 x Grounding Wire
- 1 x Standard Rackmount Kit
- 1 x Power Cord
- 1 x Quick Start Guide

Specifications

Function	GCL1916WKITU	Dimensions	GCL1916WKITU
Computer Connections		Physical Properties	
Direct	16	Case Qty	1
Daisy Chain or Cascading	256	Case Weight	43.0 lb.
Port Selection	OSD, Hotkeys, Pushbuttons	Case Dimension	30.3x 37.3x 6.5 in.
Connectors			
Computer/KVM	16 x SPHD-18 Male		
USB-A	1 x USB Type A Female		
Power	1 x 3-Prong AC Socket		
Switches			
Reset	1 x Semi-recessed Pushbutton		
Power	1 x Rocker Switch		
FW Upgrade	1 x Slide Switch		
LCD Power	1 x LED Pushbutton (Orange)		
LCD Adjustment	4 x Pushbutton		
Port Selection	16 x Pushbutton		
LEDs			
On Line	16 (Orange)		
Power On	Dark Green		
Emulation			
Keyboard	PS/2, USB		
Mouse	PS/2, USB		
Video Resolution	1366x768@60Hz		
Scan Interval	1 - 255 seconds		
Power Input Rating			
Per AC Power Inlet, 50/60Hz	100~240VAC, 50/60Hz, 1A		
Power Consumption	110V: 14.1W; 70BTU		
Environment			
Operation Temperature	0~40°C		
Storage Temperature	-20~60°C		
Humidity	0~80% RH; Non-condensing		
Housing			
Case	Metal and Plastic		