

4XEM's 65W Wall Charger Triple Output - Black

4XEM Part- 4XGAN00165WB



4XEM's 65W USB-C offers amazing charging power and speed with three USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming the standard for charging devices, allowing for up to 65W of charging power. This device features 2x USB-C ports and 1x USB-A port. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C and-A GaN Charger.

Problem it solves: Charge up to three USB devices with reliable power and speed.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features:

- 65-Watt power budget
- 2x USB-C port
- 1x USB-A port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging



## Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging

**4XEM Products Are Available At Your Favorite Online Retailers**





**DATA SHEET**

Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s)	2x USB Type-C Female 1x USB Type-A Female
	Power Source	Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Retractable Prongs
Performance	Industry Standards Certifications	USB-PD 3.0 CE ROHS ETL CB KC PSE
Physical Characteristics	Colour	Black
	Display	Yes
	LED Indicator(s)	Power: Aqua
	Power Cable Length	N/A
	Product Height	1.59 in [40.3 mm]
	Product Width	1.33 in [33.7 mm]
Product Length		3.00 in [76.2 mm]
		3.63 in [92.1 mm] (with power prongs out )
Weight of Product		4.44 oz [126 g]
Power	Total Power Budget	65W
	Power Delivery	65W Max
	Input Voltage	100-240VAC, 50Hz-60Hz @ 1.5A
	Output Voltage (C1/C2)	65W: 5/9/12/15V 3A, 20V 3.25A
	Output Voltage (USB-A)	60W: 3.4-5.5V 5A ,5/9/12/20V 3A
	Output Voltage (C1) + (C2)	63W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 18W:
	Output Voltage (C1) + (USB-A)	5V 3A, 9V 2A, 12V 1.5A
	Output Voltage (C2 + USB-A)	63W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 18W:
	Output Voltage (C1) + (C2 + USB-A)	5V 3A, 9V 2A, 12V 1.5A 24W MAX - 5V 4.8A (Shared) 60W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 15W: 5V 3A (Shared)
Environmental	Operating Temperature	32°F to 104°F [0°C to 40°C]
	Storage Temperature	-4°F to 176°F [-20°C to 80°C]
	Humidity	5% to 90% (non-condensing)
Packaging Information	Package Type	Poly-Bag
	Package Height	5.00 in [127.0 mm]
	Package Width	3.00 in [76.2 mm]
	Package Length	1.33 in [33.9 mm]
	Shipping (Package) Weight	4.52 oz [128 g]
What's in the Box	Included in Package	1x 65W Dual USB-C + USB-A GaN Charger
Notes	Notes	

\* Product appearance and specifications are subject to change without notice.  
\* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    tschaus@4xem.com**

