40M IR MOTORIZED VF BULLET CAMERA

I4-340IP5MVF+



4MP | ICR | H.265 | 0 Lux Minimum Illumination | ONVIF | WDR | 3D-DNR

BLC | HLC | Motion Detection | Analytics | 40M View | PoE | Local Storage

I/O | Two Way Audio | IP66 Protection Rating | DDNS | CMS | Internet Monitoring | Mobile

- 1/3" CMOS Sensor
- 4 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR / BLC / HLC
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- Analytics Support
- 3.3-12mm Motorized Lens with Auto-Focus
- 40m IR Illumination
- PoE Support
- Local Storage
- RS-485
- I/O
- 2 Way Audio
- Technician Port
- IP 66 Protection

Specifications

Camera	Video	Model	I4-340IP5MVF+
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (HFR* Disabled) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
		Analytics	Pro Level
Compression		Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)
		Resolution	4MP(2560x1440), 3MP(2048×1536), 1080P, 720P, D1, CIF ,480x240
		Multi-Stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)
		Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

Housing	IR Distance	40m (48 IR LED)
	Lens	3.3-12mm Motorized with Auto-Focus
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis
	Dimensions	Φ109mm×284mm
	Weight(gross)	1115g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS(BNCx1)
	Mic Connectivity	1Ch Input, 1Ch Output
	SD Card	Support Event recording over TF (128GB Max)
	RS485	Yes
	Alarm	1Ch Input, 1Ch Output
Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1X, Multicast, QoS
	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~600mA / PoE/~8.5W
	Work Environment	-30℃~50℃, 10%~90% Humidity

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.





