NL-822MP EVA-M8Q MD6 Serial PPS Multi GNSS Receiver u-blox 8 5 m

Description

The MD6 serial multi GNSS Receiver based on u-blox 8 chipset has a built-in antenna for high sensitivity. You can use this GNSS Receiver with a laptop and a suitable routing software for navigation. The MD6 universal connector enables the connection of optional USB or serial connecting cables. The NL-822MP GNSS receiver can be installed onto different vehicle roofs (car, truck, bus etc.) by using the included installation material. Thus it can perfectly fit into the vehicle concept, due to its design.



Item no. 62022

EAN: 4043619620227

Country of origin: Taiwan, Republic of China

Package: Retail Box

Technical details

- Connector: MD6 Navilock plug (USB or serial cable are optional available)
- Chipset: u-blox 8 EVA-M8Q
- Frequency:
  GPS: L1, 1575.4200 MHz
  GLONASS: L1, 1602 (k x 0.5625) MHz
  BEIDOU COMPASS: B1, 1561.0980 MHz
  GALILEO: E1, 1575.4200 MHz
  QZSS: L1, 1575.4200 MHz
- Accepts the signals of up to 72 satellites at the same time
- Supports AssistNow online / offline, SBAS (WAAS, EGNOS, QZSS and MSAS)
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
- Auto Baud Rate up to 115200 bps (9600 bps default)
- PPS signal on pin 6 (LVTTL 3.3 V)
- Update rate:
  single GNSS: 18 Hz (e.g. GPS solo)
  multi GNSS: 10 Hz (e.g. GPS+GLONASS)
- Sensibility: max. -164 dBm
- Protection class: IPX7
- Operating temperature: -10 °C ~ 50 °C
- Power supply: 5 V DC
- Current consumption: max. 45 mA
- Cold start in ca. 26 seconds

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Navilock. All rights reserved.**

- Hot start in ca. 1 second
- Positioning accuracy: 2.5 m CEP (Circular Error Probable) and 2 m CEP with SBAS
- Cable length: ca. 5 m
- Dimensions (Ø x H without screw thread): ca. 62 mm x 21 mm

System requirements

- Android 10.0 or above
- Chrome OS 90.0 or above
- Linux Kernel 5.8 or above
- Windows 10/10-64/11
- MD6 connection cable

Package content

- MD6 serial receiver
- Mounting material:
  Nut
  Washer
  Toothed washer
  Heat shrink tube

Images





All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Navilock. All rights reserved.**

General

Protection class:	IPX7
Suitable for outdoor:	yes

Interface

Connector:	1 x MD6 plug

Technical characteristics

Operating voltage:	5 V
Chipset:	u-blox 8 EVA-M8Q
Frequency range:	BEIDOU: B1, 1561.0980 MHz QZSS L1, 1575.4200 MHz GALILEO: E1 1575.4200 MHz GPS: L1, 1575.4200 MHz GLONASS: L1, 1602 (k x 0.5625) MHz
Operating temperature:	-10 °C ~ 50 °C
Polarisation:	RHCP
Current consumption:	45 mA
Sensitivity:	-164 dBm
Update rate:	up to 18 Hz

Physical characteristics

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Navilock. All rights reserved.**

Housing colour:	white
Cable colour:	black
Cable length incl. connectors:	5 m

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@navilock.de
Website	www.navilock.de

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Navilock. All rights reserved.**