

Key Features

- 2nd generation laser phosphor technology with up to 30,000 hours lifespan
- 5,000 ANSI Lumens
 offering bright images in
 any environment
- Up to 300" ultra large screen with lower cost-perinch
- Installation flexibility: V lens shift, 1.6x optical zoom, H/V keystone
- Versatile application: 360° projection, portrait mode



Product **Description**

The Luminous Superior series is ViewSonic's lamp-free high brightness lineup for both commercial and educational spaces. The LS751HD adopts industry-leading 2nd generation laser phosphor technology and delivers 5,000 ANSI Lumens while eliminating the use of toxic mercury, reducing the cost and effort of frequent lamp replacement and lowering the total cost of ownership. The lamp-free light source offers enhanced sustainability for a greener environment while delivering up to 300" large images with 1080p high resolution and vivid colors no matter if you're in a boardroom, lecture hall, or public space. The projector boasts high installation flexibility with vertical lens shift, 1.6x optical zoom, easy image adjustment with H/V keystone and 4 corner correction, and diverse applications with 360° projection and portrait mode. The LS751HD also comes with HDMI 2.0b, ensuring access to original 4K quality content with HDR/HLG supported.





Visit Us

www.viewsonic.com

SPECIFICATION		OTHERS	
Native Resolution:	1920x1080	Power Supply Voltage:	100-240V+/- 10%,
Brightness:	5000 (ANSI Lumens)		50/60Hz (AC in)
Contrast Ratio:	3000000:1	Power Consumption:	Normal: 245W Standby: <0.5W
Display Color:	1.07 Billion Colors	Operating Temperature:	0~40°C
Light Source Type:	Laser Phosphor	Carton:	Brown
Light Source Life (hours) with Normal Mode:	20000	Net Weight:	4.5kg
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Gross Weight:	6.6kg
Lens:	F=2.5-3.26, f=20.911- 32.62mm	Dimensions (WxDxH) with Adjustment Foot:	337x265x131.5mm
Projection Offset:	136%+/-5%	Packing Dimensions: OSD Language:	496x195x387mm
Throw Ratio:	1.4~2.24		English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Norwegian/Danish, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Farsi. Vietnamese, Indonesian, Romanian, Slovakian, total 27 languages
Optical Zoom:	1.6X		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	0.93-14.88m (100"@3.10m)		
Keystone:	H:+/-30°, V:+/-30°		
Lens Shift V. Range:	+0%, -18%		
Audible Noise (Normal):	32dB		
Audible Noise (Eco):	29dB	User Guide Language:	English, S-Chinese, T- Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Input Lag:	49.9ms		
Resolution Support:	VGA(640 x 480) to 4K UHD(3840 x 2160)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD		
Horizontal Frequency:	15K-102KHz	STANDARD ACCESSORY	
Vertical Scan Rate:	23-120Hz	Power Cord:	1
INPUT		Remote Control:	1
HDMI:	2 (HDMI 2.0/ HDCP 2.2 HDMI 1.4/ HDCP 1.4)	QSG:	Yes
		Warranty Card:	Yes (CN Only)
OUTPUT		OPTIONAL ACCESSORY	
Audio-out (3.5mm):	1	Wall/Ceiling Mount:	PJ-WMK-007
Speaker:	15W x2		
USB Type A (Power):	1 (5V/1.5A)		
CONTROL			
RS232 (DB 9-pin male):	1		
RJ45 (LAN control):	1		
	1		

USB Type A (Services): (share with USB A Output)