Overview

HP EliteBook 1040 G4 Notebook PC



Front

- Internal microphones (2)
- 2. Webcam and IR Camera
- 3. Webcam LED
- 4. Fingerprint reader
- 5 Glass clickpad

- 6. Audio combo jack
- 7. USB 3.1 Gen 1 charging port
- 8. Power button
- 9. Nano Security Lock Slot (Lock sold separately)



Overview



Rear

- 1. USB Type-C™ with Thunderbolt™
- 2. USB Type-C™ with Thunderbolt™
- 3 USB 3.1 Gen 1 charging port

- 4 HDMI port (Cable not included.)
- 5 WWAN SIM with plug (Plug is removable only for units with optional WWAN



Overview

At a Glance

- Natural silver CNC Aluminum chassis with diamond cut design
- Choice of 7th Generation Intel® Core™ i5, i7 Processors with integrated Intel® HD Graphics
- Display include your choice of 35.56 cm (14") diagonal IPS Wide viewing Angle, FHD or UHD, Touch or Non-Touch
- Get added protection in open or public places with the optional HP Sure View integrated privacy screen
- Passed 12 MIL-STD 810G testing, plus an additional 120,000 hours of reliability testing through HP's Total Test Process¹
- Never forget your password with your choice of simple authentication methods, including the IR camera for face recognition and Touch Fingerprint Sensor compatible with Windows Hello
- Weight starting at 2.99 lbs (1.36 kg)
- Height starting at of 15.95 mm
- Supports wireless LAN and wireless WAN options for connectivity on the go
- HP (67 WHr) Battery life up to 18 hrs
- Up to 1 TB Solid State Drives
- Up to 16 GB total system memory
- Engage teams, clients, and vendors with the best in class audio by Bang & Olufsen and the high-performance HP Premium Collaboration Keyboard
- MIL-STD-810G testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Features

PRODUCT NAME

HP EliteBook 1040 G4 Notebook PC

OPERATING SYSTEMS

Preinstalled Windows 10 Pro 64 – HP recommends Windows 10 Pro. ²

Windows 10 Home 64 2

Windows 10 Home Single Language 64 ²

FreeDOS 2.0 NeoKylin Linux® 64

2. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See http://www.windows.com/.

PROCESSORS

Intel® Core™ i7-7820HQ with Intel® HD Graphics 630 (2.9 GHz, up to 3.9 GHz with Intel Turbo Boost Technology, 8 MB cache, 4 cores) ^{3,4,5}

Intel® Core™ i7-7600U with Intel HD Graphics 620 (2.9 GHz, up to 3.9 GHz with Intel Turbo Boost Technology, 4 MB cache, 2 cores) 3,4,5

Intel® Core™ i7-7500U with Intel HD Graphics 620 (2.9 GHz, up to 3.9 GHz with Intel Turbo Boost Technology, 4 MB cache, 2 cores) 3,4,5

Intel® Core™ i5-7300U with Intel HD Graphics 620 (2.6 GHz, up to 3.5 GHz with Intel Turbo Boost Technology, 3 MB cache, 2 cores) 3,4,5

Intel® Core™ i5-7200U with Intel HD Graphics 620 (2.5 GHz, up to 3.1 GHz with Intel Turbo Boost Technology, 3 MB cache, 2 cores) ^{3,4,5}

- 3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a measurement of higher performance.
- 4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
- 5. **NOTE:** In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on http://www.support.hp.com.

CHIPSET

Integrated with processor



Features

GRAPHICS

Integrated

Intel® HD Graphics 6306 Intel® HD1 Graphics 620 with shared video memory6

6. HD content required to view HD images.

DISPLAY

Internal

HP Sure View integrated privacy screen 35.56 cm (14") diagonal FHD IPS eDP LED backlit touch screen, 700 cd/m2, 100% sRGB with Corning® Gorilla® Glass 4, privacy screen, camera and WWAN (1920 x 1080) 6,7

35.56 cm (14") diagonal FHD IPS eDP LED-backlit touch screen, 340 cd/m2, 100% sRGB, direct bonded with Corning® Gorilla® Glass 4 and camera (1920 x 1080) 6,7

35.56 cm (14") diagonal FHD IPS eDP LED-backlit touch screen, 340 cd/m2, 100% sRGB, direct bonded with Corning® Gorilla® Glass 4, camera and WWAN (1920 x 1080) 6,7

35.56 cm (14") diagonal 4K IPS eDP LED-backlit touch screen, 400 cd/m2, 100% sRGB, direct bonded with Corning® Gorilla® Glass 4, camera and WWAN (3840 x 2160) 6,7

HP Sure View integrated privacy screen 35.56 cm (14") diagonal FHD IPS eDP antiglare LED-backlit, 700 cd/m2, 100% sRGB with camera and WWAN (1920 x 1080) 6,7

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit, 340 cd/m2, 100% sRGB with camera (1920 x 1080^{6.7}

35.56 cm (14") diagonal FHD UWVA eDP anti-glare LED-backlit, 340 cd/m2, 100% sRGB with camera and WWAN (1920 x $1080^{6.7}$

35.56 cm (14") diagonal 4K UWVA eDP anti-glare LED-backlit, 400 cd/m2, 100% sRGB with camera and WWAN (3840 x 2160) $^{6.7}$

Size (imperial)

14"

Size (metric)

35.56m

- HD content required to view HD images.
- 7. Resolutions are dependent upon monitor capability, and resolution and color depth settings.



Features

STORAGE AND DRIVES

M.2 (NGFF) 2280 Solid State Drive 128 GB SATA-3 SS TLC⁸ 256 GB PCIe Gen 3x4 NVMe SS TLC⁸ 256 GB SATA-3 SS TLC (Opal 2) ⁸ 360 GB PCIe Gen3x4 SS TLC (Intel) ⁸ 512 GB PCIe Gen3x4 NVMe SS TLC⁸ 360 GB M.2 PCIe Gen 3x4 TLC SSD⁸ 512 GB PCIe Gen3x4 NVMe SS MLC⁸ 1 TB PCIe Gen3x4 NVMe SS TLC⁸

8. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for windows 10) is reserved for system recovery software.

MEMORY

8 GB DDR4-2133 SDRAM 16 GB DDR4-2133 SDRAM

Configurations

Memory soldered down System runs at 2133 Supports Dual Channel Memory **Maximum** 16 GB DDR4-2133 SDRAM

NETWORKING/COMMUNICATIONS

WLAN

Intel Dual band wireless-AC 8265 802.11AC 2x2 WiFi + BT 4.2 Combo Adaptor⁸ Compatible with Miracast-certified devices (models with Windows 10)⁹

NFC

NFC Mirage module (NXP NPC300 I2C 10mmx17mm)

WWAN

Foxconn HP It4120 LTE/EVDO/HSPA+ w/GPS M.2¹⁰ Huawei HP It4132 - LTE/HSPA+ w/GPS M.2¹⁰ Fibocom HP hs3210 WW HSPA+ w/o GPS¹⁰ "No WWAN" option

- Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.
 The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.
- 10. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming media players that also support Miracast. You can use Miracast to share what you're doing on your PC and present a slide show. For more information:
 - http://windows.microsoft.com/en-us/windows-8/project-wireless-screen-miracast.



Features

11. WWAN module is optional, must be configured at the factory and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

AUDIO/MULTIMEDIA

Audio

Audio by Bang & Olufsen; Digital dual-array microphone Integrated premium speakers

Camera

IR camera for face authentication with Windows Hello¹²

Webcam

720p HD webcam⁶

- 6. HD content required to view HD images.
- 12. Internet access required.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full size HP Premium Collaboration Keyboard Backlit DuraKeys Spill-resistant

Pointing Device

Clickpad with image sensor and glass surface, multi-touch gestures enabled, taps enabled as default.

SOFTWARE AND SECURITY

Software

Native Miracast Support¹⁰
HP LAN-Wireless Protection
HP Wireless Wakeup
HP Sure Connect
HP 3D DriveGuard
HP ePrint + JetAdvantage ¹¹



Features

HP Hotkey Support

HP Recovery Manager

HP Jumpstart

HP Support Assistant¹²

HP Noise Cancellation Software

Buy Office

Bing Search

Manageability Features

HP Driver Packs13

HP System Software Manager (SSM)

HP BIOS Config Utility (BCU)

HP Client Catalog

HP Management Integration Kit for Microsoft System Center Configuration Manager¹⁴

LANDESK Management¹⁵

Security Management

HP BIOSphere Gen3¹⁶

HP DriveLock & Automatic DriveLock

BIOS Update via Network

HP Sure Start Gen3

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)

SATA 0,1 port disablement (viaBIOS)

RAID configurations

Serial, USB enable/disable (viaBIOS)

Power-on password (viaBIOS)

Setup password (viaBIOS)

Support for chassis padlocks and cable lock devices

Integrated hood sensor

Absolute Persistence Module 17

HP Client Security Suite Gen 3 [HP Security Manager (HP Credential Manager, HP Password Manager, HP Spare Key), HP Power On Authentication, HP Device Access Manager¹⁸

Microsoft Defender¹⁹

HP Sure Click

- 10. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming media players that also support Miracast. You can use Miracast to share what you're doing on your PC and present a slide show. For more information: http://windows.microsoft.com/en-us/windows-8/project-wireless-screen-miracast.
- 11. HP ePrint Drive requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hp.com/go/eprintcenter). Print times and connection speeds may vary.
- 12. HP Support Assistant requires Windows and Internet access.
- 13. HP Driver Packs not preinstalled, however available for download at http://www.hp.com/go/clientmanagement.



Features

- 14. HP Management Integration Kit can be downloaded from http://www8.hp.com/us/en/ads/clientmanagement/overview.html.
- 15. LANDESK Management subscription required.
- 16. HP BIOSphere Gen3 requires Intel® 7th or 8th Generation processors
- 17. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: http://www.absolute.com/company/legal/agreements/ computrace-agreement. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
- 18. HP Client Security Suite Gen3 requires Windows and Intel® or AMD 7th or 8th Generation processors.
- 19. Microsoft Defender Opt in and internet connection required for updates.

POWER

Power Supply

65 W USB Type-C[™] AC adapter²⁰ 90 W USB Type-C[™] AC adapter²⁰

Primary Battery

HP Long Life 6-cell, 67 Wh Li-ion^{21,22}

NOTE: Battery is internal and not replaceable by customer.

Power Cord

65W USB-Type C[™], Duckhead Power Cord Length: 1.0m 90W USB-Type C[™], Duckhead Power Cord Length: 1.0m

Battery life

Up to 18 hours²³

- 20. Availability may vary by country.
- 21. Supports HP Fast Charging with 90W only
- 22. Battery is internal and not replaceable by customer. Serviceable by warranty.
- 23. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

WEIGHTS & DIMENSIONS

Weight

Starting at 2.99 lbs²⁴ Starting at 1.35 kg²⁴

Dimensions (w x d x h)

12.95 x 9.17 x 0.63 in 32.89 x 23.28 x 1.59 cm



Features

24. Weight will vary by configuration.

PORTS/SLOTS

2 USB Type-C[™] with Thunderbolt[™]
2 USB 3.1 Gen 1 Charging
1 HDMI 1.4²⁵
1 headphone/microphone combo
Nano Security Lock Slot (Lock sold separately)

25. HDMI 1.4 cable sold separately.

ENVIRONMENTAL & INDUSTRY

| Environmental Data | Eco-Label Certifications & declarations | This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: IT ECO declaration US ENERGY STAR® US Federal Energy Management Program (FEMP) EPEAT® Gold registered in the United States. See http://www.epeat.net for registration status in your country. Search keyword <i>generator</i> on HP's 3rd party option store for solar energy accessory at http://www.hp.com/go/options. TCO or TCO Certified Edge | | | |
|-----------------------|--|---|---|--------------|--|
| | System Configuration | | r the Energy Consumption ar tebook model is based on a " | | |
| | Energy Consumption (in accordance with US ENERGY STAR® test method) | 115VAC, 60Hz | 230VAC, 50Hz | 100VAC, 50Hz | |
| | Normal Operation (Sort idle) | 7.04 W | 6.99 W | 6.99 W | |
| | Normal Operation (Long idle) | 3.28 W | 3.39 W | 3.33 W | |
| | Sleep | 0.87 W | 0.87 W | 0.88 W | |
| | Off | 0.52 W | 0.52 W | 0.52 W | |
| | | Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. | | | |
| | Heat Dissipation* | 115VAC, 60Hz | 230VAC, 50Hz | 100VAC, 50Hz | |
| | Normal Operation (Short idle) | 24 BTU/hr | 24 BTU/hr | 24 BTU/hr | |



Features

| Normal Operation (Long idle) | 11 BTU/hr | 11 BTU/hr | 11 BTU/hr |
|------------------------------------|--|---|-------------------------------|
| Sleep | 3 BTU/hr | 3 BTU/hr | 3 BTU/hr |
| Off | 2 BTU/hr | 2 BTU/hr | 2 BTU/hr |
| | *NOTE: Heat dissipation is service level is attained fo | | neasured watts, assuming the |
| Declared Noise | Sound Power | | Sound Pressure |
| Emissions | (L _{WAd} , bels) | | (L _{pAm} , decibels) |
| (in accordance with | , ,, | | |
| ISO 7779 and ISO 9296) | | | |
| Typically Configured – Idle | 2.6 | | 15 |
| Fixed Disk – Random writes | 2.6 | | 15 |
| Longevity and Upgrading Batteries | This product can be upgraded, possibly extending its useful life by severa Upgradeable features and/or components contained in the product may in a USB ports 1 PC card slot (type I/II) 1 ExpressCard/54 slot 1 IEEE 1394 Port 2 SODIMM memory slots Optional expansion base docking station 1 multi-bay II storage port Interchangeable HDD?? Spare parts are available throughout the warranty period and or for up to years after the end of production. | | |
| batteries | This battery(s) in this prod Batteries used in the prodice Mercury greater the 1 produced for the 1 produce | uct do not contain: opm by weight n 20ppm by weight 32 (coin cell) | |



Features



Features

| Packaging Usage | HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards. |
|--|---|
| End-of-life Management and Recycling | Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment. |
| HP, Inc. Corporate Environmental Information | For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications http://www8.hp.com/us/en/hp- information/environment/ecolabels.html ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755 842 and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf |



Features

SERVICE AND SUPPORT

HP Services offers a 1-year limited warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Long Life batteries will have same warranty as the platform. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc.28

26. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

CERTIFICATION AND COMPLIANCE

ENERGY STAR® certified EPEAT® Gold²⁷

27. EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.



Technical Specifications

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Panel LCD 14 inch FHD (1920x1080) Anti-Glare WLED UWVA 72percent cg 340nits eDP 1.3 + PSR ultraslim 2.4mm NB Outline Dimensions (W x H x D) 315.41 x 196.17 max. (w/ PCB)

Active Area 309.37 x 174.02 (mm)

Weight 225 g max
Diagonal Size 14.0 (inch)
Surface Treatment Anti-Glare (AG)

Touch enabled Yes

Contrast Ratio 600:1 (typical)

Refresh Rate 60 Hz Brightness 340 nits

Pixel Resolution

Format RGB

Configuration 1920 x 1080 (FHD) Interface eDP 1.3 + PSR

LCD Mode

PPI 157

Viewing Angle UWVA 85/85/85

Panel LCD 14 inch UHD (3840x2160) Anti-Glare WLED UWVA 72percent cg 400nits eDP 1.3 + PSR ultraslim N.B. Outline Dimensions (W x H x D) 315.31 x 199.54 (mm) max (w/ PCB)

Active Area 309.31 x 173.99 (mm)

Weight 240 g max
Diagonal Size 14.0 (inch)
Surface Treatment Anti-Glare (AG)

Touch enabled Yes

Contrast Ratio 1200:1 (typical)

Refresh Rate 60 Hz Brightness 400 nits

Pixel Resolution

Format RGB

Configuration 3840 x 2160 (UHD) Interface eDP 1.3 + PSR

LCD Mode

PPI 315

Viewing Angle UWVA 85/85/85



Technical Specifications

ENVIRONMENTAL & INDUSTRY

ENVIRONMENTAL DATA HP ELITE X2 1012 G2

| within the model family. HP computers marked with the ENERGY STAR® Logo a compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is f a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. Heat Dissipation* | Environmental Data | Eco-Label Certifications & declarations System Configuration | This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: • IT ECO declaration • US ENERGY STAR® • US Federal Energy Management Program (FEMP) • EPEAT® Gold registered in the United States. See http://www.epeat.net for registration status in your country. Search keyword generator on HP's 3rd party option store for solar energy accessory at http://www.hp.com/go/options. • TCO or TCO Certified Edge The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured" | | | | |
|--|-----------------------|---|--|----------------|---------------|---|--|
| Normal Operation (Sort idle) Normal Operation (Long idle) Sleep 0.87 W 0.87 W 0.88 W Off Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offer within the model family. HP computers marked with the ENERGY STAR® Logo a compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® compliant configurations, then energy efficiency data listed is f a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. Heat Dissipation* 115VAC, 60Hz 230VAC, 50Hz Normal Operation (Short idle) Normal Operation (Long in 11 BTU/hr idle) Sleep 3 BTU/hr 24 BTU/hr 24 BTU/hr 25 BTU/hr 27 BTU/hr 3 BTU/hr 3 BTU/hr 3 BTU/hr 2 BTU/hr 2 BTU/hr 3 SETU/hr 2 BTU/hr 3 SETU/hr 2 SETU/hr 2 SETU/hr 3 SOUND Pressure | | (in accordance with US ENERGY STAR® test | | 230VAC | ., 50Hz | 100VAC, 50Hz | |
| Normal Operation (Long idle) Sleep | | Normal Operation (Sort | - | | | | |
| Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offer within the model family. HP computers marked with the ENERGY STAR® Logo a compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is f a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. Heat Dissipation* | | Normal Operation (Long | 3.28 W | 3.39 |) W | 3.33 W | |
| Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offer within the model family. HP computers marked with the ENERGY STAR® Logo a compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is f a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. Heat Dissipation* | | Sleep | 0.87 W | 0.87 | ' W | 0.88 W | |
| Energy efficiency data listed is for an ENERGY STAR® compliant product if offer within the model family. HP computers marked with the ENERGY STAR® Logo a compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is f a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. Heat Dissipation* 115VAC, 60Hz 230VAC, 50Hz Normal Operation (Short idle) Normal Operation (Short idle) Normal Operation (Long idle) Sleep 3 BTU/hr 11 BTU/hr 11 BTU/hr 11 BTU/hr 3 BTU/hr 2 BTU/hr 2 BTU/hr *NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour. Declared Noise Sound Power Sound Pressure | | Off | 0.52 W | 0.52 | 2 W | 0.52 W | |
| Normal Operation (Short idle) Normal Operation (Long 11 BTU/hr 11 BTU/hr 11 BTU/hr idle) Sleep 3 BTU/hr 3 BTU/hr 3 BTU/hr 3 BTU/hr Off 2 BTU/hr 2 BTU/hr 2 BTU/hr 2 BTU/hr *NOTE: Heat dissipation is calculated based on the measured watts, assuming service level is attained for one hour. Declared Noise Sound Power Sound Pressure | | Heat Dissipation* | Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system. | | | | |
| idle) Normal Operation (Long idle) Sleep 3 BTU/hr 3 BTU/hr 3 BTU/hr Off 2 BTU/hr 2 BTU/hr 2 BTU/hr *NOTE: Heat dissipation is calculated based on the measured watts, assuming service level is attained for one hour. Declared Noise Sound Power Sound Pressure | | • | | | | | |
| Normal Operation (Long idle) Sleep 3 BTU/hr 3 BTU/hr 3 BTU/hr Off 2 BTU/hr 2 BTU/hr 2 BTU/hr 2 BTU/hr *NOTE: Heat dissipation is calculated based on the measured watts, assuming to service level is attained for one hour. Declared Noise Sound Power Sound Pressure | | | 24 010/111 | 2701 | 5 /111 | 27 010/111 | |
| Off 2 BTU/hr 2 BTU/hr 2 BTU/hr 2 BTU/hr *NOTE: Heat dissipation is calculated based on the measured watts, assuming to service level is attained for one hour. Declared Noise Sound Power Sound Pressure | | Normal Operation (Long | 11 BTU/hr | 11 BT | U/hr | 11 BTU/hr | |
| *NOTE: Heat dissipation is calculated based on the measured watts, assuming to service level is attained for one hour. Declared Noise Sound Power Sound Pressure | | | | | | 3 BTU/hr | |
| | | Off | *NOTE: Heat dissipation is o | calculated bas | | ' | |
| | | Deslayed Noise | Cound Decree | | | Cound Droccure | |
| FMICCIONC (Line hale) (Line docibale) | | Declared Noise Emissions | Sound Power (L _{WAd} , bels) | | | Souna Pressure (L _{pAm} , decibels) | |



Technical Specifications

| (in accordance with | | | | |
|--------------------------------|---|-----------------------------------|-------------------------------|--|
| Typically Configured – | | 2.6 | 15 | |
| Idle Fixed Disk – Random | | 2.6 | 15 | |
| writes Longevity and Upgrading | Just por Just por Period Express IEEE 139 Sodim Optional 6 Imulti-bit Interchan | slot (type I/II) Card/54 slot | ntained in the product may in | clude: |
| Batteries | This battery(s) in this product comply with EU Directive 2006/66/EC Batteries used in the product do not contain: Mercury greater the1ppm by weight Cadmium greater than 20ppm by weight Battery description: CR2032 (coin cell) Battery type: Lithium Battery description: 6-cell high capacity Lithium-Ion battery (optional 8 cell available) Battery type: | | | |
| Additional Information | This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC. This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). This product is in compliance with the IEEE 1680 (EPEAT) standard at < Gold > level, see www.epeat.net Plastics parts weighing over 25 grams used in the product are marke per IS011469 and IS01043. This product contains 0.0% post-consumer recycled plastic (by wt.) This product is 93.6% recycle-able when properly disposed of at end life. | | | e of 6). d at the rked t.) |
| Packaging Materials | External: | PAPER/Corrugated | 3 | 840 g |
| | Internal: | PLASTIC/Polyethylene low der | • | 9 g |
| | | PLASTIC/Polyethylene Expand | ed - EPE 5 | 52 g |
| | | | | |
| | | packaging material contains at le | | |



Technical Specifications

| Material Usage | This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf): Asbestos Certain Azo Colorants Certain Brominated Flame Retardants – may not be used as flame retardants in plastics Cadmium Chlorinated Hydrocarbons Chlorinated Paraffins Formaldehyde Halogenated Diphenyl Methanes Lead carbonates and sulfates Lead and Lead compounds Mercuric Oxide Batteries Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. Ozone Depleting Substances Polybrominated Biphenyls (PBBs) Polybrominated Biphenyl Ethers (PBBEs) Polybrominated Biphenyl Oxides (PBBOs) Polychlorinated Biphenyl (PCB) Polychlorinated Terphenyls (PCT) Polyvinyl Chloride (PVC) – except for wires and cables, has been voluntarily removed from most applications. Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO) |
|---------------------------------------|--|
| Packaging Usage | HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards. |
| End-of-life Manageme and Recycling | Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This |



Technical Specifications

| | information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers . These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment. |
|-------------------------------------|--|
| HP, Inc. Corporate Environmental | For more information about HP's commitment to the environment: |
| Information | Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications http://www8.hp.com/us/en/hp- information/environment/ecolabels.html ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755 842 and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf |

STORAGE AND DRIVES

HARD DRIVES

SSD 128GB 2280 M2 SATA-3 Drive Weight 0.02 lb (10 g)

Capacity 128GB

Height0.09 in (2.3 mm)Width0.87 in (22 mm)InterfaceATA-8, SATA 3.0

Performance

Maximum Sequential Read Up To 520 MB/s
Maximum Sequential Write Up To 450 MB/s
Logical Blocks 250,069,680

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features DIPM; TRIM; DEVSLP

SSD 1TB 2280 PCle-3x4 NVMe TLC Drive Weight 0.02 lb (10 g)
Capacity 1024GB

Height 0.09 in (2.3 mm)
Width 0.87 in (22 mm)
Interface PCIe NVMe Gen3X4

Performance

Maximum Sequential Read Up To 2800 MB/s
Maximum Sequential Write Up To 1600 MB/s
Logical Blocks 2,000,409,264

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features TRIM; L1.2



Technical Specifications

SSD 256GB 2280 M2 SATA-3 Drive Weight Self Encrypted OPAL2 TLC Capacity

Drive Weight 0.02 lb (10 g)
Capacity 256GB

Height 0.09 in (2.3 mm)
Width 0.87 in (22 mm)
Interface ATA-8, SATA 3.0

Performance

Maximum Sequential Read Up To 530 MB/s
Maximum Sequential Write Up To 515 MB/s
Logical Blocks 500,118,192

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features DIPM; TRIM; DEVSLP

SSD 360GB 2280 PCIe-3x4 NVMe TLC Drive Weight 0.02 lb (10 g)
Capacity 360GB

 Height
 0.09 in (2.3 mm)

 Width
 0.87 in (22 mm)

 Interface
 PCIe NVMe Gen3X4

Performance

Maximum Sequential Read Up To 1700 MB/s
Maximum Sequential Write Up To 600 MB/s
Logical Blocks 703,282,608

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features TRIM; L1.2

SSD 512GB 2280 M2 PCIe-3x4 SS NVMe Drive Weight 0.02 lb (10 g)
Capacity 512GB

Height 0.09 in (2.3 mm)
Width 0.87 in (22 mm)
Interface PCIe NVMe Gen3X4

Performance

Maximum Sequential Read Up To 3000 MB/s
Maximum Sequential Write Up To 1500 MB/s
Logical Blocks 1,000,215,216

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features TRIM; L1.2

Drive Weight 0.02 lb (10 g)



Technical Specifications

Capacity 512GB

Height 0.09 in (2.3 mm)
Width 0.87 in (22 mm)
Interface PCIe NVMe Gen3X4

Performance

Maximum Sequential Read Up To 2600 MB/s
Maximum Sequential Write Up To 1400 MB/s
Logical Blocks 1,000,215,216

SSD 512GB 2280 M2 PCIe-3x4 SS NVMe TLC Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features TRIM; L1.2

SSD 512GB 2280 M2 SATA-3 TLC FIPS

Drive Weight 0.02 lb (10 g)
Capacity 512GB

Height 0.09 in (2.3 mm)
Width 0.87 in (22 mm)
Interface ACS-3, SATA 3.2

Performance

Maximum Sequential Read Up To 530 MB/s
Maximum Sequential Write Up To 400 MB/s
Logical Blocks 1,000,215,216

Operating Temperature 32° to 158°F (0° to 70°C) [ambient temp]

Features DIPM; TRIM; DEVSLP



Technical Specifications

NETWORKING/COMMUNICATIONS

WLAN

Intel 802.11a/b/g/n/ac Win (2x2) WiFi and Bluetooth® 4.2 Combo

Wireless LAN Standards

IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac

Wi-Fi certified

Interoperability Frequency Band

802.11b/g/n

• 2.402 – 2.482 GHz

802.11a/n

4.9 – 4.95 GHz (Japan)
 5.15 – 5.25 GHz
 5.25 – 5.35 GHz
 5.47 – 5.725 GHz
 5.825 – 5.850 GHz

Data Rates

802.11b: 1, 2, 5.5, 11 Mbps

802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)

 *802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)

Modulation

Direct Sequence Spread Spectrum

BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM

Security

- IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only
- AES-CCMP: 128 bit in hardware
- •802.1x authentication
- WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.
- WPA2 certification
- IEEE 802.11i
- Cisco Certified Extensions, all versions through CCX4 and CCX Lite
- WAPI

Network Architecture Models Ad-hoc (Peer to Peer)
Infrastructure (Access Point Required)

Roaming

IEEE 802.11 compliant roaming between access points

Output Power[2]

- • 802.11b: +14dBm minimum
- 802.11g: +12dBm minimum
 802.11a: +12dBm minimum
- 802.11n HT20(2.4GHz): +12dBm minimum
- 802.11n HT40(2.4GHz): +12dBm minimum
- 802.11n HT20(5GHz): +10dBm minimum
- 802.11n HT40(5GHz): +10dBm minimum
- 802.11ac VHT80(5GHz): +10dBm minimum



Technical Specifications

2.0 W (max) **Power Consumption** Transmit:

Receive: 1.6 W (max)

Idle mode (PSP): 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated)

Connect Standby: 10 mW Radio disabled8 mW

Power Management ACPI and PCI Express compliant power management

802.11 compliant power saving mode

Receiver Sensitivity[3] 802.11b, 1Mbps: -93.5dBm maximum

> 802.11b, 11Mbps: -84dBm maximum 802.11a/q, 6Mbps: -86dBm maximum 802.11a/q, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac. MCS9: -59dBm maximum

High efficiency antenna with spatial diversity, mounted in the display Antenna type

enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

Form Factor PCI-Express M.2 MiniCard

Dimensions Type 2230: 2.3 x 22.0 x 30.0 mm

Weight Type 2230: 2.8q Operating Voltage 3.3v +/- 9%

Temperature 14° to 158° F (-10° to 70° C) Operating

> -40° to 176° F (-40° to 80° C) Non-operating

Humidity Operating 10% to 90% (non-condensing)

Non-operating 5% to 95% (non-condensing)

Altitude 0 to 10,000 ft (3,048 m) Operating

Non-operating 0 to 50,000 ft (15,240 m)

LED Activity LED Amber - Radio OFF: LED White - Radio ON

HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless **Technology**

Bluetooth Specification 4.0/4.1/4.2 Compliant **Frequency Band** 2402 to 2480 MHz **Number of Available** Legacy: 0~79 (1 MHz/CH)

Channels BLE: 0~39 (2 MHz/CH)

Data Rates and Throughput

Data Rates and

Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps

BLE: 1 Mbps data rate; throughput up to 0.2 Mbps

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice

channels

Throughput Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps **Transmit Power**

asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

The Bluetooth component shall operate as a Class II Bluetooth device with

a maximum transmit power of + 4 dBm for BR and EDR.

Power Consumption Peak (Tx) 330 mW

Peak (Rx) 230 mW



Technical Specifications

Selective Suspend 17 mW

Electrical Interface

Bluetooth Software

Supported Link Topology

Power Management

Certifications

Power Management Certifications USB 2.0 compliant

Microsoft Windows Bluetooth Software

Microsoft Windows ACPI, and USB Bus Support

FCC (47 CFR) Part 15C, Section 15.247 & 15.249

ETS 300 328, ETS 300 826

Low Voltage Directive IEC950

UL, CSA, and CE Mark

Bluetooth Profiles Supported

BT4.1-ESR 5/6/7 Compliance

LE Link Layer Ping LE Dual Mode LE Link Layer

LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels

Train Nudging & Interlaced Scan

BT4.2 ESR08 Compliance

LE Secure Connection- Basic/Full LE Privacy 1.2 -Link Layer Privacy

LE Privacy 1.2 – Extended Scanner Filter Policies

LE Data Packet Length Extension

FAX Profile (FAX)

Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

Bluetooth Profiles Supported BT4.1-ESR 5/6/7 Compliance

LE Link Layer Ping LE Dual Mode LE Link Layer

LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels

Train Nudging & Interlaced Scan

BT4.2 ESR08 Compliance

LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy

LE Privacy 1.2 - Extended Scanner Filter Policies

LE Data Packet Length Extension

FAX Profile (FAX)

Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

WWAN



Technical Specifications

Mobile Broadband Module

HP lt4132 LTE/HSPA+ 4G Technology/Operating

hands

LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3) MHz.

850 (Band 5), 2600 (Band 7), 900 (Band 8) MHz.

800 (Band 20), 700 (Band 28) MHz.

HSPA+: 2100 (Band 1), 1900 (Band 2), 850 (Band 5), 900 (Band 8) MHz E-GPRS: 1900 (Band 2), 1800 (Band 3), 850 (Band 5), 900 (Band 8) MHz

Wireless protocol

standards

3GPP Release 10 LTE Specification CAT.4. 20MHz BW WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification E-GPRS: Class B. Multi-slot class 12. coding schemes CS1 - CS4

and MSC1 - MSC9

GPS Standalone, A-GPS (MS-B and LTO)

GPS bands 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz

Maximum data rates LTE: 150 Mbps (Download), 50 Mbps (Upload)

> DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload) EDGE: 236.8 kbps (Download), 236.8 kbps (Upload) GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)

Maximum output power

LTE: 23 dBm

HSPA+: 23.5 dBm E-GPRS 1900/1800: 26 dBm

E-GPRS 900/850: 27 dBm GPRS 1900/1800: 29.5 dBm GPRS 900/850: 32.5 dBm

Maximum power consumption

LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average) E-GPRS: 2,600 mA (peak); 500 mA (average)

Form Factor M.2, 3042-S3 Key B

Weight 6 g

Dimensions 42 x 30 x 2.3 mm

(Length x Width x Thickness)

NOTE: Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

HP lt4120 Qualcomm® Snapdragon™ X5 LTE **Mobile Broadband** Module

Technology/Operating

bands

GPS

LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3),

1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 17 lower),

800 (Band 20), 700 (Band 28).

HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4),

850 (Band 5), 900 (Band 8) MHz

EV-DO: 850 (BC0), 1900 (BC1) MHz (Only work with Verizon network) E-GPRS: 1900 (Band 2), 1800 (Band 3), 850 (Band 5), 900 (Band 8)

Wireless protocol standards

3GPP Release 10 LTE Specification CAT.4, 20MHz BW WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification

1xEVDO Release O, A and B.

E-GPRS: Class B, Multi-slot class 12, coding schemes CS1 - CS4

and MSC1 - MSC9

Standalone, A-GPS (MS-A, MS-B and XTRA)



Technical Specifications

GPS bands 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz

Maximum data rates LTE: 150 Mbps (Download), 50 Mbps (Upload)

DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)

CDMA 1xRTT: 153.6 kbps (Download), 153.6 kbps (Upload) EVDO Rel.A: 3.1 Mbps (Download), 1.8 Mbps (Upload) EVDO Rel.B: 14.7 Mbps (Download), 5.4Mbps (Upload) EDGE: 236.8 kbps (Download), 236.8 kbps (Upload) GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)

Maximum output power LTE: 23 dBm

> HSPA+: 23.5 dBm 1xRTT/EVD0: 24dBm E-GPRS 1900/1800: 26 dBm E-GPRS 900/850: 27 dBm GPRS 1900/1800: 29.5 dBm GPRS 900/850: 32.5 dBm

Maximum power consumption

LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average) 1xRTT/EVD0: 1.000 mA (peak): 700 mA (average) E-GPRS: 2,800 mA (peak); 500 mA (average)

Form Factor M.2. 3042-S3 Kev B

Weight 6.2 q

Dimensions 42 x 30 x 2.3 mm

(Length x Width x Thickness)

NOTE: Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

HP hs3210 HSPA+ Mobile Technology/Operating

Broadband Module

bands

HSPA+: 2100 (Band1), 1900 (Band 2), 850 (Band 5), 900 (Band 8) MHz E-GPRS: 1900 (Band 2), 1800 (Band 3), 850 MHz (Band 5), 900 (Band 8) MHz

WCDMA R99, 3GPP Release 5, 6 and 7 UMTS Specification

Wireless protocol standards E-GPRS: Class B, Multi-slot class 33, coding schemes CS1 - CS4 and MSC1 -

MSC9

GPS Not supported **GPS** bands Not supported

Maximum data rates HSPA+: 21.6 Mbps (Download), 5.76 Mbps (Upload)

E-GPRS: 296 kbps (Download), 236.8 kbps (Upload)

Maximum output power HSPA+: 1,100 mA (peak); 800 mA (average)

E-GPRS: 2,800 mA (peak); 700 mA (average) LTE: 1,200 mA (peak); 900 mA (average)

HSPA+: 1,100 mA (peak); 800 mA (average) consumption **Form Factor** M.2, 3042-S3 Key B

Weight 6 q

Dimensions 42 x 30 x 2.3 mm

(Length x Width x Thickness)

Maximum power



Technical Specifications

NOTE: Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

POWER

AC Adapter 65 Watt nPFC Dimensions (H x W x D) **USB** type C

2.91 x 2.91 x 1.12 in (7.4 x 7.4 x 2.85 cm)

Weight

0.54 lb (245g) max

Input Efficiency 81.5% min at 115 Vac/ 230Vac @ 5V/3A

> 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 10V/5A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A

Input frequency range

Input AC current

1.7 A at 90 VAC and maximum load

47 to 63 Hz

Output **Output power**

> DC output 5V/9V/10V/12V/15V/20V Hold-up time 5 ms at 115 VAC input

65W

Output current limit <8.0A

Connector Duck head / duck head power cord, without Smart ID DC connector

Environmental Design Operating

temperature

32° to 95° F (0° to 35° C)

Non-operating (storage) -4° to 185° F (-20° to 85° C)

temperature

Altitude 0 to 16,400 ft (0 to 5,000 m)

Humidity 5% to 95% 5% to 95% **Storage Humidity**

EMI and Safety Certifications

*CE Mark - full compliance with LVD and EMC directives

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV: Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B.

FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 100,000 hours at 25°C ambient condition.

AC Adapter 90 Watt PFC USB type C

Dimensions (H x W x D)

129.5x65.5x28.5mm (5.09 x 2.57 x 1.12 inch)

Weight

0.320 kg (0.705lb) **Input Efficiency**

81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 10V/5A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A



Technical Specifications

89% min at 115 Vac/ 230Vac @ 20V/3.25A

Input frequency range

47 to 63 Hz

Input AC current

1.7 A at 90 VAC and maximum load

Output **Output power** 90W

DC output

5V/9V/10V/12V/15V/20V

Hold-up time

5 ms at 115 VAC input

Output current limit

<11A

Connector

C6 (3pin/with grounded, without Smart ID DC connector)

Environmental Design

Operating temperature 32° to 95° F (0° to 35° C)

Non-operating (storage) -4° to 185° F (-20° to 85° C)

temperature

Altitude

0 to 16,400 ft (0 to 5,000 m)

Humidity 5% to 95% **Storage Humidity** 5% to 95%

EMI and Safety Certifications

*CE Mark - full compliance with LVD and EMC directives

* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B,

FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.

* MTBF - over 100,000 hours at 25°C ambient condition.

Battery BE 6 Cell WHr 67 Dimensions (H x W x L) Long Life -PL Fast

Charge

9.45 x 86.1 x 271mm

(0.372 x 3.38 x 10.66 inch)

Weight

0.271 kg (0.5971lb)

Cells/Type

ATL: 416760

Coslight: 416760G

Energy

Voltage

11.55V

Amp-hour capacity

5800mAh / 5510mAh

Watt-hour capacity

67.0Wh / 63.65Wh

Temperature

Operating (Charging)

0°C ~ 50°C

Operating (Discharging)

-10°C ~ 60°C

Fuel Gauge LED

No

Warranty

15 months Nο

Optional Travel Battery Available



Technical Specifications

China



Options and Accessories (sold separately and availability may vary by country)

| Туре | Description | Part Number |
|-------------|---------------------------------------|-------------|
| Cases | HP Business Slim Top Load | H5M91AA |
| | HP Business Backpack | H5M90AA |
| | HP Essential Top Load Case | H2W17AA#xxx |
| Docking | HP Elite 90W Thunderbolt3 Dock | 1DT93AA#xxx |
| | HP Thunderbolt Dock 120W G2 | TBD |
| | HP USB-C Mini Dock | 1PM64AA#xxx |
| | HP USB-C Universal Dock | 1MK33AA#xxx |
| | HP Elite USB-C Dock | Z9R42AA |
| | HP Elite USB-C Dock G3 | 2DW60AA |
| | HP USB-C Travel Dock | T0K29AA |
| | HP USB Travel Dock | TOK30AA |
| I/O Devices | HP Comfort Grip Wireless Mouse | H2L63AA |
| | HP Wireless Premium Mouse | 1JR31AA |
| | HP USB Premium Mouse | 1JR32AA |
| | HP Wireless (Link-5) Keyboard | T6U20AA |
| | HP Slim USB Keyboard and Mouse | T6T83AA |
| | HP USB-C to USB-A Hub | Z6A00AA |
| | HP USB-C to RJ45 | V7W66AA#xxx |
| | HP USB to RJ 45 | N7P47AA |
| | HP USB-C to VGA Adapter | N9K76AA |
| | HP USB-C to DisplayPort Adapter | N9K78AA |
| | HP HDMI to VGA Adapter | H4F02AA |
| Power | HP 65W USB-C AC Adapter | 1HE08AA#xxx |
| | HP 90W USB-C AC Adapter | TBD |
| | HP USB-C Notebook Power Bank | 1TZ86AA |
| Storage | HP External USB Optical Drive | F2B56AA |
| Security | HP Keyed Cable Lock 10mm | 1AJ39AA |
| | HP Dual Head Keyed Cable Lock | 1AJ41AA |
| | HP 14.0 Privacy Filter designed by 3M | V8Z57AA#XXX |
| | HP Nano Lock | 1AJ39AA |
| UCC | HP Conferencing Keyboard | K8P74AA#xxx |
| | HP USB Collaboration Keyboard | Z9N38AA#xxx |
| | HP Wireless Collaboration Keyboard | Z9N39AA#xxx |
| | HP UC Wireless Mono Headset | W3K08AA |
| | HP UC Wireless Duo Headset | W3K09AA |
| | HP UC Wired Headset | K7V17AA |
| | HP UC Speaker Phone | K7V16AA |
| | | |



HP EliteBook 1040 G4 Notebook PC

QuickSpecs

Options and Accessories (sold separately and availability may vary by country)

| Displays | HP EliteDisplay S140u USB Portable Monitor | G8R65AA |
|----------|---|---------|
| | HP EliteDisplay S340c 34-inch Curved Monitor | V4G46AA |
| | HP EliteDisplay S240n 23.8-inch Micro Edge Monitor | W9A88AA |
| | HP EliteDisplay E272q 27-inch QHD Monitor | M1P04AA |
| | HP EliteDisplay E230t 23-inch Touch Monitor | W2Z50AA |
| | HP EliteDisplay E240c 23.8-inch Collaboration Monitor | M1P00A8 |



Change Log

| Date of change: | Version History: | | Description of change: |
|--------------------|------------------|---------|--|
| August 28, 2017 | From V1 to V2 | Update | Battery information changed to "TBD" |
| September 6, 2017 | From V2 to V3 | Update | Weight updated |
| September 11, 2017 | From V3 to V4 | Update | Processors family correction made on i5-7300HQ switched to 7300U |
| September 20, 2017 | From V4 to V5 | Update | Processors list updated |
| October 9, 2017 | From V5 to V6 | Update | Battery Life updated |
| October 18, 2017 | From V6 to V7 | Update | Keyboard section updated |
| November 7, 2017 | From V7 to V8 | Update | Footnote added to Primary battery on Power section. |
| December 18, 2017 | From V8 to V9 | Update | HP Nano Lock added to Options and Accessories |
| February 7, 2018 | From V9 to V10 | Update | Footnote n. 10 removed on page 6 and replaced |
| March 30, 2018 | From V10 to V11 | Update | Security section |
| April 30, 2018 | From V11 to V12 | Update | Environmental tab |
| May 8, 2018 | From V12 to V13 | Added | Environmental tab |
| July 11, 2018 | From V13 to V14 | Update | Warranty |
| July 25, 2018 | From V14 to V15 | Update | Networking section |
| August 6, 2018 | From V15 to V16 | Removed | Software Velocity |
| May 30, 2019 | From V16 to V17 | Updated | Lock Slot |

Copyright © 2019 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Bluetooth is a trademark of its proprietor and used by HP Inc. under license. Intel, Core, Celeron and Intel vPro are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners.

