

# Product data sheet

Specifications



## RACK PDU, BASIC, HALF HEIGHT, 100-240V/20A, 220-240V/16A, (14) C13

AP6003A

### Overview

Lead time Usually in Stock

### Main

Color Black

Product or Component Type PDU

PDU Type Basic

Provided Equipment Installation guide  
Safety guide

### Complementary

Input Voltage 230 V

Height 20.6 in (52.3 cm)

Width 2.2 in (5.6 cm)

Output Voltage 100 V  
120 V  
200 V  
208 V  
230 V  
240 V

Depth 1.9 in (4.7 cm)

Net Weight 4.14 lb(US) (1.88 kg)

Mounting Location Side

Mounting preference Lower

Input Plug Type IEC 60320 C20

Mounting Mode Not rack-mountable

Rack units 0U

USB compatible No

Mounting position Vertical

Line Rated Current 16 A

Acceptable Input Voltage 100...240 V

Max line current 20 A

Input current limits 20 A

Load Capacity 3300 VA

Input Frequency 50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Outlet type and quantity	14 IEC 60320 C13
--------------------------	------------------

## Environment

---

Product Certifications	cUL Listed UL Listed
------------------------	-------------------------

---

Ambient Air Temperature for Operation	32...122 °F (0...50 °C)
---------------------------------------	-------------------------

---

Relative Humidity	5...95 %
-------------------	----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
-------------------------------------	--------------------------

---

Storage Relative Humidity	5...95 %
---------------------------	----------

---

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

## Ordering and shipping details

---

GTIN	731304327769
------	--------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	24.09 in (61.2 cm)
------------------	--------------------

---

Package 1 Width	4.2 in (10.7 cm)
-----------------	------------------

---

Package 1 Length	4.8 in (12.3 cm)
------------------	------------------

---

Package 1 Weight	5.62 lb(US) (2.55 kg)
------------------	-----------------------

---

SCC14	10731304327766
-------	----------------

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

 Energy Efficient Product

 Take-Back Program Available

## Well-being performance

 Lead Free

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)