

4XEM™ **Product Data Sheet**

4K Wireless Display Adapter with PD Charging



Crafted for crystal-clear 4K wireless display and 100W charging, giving you a sleek, portable solution for reliable screen sharing on the go.

Key Features

-  100W Power Delivery Charging
-  15M Transmission Distance
-  Bus Powered through device
-  Windows, Mac and Android compatible
-  4K@30Hz video supported
-  USB-C and HDMI connection

Technical Highlights

SKU Name	4XHDMIWL4KPD
Warranty	1 Years
Maximum Resolution	4K @ 30Hz (3840*2160/30Hz)
Charging Capabilities	PD3.0 100W 20V 5A Max

Application(s)

Perfect for offices, classrooms, clinics, and home workstations, this adapter simplifies high-resolution wireless presentations and streaming while maintaining fast, reliable device charging.

Visit [4XEM.com](https://www.4xem.com)

Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 ext.113 bhegarty@4xem.com



Technical Specifications

Warranty Information	Warranty	1 Year
Hardware	Operating Mode Host Interface Bus Type AV Output Audio Support Power Chip ID Industry Standards	Active USB-C HDMI HDMI Yes Yes VLI03+RV1126+RK3229+RTL8811U+NT5CC256M16ER-EK+IT6510 PD 3.0 HDMI
Connector(s) & Performance	Host Connector Display Connector Maximum Resolution Audio Specifications Transmission Distance Delay time	USB-C HDMI + USB-C 5V power supply 4K @ 30Hz (3840*2160/30Hz) Supports up to 192K 15M (barrier free) 100ms
Software	OS Compatibility	Windows 7 or later Mac OS 10.10 or later Android
Power	Power Source Standby Power Consumption Active Power Consumption Charging Capabilities	Bus-Powered Transceiver: 2.3W +/- 5% Receiver: 1.05W +/- 5% Transceiver: 2.58W +/- 5% Receiver: 1.97W +/- 5% PD3.0 100W 20V 5A Max
Physical Characteristics	Color Button Cable Jacket Type Main Body dimensions Cable Length Connector Length Connector Width Connector Height Weight of Product	Black Switch at the transmitter - supports opening and closing screen projection mode PVC Diameter: 2.36 in [60 mm] Height: 0.59 in [15.1 mm] Transceiver: 3.6 in [91.44 mm] Receiver: 3.9 in [99.06 mm] Transceiver: 0.79 in [20 mm] Receiver: 0.79 in [20 mm] Transceiver: 0.43 in [10.9 mm] Receiver: 0.43 in [10.9 mm] Transceiver: 0.24 in [6 mm] Receiver: 0.24 in [6 mm] 2.99 oz [85 g]
Environmental	Humidity Operating Temperature Storage Temperature	45%~90%RH 0°C to 40°C (32°F to 104°F) -20°C to 60°C (4°F to 140°F)
Packaging Information	Packaging Type Package Height Package Width Package Length Shipping (Package) Weight	Box 0.98 in [25 mm] 7.28 in [185 mm] 8.26 in [210 mm] 6.17 oz [175 g]
What's in the Box	Included in Package	1 - USB-C video transceiver 1 - HDMI + USB-C 5V power supply adapter receiver 1 - USB-C to USB-A charging cable
Notes	System Requirements Notes	Plug and play, no driver, ethernet or wifi required USB-C Host needs to be DP-alt mode compliant or Thunderbolt 3/4 compliant for video to work properly One receiver can connect up to 5 transmitters max Supports both mirror mode and extension mode

Visit [4XEM.com](https://www.4xem.com)

Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 ext.113 bhegarty@4xem.com