


Programmable Relay I/O Card for Tripp Lite SVTX, SVX and SV UPS Systems

MODEL NUMBER: RELAYCARDSV



Description

The RELAYCARDSV Programmable Relay I/O Card is a contact-closure management accessory card compatible only with Tripp Lite SVTX, SVX and SV Series 3-phase UPS systems. It is ideal for providing contact closure output communications for IBM server, PC and workstation equipment and auto-controlled industrial equipment and communications applications. It lets you communicate UPS system status and events via six contact closure outputs. Each output relay can be configured as either Normally Close or Normally Open. You can also configure the input signal to perform remote UPS system shutdowns or battery tests. Relay contacts report UPS alarm, utility failure, UPS on-line mode, low battery, bypass mode and UPS failure. The RELAYCARDSV is simple to install in Tripp Lite SmartOnline® SVTX 400V non-modular, SVX 400V modular or SV 208V modular UPS system. A six-foot DB9 cable is included for connecting the UPS system to equipment for remote monitoring and control.

Features

Provides Contact Closures for Remote UPS System Monitoring

- Recommended for IBM server, PC and workstation equipment and auto-controlled industrial equipment and communications applications
- 6 output relays configurable to Normally Close or Normally Open
- Input signal performs remote UPS shutdown or battery test
- Relay contacts report UPS alarm, utility failure, UPS on-line mode, low battery, bypass mode and UPS failure
- Compatible with Tripp Lite SmartOnline SVTX 400V non-modular, SVX 400V modular and SV 208V modular UPS systems
- 6 ft. DB9 cable included

Specifications

OVERVIEW	
Accessories Type	Relay I/O Card
Power Management Type	Network Interfaces

Highlights

- Allows UPS to provide contact closure output communications
- 6 output relays configurable to Normally Close or Normally Open
- Input signal performs remote UPS shutdown or battery test
- For Tripp Lite SVTX, SVX and SV 3-phase UPS systems only

System Requirements

- Tripp Lite SmartOnline SVTX 400V non-modular, SVX 400V modular or SV 208V modular UPS system

Package Includes

- RELAYCARDSV Programmable Relay I/O Card
- DB9 communication cable, 6 ft.
- Owner's manual



OUTPUT	
Output Connector Type	DB9 port
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.89 x 6.54 x 4.89
Shipping Dimensions (hwd / cm)	4.8 x 16.61 x 12.42
Shipping Weight (lbs.)	0.44
Shipping Weight (kg)	.2
Unit Dimensions (hwd / in.)	5.08 x 1.3 x 2.64
Unit Dimensions (hwd / cm)	3.3 x 6.71 x 12.9
Unit Weight (lbs.)	0.18
Unit Weight (kg)	0.08
COMMUNICATIONS	
Communications Interface	Contact closure
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>