

# Product data sheet

Specifications



## APC NetShelter Metered Rack PDU, 0U, 3PH, 11kW 230V 16A or 11kW 230V 16A, 36 C13 and 6 C19 outlets, IEC 309 3P+N+PE cord

AP8881

### Overview

<b>Presentation</b>	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
---------------------	---

<b>Lead time</b>	Usually in Stock
------------------	------------------

### Main

<b>Color</b>	Black
<b>Product or Component Type</b>	PDU
<b>PDU Type</b>	Metered
<b>Cord length</b>	6 ft (1.8 m)
<b>Number of cables</b>	1
<b>Provided Equipment</b>	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

### Complementary

<b>Input Voltage</b>	400 V 3 phase
<b>Height</b>	70.5 in (179.1 cm)
<b>Width</b>	2.2 in (5.6 cm)
<b>Output Voltage</b>	230 V
<b>Depth</b>	1.7 in (4.4 cm)
<b>Net Weight</b>	14.07 lb(US) (6.38 kg)
<b>Mounting Location</b>	Side
<b>Mounting preference</b>	No preference
<b>Input Plug Type</b>	IEC 60309 16 A 3P+N+PE IEC 60309 20 A 3P+N+PE
<b>Mounting Mode</b>	Rack-mounted
<b>Rack units</b>	0U
<b>USB compatible</b>	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting position	Vertical
Line Rated Current	16 A
Max line current	16 A
Input current limits	16 A
Load Capacity	11000 VA
Input Frequency	50/60 Hz
Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19

## Environment

Product Certifications	VDE
Standards	CSA C22.2 No. 60950 IEC 60950 UL 60950-1
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

GTIN	731304277071
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.7 in (200 cm)
Package 1 Width	6.4 in (16.2 cm)
Package 1 Length	4.2 in (10.7 cm)
Package 1 Weight	17.68 lb(US) (8.02 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back RoHS/REACH

## Resource performance


 Energy Efficient Product

---


 Take-Back Program Available

---


## Well-being performance

 Lead Free

---

 Mercury Free

---

 Rohs Exemption Information [Yes](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive Compliant with Exemptions

---

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

---

Circularity Profile [End of Life Information](#)

---