

Key Features

- **Instant, secure access** to your digital workspace using **Windows Hello**
- **Crystal-clear video with 5MP webcam**, privacy cover, dual microphones, and stereo speakers
- **QHD resolution and 120Hz refresh rate** deliver ultra-smooth, razor-sharp visuals for meetings and multitasking
- **USB-C port** simplifies connections for audio, video, and data transfer
- **USB 3.2 hub** with 1 USB-C upstream, 3 USB downstream ports, HDMI, and DisplayPort inputs for **seamless multi-device connectivity**



Product Description

The VG2741V-2K is a 27" QHD (2560 x 1440) **USB-C video conferencing monitor with Windows Hello**, designed to deliver secure, high-quality virtual meetings straight out of the box. With **facial recognition login via Windows Hello**, users can sign in quickly and securely—reducing password fatigue and minimizing the risk of visual hacking. A built-in **5MP adjustable webcam, dual microphones, and dual 2W speakers** provide sharp video and clear audio for professional-grade conferencing. The webcam's **±5° vertical tilt** ensures perfect framing, while the **built-in privacy cover** safeguards user privacy when the camera is not in use. The monitor supports streamlined connectivity with a **USB-C upstream port** for video, audio, and data, plus **HDMI, DisplayPort, and three USB 3.2 downstream ports**—making it ideal for both home and office environments. The VG2741V-2K combines a sharp QHD resolution with a 120Hz refresh rate for ultra-smooth, pixel-precise visuals—ideal for video conferencing, multitasking, and media playback. Eye ProTech+ technology helps reduce fatigue with low blue light and flicker-free viewing. For additional productivity, it supports **vDisplay Manager** for on-screen control and **vSplit** for efficient window layout management—both available via the **ViewSonic Display Portal**. With **full ergonomic adjustability** including height, tilt, swivel, and pivot, the VG2741V-2K adapts to your setup for long-lasting comfort and flexible workflows.

- | | | |
|--|---------------------------------|-----------------|
| 1. Menu Control Panel | 7. USB 3.2 Up Stream (Type C) | 14. Slide Cover |
| 2. Speakers | 8. USB 3.2 Down Stream (Type A) | 15. IR Camera |
| 3. VESA Compatible(Wall Mount 100 x 100 mm) | 9. Audio Out | |
| 4. Power In | 10. USB Type C (Quick Charging) | |
| 5. HDMI | 11. Microphones | |
| 6. DisplayPort | 12. IR Sensors | |
| | 13. 5MP Camera | |

Visit Us www.viewsonic.com



DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,500:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Response Time (GTG w/OD):	3.9ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	120
Variable Refresh Rate Technology:	Yes
Low Blue Light:	Hardware solution
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 85% coverage (Typ) NTSC: 85% size (Typ) sRGB: 120% size (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

USB 3.2 Type A Down Stream:	2
USB 3.2 Type C Down stream:	1 (15W power charger)
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1
3.5mm Audio Out:	1
HDMI 2.0:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	17W
Eco Mode (optimized):	21W
Consumption (typical):	25W
Consumption (max):	70W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Webcam:	5.0M pixel
Cable Organization:	Yes
Microphone:	Yes

CONTROLS

Physical Controls:	Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	30 ~ 230KHz
Frequency Vertical:	48 ~ 120Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	150
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	11.7
Net Without Stand (lbs):	8.2
Gross (lbs):	17.9

WEIGHT (METRIC)

Net (kg):	5.3
Net Without Stand (kg):	3.7
Gross (kg):	8.1

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	27.6 x 20.7 x 4.9
Physical (in.):	24.15 x 15.78~21.69 x 8.11
Physical Without Stand (in.):	24.15 x 15.3 x 2.33

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	700 x 525 x 125
Physical (mm):	613.3 x 400.9~550.9 x 206.1
Physical Without Stand (mm):	613.3 x 388.7 x 59.2

GENERAL

Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO
PACKAGE CONTENTS:	VG2741V-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male; with Type-A adapter) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT