VX2262wm

22" WIDESCREEN LCD

WITH 20,000:1 DYNAMIC CONTRAST

High performance in a beautiful design

ViewSonic's 22" VX2262wm widescreen LCD offers the perfect balance of performance and style. With its elegant lines, the VX2262wm fits beautifully into your office décor and its high performance features BLEND EFFORTLESSLY INTO YOUR TECHNOLOGY LIFE-STYLE. Images leap from the screen with Super-HD 1680x1050 resolution, video response as fast as 2ms and 20,000:1 DYNAMIC CONTRAST RATIO. Scrolling text, Internet pages and spreadsheet applications are displayed in crisp, blur-free detail with precise color The SRS WOW HD sound* powerfully complements your games, movies and other multimedia applications. Demanding designers, professionals and gamers will love the sophisticated performance of the 22" VX2262wm.



ACCENT YOUR DESKTOP WITH SOPHISTICATED STYLE.

- > Full 22" viewable widescreen with 1680x1050 resolution
- > Fast ClearMotiv® video response Video response as fast as 2ms enables digital HD broadcast-quality video.
- > 20,000:1 dynamic contrast ratio Provides for darker black levels and better overall front-of-screen performance.
- > Stylish slim-bezel design The thin bezel lets you see more without taking up valuable desktop real estate.
- > OptiSync® digital/analog inputs expand your connectivity Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > OnView® controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > SRS WOW HD sound and high quality stereo speakers
- > Windows Vista® certified
- > PC and Mac compatible
- > MPRII and ENERGY STAR® qualified













VX2262wm

22" WIDESCREEN LCD WITH 20,000:1 DYNAMIC CONTRAST



















ViewSonic Corporation's QMS & EMS have been

LCD	Туре	22" Wide Color TFT Active Matrix LCD
	Display Area	18.7" horizontal x 11.6" vertical; 22.0" diagonal
	Optimum Resolution	1680x1050
	Contrast Ratio	1000:1 static (typ), 20,000:1 dynamic
	Viewing Angles	170° horizontal, 150° vertical @ contrast ratio > 10:1
	Response Time	up to 2ms (gray-to-gray); 5ms black-to-white (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m ² (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F _h : 24~83kHz, F _v : 50~76Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1680x1050 non-interlaced
	Mac®**	G3/G4/G5 up to 1680x1050
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Power	3-pin AC plug (CEE22)
AUDIO	Speaker	2x2-watt SRS WOW HD*
POWER	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	45W (typ)
ERGONOMICS	Tilt	-5/+20°
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input select
		(analog, digital), ViewMatch® color adjust (sRGB, 9300K,
		7500K, 6500K-default, 5400K, user color-RGB),
		information (resolution, H. frequency, V. frequency, pixel
		clock, model number, serial number), manual image
		adjust (H. size, H. position, V. position, fine tune,
		sharpness, dynamic contrast aspect ratio), setup menu
		(language, resolution notice, OSD position, OSD
		timeout, OSD background), memory recall
OPERATING	Temperature	32–104°F (0–40°C)
CONDITIONS	Humidity	10–90% (non-condensing)
DIMENSIONS	Physical with stand	20.2" x 17.3" x 7.9" (508mm x 440mm x 203mm)
(W x H x D)	Physical without stand	20.2" x 14.1" x 2.5" (508mm x 359mm x 64mm)
WEIGHT	Net with stand	12.2 lb. (5.6 kg)
	Net without stand	9.9 lb. (4.5 kg)
DECLU ATIONS	Gross with stand	16.9 lb. (7.7 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, WEEE
		TUV-S), ICES-B, ISO 13406-2 & MPR II), TCO'03, GOST-R + 20
		original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC,
DEGVELE (DISPOSAL)		PSB, C-TICK, MIC, Green Mark, RoHS, EPEAT-Silver
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please
		dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		Meets MPRII and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, DVI
		cable, audio cable, Quick Start Guide, ViewSonic Wizard CD



Three-year limited warranty on LCD, parts and labor

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [13905-008-02/08] VX2262wm-1

WARRANTY