

Product data sheet

Specifications



APC Back-UPS Pro, 1350VA/
810W, Tower, 120V, 10x NEMA
5-15R outlets, Sine Wave, AVR,
USB Type A + C ports, LCD, User
Replaceable Battery

BR1350MS

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|------------------------------------|
| Main Input Voltage | 120 V |
| Main Output Voltage | 120 V |
| Kw Rating | 810 W |
| Rated power in VA | 1350 VA |
| Product or Component Type | Uninterruptible power supply (UPS) |
| Input Connection Type | NEMA |
| output connection type | 6 NEMA 5-15R 4 NEMA 5-15R surge |
| Cable length | 6 ft (1.8 m) |
| Number of cables | 1 |
| Battery Type | Lead-Acid battery |

Batteries & Runtime

| | |
|------------------------------|---------------------------------------|
| Run Time | View Runtime Graph |
| Efficiency | View Efficiency Graph |
| Included Battery Modules | 1 |
| Battery Slots Empty | 0 |
| Typical recharge time | 16 h |
| RBC Quantity | 2 |
| Battery Charge Power (Watts) | 10 W rated |
| Battery life | 3...5 year(s) |
| Replacement battery | APCRBC161 |
| Extendable Run Time | 0 |

General

| | |
|--------------------|---|
| Provided equipment | Coaxial cable User Manual USB cable |
|--------------------|---|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|-------------------------------------|--------------------|
| product web sub-family | Gaming performance |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|-----------------------|
| Height | 10.2 in (26 cm) |
| Width | 3.9 in (10 cm) |
| Depth | 14.5 in (36.8 cm) |
| Net Weight | 25.8 lb(US) (11.7 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | No |

Input

| | |
|---------------------------------|----------------|
| Input Frequency | 60 Hz +/- 3 Hz |
| Efficiency at full load | 88...147 V |
| Maximum Input Current per Phase | 12 A |
| Switching current capacity | 15 A |

Output

| | |
|----------------------------------|------------------------------|
| Max Configurable Power (Watts) | 810 W |
| Output Frequency (sync to mains) | 60 Hz +/- 3 Hz sync to mains |
| Topology | Line Interactive |
| Waveform Type | Sine wave |
| Maximum configurable power in VA | 1350 VA |
| Transfer Time | 8ms typical : 10 ms maximum |

Conformance

| | |
|-----------------------------|---|
| Product Certifications | ENERGY STAR V2.0 (USA) NOM TUV C-US certified |
| Equipment protection policy | Lifetime : \$500000 |

Environmental

| | |
|---------------------------------------|---|
| Ambient Air Temperature for Operation | 32...104 °F (0...40 °C) |
| Relative Humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | 5...104 °F (-15...40 °C) |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0...10000 ft (0.0000000000...3048.0000000000 m) |

| | |
|----------------|--------|
| Acoustic level | 45 dBA |
|----------------|--------|

Communications & Management

| | |
|---------------|---|
| Control panel | Multi-function LCD status and control console |
|---------------|---|

Surge Protection and Filtering

| | |
|---------------------|--------|
| Surge energy rating | 1080 J |
|---------------------|--------|

| | |
|-----------|---|
| Filtering | Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in |
|-----------|---|

Ordering and shipping details

| | |
|----------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
|----------|---------------------------|

| | |
|-------------------|------|
| Discount Schedule | APC1 |
|-------------------|------|

| | |
|------|----------------|
| GTIN | 00731304335399 |
|------|----------------|

| | |
|---------------|----|
| Returnability | No |
|---------------|----|

| | |
|-------------------|----|
| Country of origin | PH |
|-------------------|----|

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

| | |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

| | |
|------------------|---------------------|
| Package 1 Height | 14.12 in (35.87 cm) |
|------------------|---------------------|

| | |
|-----------------|-------------------|
| Package 1 Width | 19.0 in (48.2 cm) |
|-----------------|-------------------|

| | |
|------------------|------------------|
| Package 1 Length | 8.8 in (22.3 cm) |
|------------------|------------------|

| | |
|------------------|-----------------------|
| Package 1 Weight | 29.3 lb(US) (13.3 kg) |
|------------------|-----------------------|

| | |
|-------|----------------|
| SCC14 | 10731304335396 |
|-------|----------------|

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information Yes

Environmental Certifications

 Energy Star® ENERGY STAR UPS V2.0 (USA)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov