

ConferenceSHOT AV HD Conference Room System **SKU: 999-99950-800B**



ConferenceSHOT AV Bundle - CeilingMIC 1 (without speaker)

Ideal for video conferencing rooms, ConferenceSHOT AV integrates a PTZ camera and audio conferencing mixer into a single USB 3.0 device, so you can easily connect up to two microphones and an external speaker directly to the camera. Easy plug and play functionality with all major UCC soft clients such as Microsoft Teams, Google Meet and Zoom.

This Package Includes:

- ConferenceSHOT AV camera (black)
- 1 qty CeilingMIC microphone (white)
- 1 qty silicone split strain relief boot (white)
- ConferenceSHOT AV Quick-start card
- CeilingMIC Installation Guide
- PoE+ Midspan Power Injector with AC cord set(s)
- Thin Profile Wall Mount (black) with mounting hardware and installation manual
- Vaddio IR Remote Commander with audio controls
- 1 qty CeilingMIC interface box
- 1 qty cable clamp grommet
- 2 qty ceiling trim ring plates (white) with mounting screws
- 1 qty ceiling tile brace
- 6' (1.8m) USB 3.0 cable, type A to B
- 3' (0.9m) cat-5 cable, white
- 10' (3m) cat-5 cable, black
- 1 qty 4-position phoenix-style connector

This conference room AV system is ideal for small to medium-sized videoconferencing rooms, choose color, power cord, speaker and microphone options to build the perfect ConferenceSHOT AV bundle for your space.

- **Powerful:** ConferenceSHOT AV integrates a 10x zoom HD PTZ camera and audio conferencing mixer into a single USB 3.0 device, so you can easily connect microphones and an external speaker to the camera. The ConferenceSHOT AV is easy to install and allows simple plug and play functionality with all major UCC soft clients such as Microsoft Teams, WebEx and Google Meet.
- **Simple:** ConferenceSHOT AV is UVC compliant. No external drivers need to be installed on your PC – just plug and play. The versatile system supports customized AV designs with third-party equipment or can be deployed as a standalone solution.
- **Enterprise-Class:** ConferenceSHOT AV allows for remote monitoring, management and control of a distributed camera network. IP-accessible and a browser-based user interface enables both browser control and IP-live preview and setup from PCs, Macs and mobile devices including iPhone, iPad and Android devices.

This USB-based solution makes it easy for your organization to collaborate using your preferred videoconferencing software like Microsoft Teams, Google Meet and more.

ConferenceSHOT AV turns your BYOD device into a small space UC system with professional PTZ camera quality and full room audio performance. It's a significant step up in performance from the current webcam-based technology offerings.

Total Pixels: 2.14 Megapixel

Specifications

Dimensions &

Measurements

Depth	5.5 in (14 cm)
Height	6.3 in (16 cm)
Operating Temperature	32° to 104°F (0° to 40°C)
Product Weight	3 lbs (1.4 kg)
Shipping Dimensions	28" x 13" x 20" (711.2 x 330.2 x 508 mm)
Shipping Weight	20 lbs (9.1 kg)
Width	6.1 in (15.5 cm)

Characteristics &

Features

3rd Party Control	Telnet
Audio Type	• Microphone • Mixers and IO Devices
Browser-based User Interface for Remote Control	Built-in
Camera Type	PTZ
Color	Black
Compatible With	Vaddio
Control Method	• IR Remote • Joystick • Telnet • Touch Screen • Web UI
Estimated Room Size	• Medium Room • Small Room
Field of View	74° Wide End to 7.6° Tele End
Field of View Wide	Greater than 70
Focus System	• Auto • Manual

Gain	• Auto • Manual
Image Sensor Type	1-2_8 Exmor CMOS
Input Ports	• EasyMIC • Network • USB 3.0
Invertible	Yes
Manufacturer	Vaddio
Max Resolution	1080p 60
Microphones	One Ceiling Microphone
Minimum Illumination	0.4 Lux (F1.6)
OneLINK Compatibility	No
Output Ports	• Audio • IP Streaming • Network • USB 3.0 Type B
Pan and Tilt Range	• Tilt: +90° to -30° • Pan: ±162°
Pan and Tilt Speed	0.35°/sec - 90°/sec
Pixels	2.14 Megapixel
Power Cord	US Cord
Power Supply	PoE+
Power Type	PoE+
Preset Positions	16 Custom Home Position
PTZ Motors	Stepper Motors
Quick-Connect Compatibility	No

Signal Type	• Audio • IP Streaming • USB 2.0 • USB 3.0
Solution Type	Conference Room System
Speaker	None
TAA Compliant	• Yes • Yes
Tri-Sync Motion	No
UPC	840077506490
White Balance	• Auto • Manual • One Push
Zoom	10x

Certifications & Warranties

Certifications	• CE • FCC • TAA • UL Listed
Warranty	3 years

Source:

https://www.legrandav.com/products/cameras/videoconferencing_ptz_camera/conferenceshot-av/999-99950-800b