

Dual-4K Docking Station with 6 x USB 3.0 Ports

Product ID: DK30A2DH



This dual-4K docking station offers wide flexibility in setting up your workstation, working with both USB-C and USB-A port laptops and supporting multiple combinations of Ultra HD 4K DisplayPort and HDMI monitors.

Ideal for highly detailed graphics applications, this dual-4K 60Hz docking station enhances your productivity by expanding the display capabilities of your laptop across two Ultra HD 4K monitors. The laptop docking station works with DisplayLink to support high-resolution monitors, enabling two full 4K 60Hz displays from a single USB connection.

With the dual-4K dock, connect:

- 2x 4K DisplayPort displays (up to 4096 x 2160p @ 60Hz)
- 2x 4K HDMI displays (up to 4096 x 2160p @ 60Hz)
- 1x 4K DisplayPort + 4K HDMI displays (up to 4096 x 2160p @ 60Hz)

The USB 3.0 docking station supports USB-C and USB-A enabled Mac and Windows laptops. This means you can connect newer USB-C or Thunderbolt 3 laptops or extend the life of legacy USB 3.0 (Type-A) laptops.

This USB-A & USB-C dock lets you transform your Mac or Windows laptop into a full workstation with six USB 3.0 (Type-A) ports, a Gigabit Ethernet port, and separate 3.5 mm audio and microphone ports for multiple audio connections, all using a single cable.

To add laptop charging support for USB-C-equipped laptops, simply add the StarTech.com HB30C1A1CPD* USB to USB-C adapter.

DK30A2DH is backed by a StarTech.com 3-year warranty and free lifetime technical support.

*Note: USB-C type power adapter is required in conjunction with the HB30C1A1CPD to charge a USB-C laptop.

Certifications, Reports and Compatibility

Applications

- Perfect for laptops in business, government, finance, and sales environments
- Ideal for working with graphics or data-intensive applications on your laptop

Features

- **DUAL 4K DOCKING STATION:** Expand the display capabilities of your laptop to two Ultra HD 4K monitors with this dual display dock; connect your laptop to 2x DisplayPort or HDMI displays or 1x DP + 1x HDMI
- **FOR USB-A & USB-C LAPTOPS:** DisplayLink certified DL 6950 chipset supports USB-C, TB3 and USB-A laptops; supports dual extended displays on Macbook Pro/Air with an Intel processor or Apple M1 chip; works with Windows, Chrome OS, Ubuntu and macOS
- **CREATE A POWERFUL WORKSTATION:** Features 6x USB 3.0 ports, charging support for USB-C laptops with Type C power adapters and the HB30C1A1CPD adapter (sold separately);
- **CONNECT MORE DEVICES:** The port replicator lets you utilize your USB devices with 6x USB 3.0 (Type-A) ports; connect your peripheral devices such as hard drives or a wired mouse
- **STARTECH.COM ADVANTAGE:** StarTech.com offers a 3-year warranty and free lifetime technical support on all docking stations; with over 3000 products globally, StarTech.com makes hard-to-find easy

Prominence

| | |
|-------------------------------|---|
| Warranty | 3 Years |
| Description CDW 75 - 1st Line | StarTech.com Dual 4K Dock - Mac and Windows - USB-A & USB-C - DP & HDMI |

Hardware

| | |
|---------------------|--|
| 4K Support | Yes |
| Fast-Charge Port(s) | No |
| Displays Supported | 2 |
| Bus Type | USB-C |
| | USB 3.0 |
| Industry Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab |
| | USB 3.0 - Backward compatible with USB 2.0/1.1 |



Chipset ID DisplayLink - DL-6950
 VIA/VLI - VL813

Performance

| | |
|-----------------------------|---|
| Maximum Data Transfer Rate | 5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex) |
| Maximum Digital Resolutions | Single display - DisplayPort - 4096 x 2160 @ 60Hz / 3840 x 2160 @ 60Hz Single Display - HDMI - 4096 x 2160 @ 60Hz / 3840 x 2160 @ 60Hz Dual displays - DisplayPort and HDMI - 4096 x 2160 @ 60Hz / 3840 x 2160 @ 60Hz |
| Type and Rate | USB 3.0 - 5 Gbit/s |
| UASP Support | Yes |
| Compatible Networks | 10/100/1000 Mbps |
| Auto MDIX | Yes |
| Full Duplex Support | Yes |

Connector(s)


| | |
|-------------------|--|
| Connector Type(s) | DisplayPort (20 pin) HDMI (19 pin) USB Type-C (24 pin) USB 3.0 (5Gbps) RJ-45 USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) 3.5 mm Mini-Jack (3 Position) 3.5 mm Mini-Jack (4 Position) |
|-------------------|--|

Software

| | |
|------------------|---|
| OS Compatibility | Windows 2000, XP, Vista, 7, 8, 8.1, 10, macOS 10.6 - 10.12, 10.14 - 10.15, 11.0, Ubuntu 14.04, 16.04, 19.04, Linux Kernel 4.2 - 5.2, Chrome OS v55+ |
|------------------|---|

Special Notes / Requirements

| | |
|-------------------------------|---|
| System and Cable Requirements | A host laptop with an available USB-C port or a USB-A port. |
|-------------------------------|---|



Note USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.

A USB-C to USB-C cable and a USB-C to USB-A cable are included.

4K resolution is supported on both video ports. A 4K-capable DisplayPort or HDMI display is required to achieve 4Kx2K resolution

DisplayLink docking stations and video adapters support more than one external display on Apple's M1-based Mac. Requires driver installation. Please contact StarTech.com support for a recommendation based on your specific setup.

Indicators

| | |
|----------------|-------|
| LED Indicators | Power |
|----------------|-------|

Power

| | |
|------------------------------|---------------------|
| Power Source | AC Adapter Included |
| Input Voltage | 100 - 240 AC |
| Input Current | 1 A |
| Output Voltage | 20V DC |
| Output Current | 2 A |
| Center Tip Polarity | Positive |
| Plug Type | N |
| Power Consumption (In Watts) | 40W |

Environmental

| | |
|-----------------------|---------------------------|
| Operating Temperature | 0C to 40C (32F to 104F) |
| Storage Temperature | -10C to 70C (14F to 158F) |
| Humidity | 10~90% RH |

Physical Characteristics

| | |
|--------------|----------------------|
| Color | Black & Silver |
| Material | Aluminum and Plastic |
| Cable Length | 39.4 in [100 cm] |



| | |
|-------------------|------------------|
| Product Length | 8.9 in [22.6 cm] |
| Product Width | 3.4 in [87 mm] |
| Product Height | 1.1 in [28 mm] |
| Weight of Product | 10.6 oz [301 g] |

Packaging Information

| | |
|---------------------------|-------------------|
| Package Length | 12.5 in [31.8 cm] |
| Package Width | 5.1 in [13 cm] |
| Package Height | 2.0 in [52 mm] |
| Shipping (Package) Weight | 30.0 oz [851 g] |

What's in the Box

| | |
|---------------------|--|
| Included in Package | docking station |
| | 1 m USB-C to USB-A cable |
| | 1 m USB-C to USB-C cable |
| | universal power adapter (NA/JP, UK, EU, ANZ) |
| | quick-start guide |

****Product appearance and specifications are subject to change without notice.***

