

DisplayPort to HDMI Adapter - 4K 60Hz

Product ID: DP2HD4K60S



This DisplayPort to HDMI adapter lets you output HDMI video and audio from a DP device, with support for Ultra HD 4K at 60Hz.

The adapter lets you harness the video capabilities that are built into your DisplayPort connection, to deliver the astonishing quality of UHD to your 4K 60Hz display. This makes it easier for you to multitask while using multiple monitors to work on resource-demanding applications.

Unlike many 4K DisplayPort to HDMI adapters that only support a 30Hz refresh rate, this adapter works with HDMI 2.0 displays that can deliver output resolutions of up to 3840 x 2160p at 60Hz. Support for HDMI 2.0 means this adapter can support bandwidth up to 18Gbps, making it the ideal solution for performing high-resolution tasks such as editing 4K video.

The adapter is backward compatible with 1080p displays, which ensures that it will work with lower resolution displays such as TVs or projectors around your home or office.

The compact video adapter is highly portable and lightweight. It's the perfect accessory for your portable DP devices, fitting easily into your laptop bag or carrying case.

The portable adapter is a convenient addition when deploying company computers because it enables your employees to interface with BYOD (Bring Your Own Device) HDMI applications around the office, such as working at a hot-desk with an HDMI display or sharing your laptop's screen on a boardroom projector.

To ensure compatibility with any DisplayPort output, the DP adapter offers active conversion. Active video conversion is required to maintain 4K resolutions when converting DisplayPort to HDMI. An active DP adapter is ideal for outputting 1080p resolutions because it will work with graphics cards that can't output multimode DP++ signals, such as ATI Eyefinity cards.

For a hassle-free setup, the DisplayPort to HDMI adapter allows for plug-and-play installation without any additional software or drivers.

Note: To achieve 4K resolution at 60 Hz, a DisplayPort 1.2 output and an HDMI 2.0 display are required.



The DP2HD4K60S is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

• Connect your 4K 60Hz HDMI display to a DisplayPort output port

• Deploy this adapter with company laptops to ensure your employees can interface with BYOD displays around the office

• Use an HDMI display as a secondary monitor for your DisplayPort computer

Features

- Astonishing picture quality with support for UHD 4K resolution at 60Hz
- Maximum portability with a compact, lightweight design
- Hassle-free setup with an active DisplayPort conversion
- No power adapter required
- Plug-and-play installation
- Supports HDMI 2.0 displays

Prominence		
	Warranty	3 Years
	Description CDW 75 - 1st Line	StarTech.com DisplayPort to HDMI Adapter - 4K 60Hz DP 1.4 to HDMI Converter
Hardware		
	Active or Passive Adapter	Active
	Ports	1
	AV Input	DisplayPort - 1.4
	AV Output	HDMI - 2.0
	Audio	Yes
	Industry Standards	DPCP (DisplayPort Content Protection)
	moustry Standards	



		HDCP 2.2 (High Definition Content Protection)
		DisplayPort 1.2
		HDMI 2.0
	Chipset ID	Parade - PS176
Performance		
	Maximum Cable Distance To Display	23.0 ft [7 m]
	Maximum Digital Resolutions	4K x 2K @ 60 Hz
	Supported Resolutions	4k x 2K (Ultra HD) @ 60 Hz
		1920x1200
		1920x1080 (1080p)
		1280x720 (720p)
	Wide Screen Supported	Yes
	Audio Specifications	HDMI - 32 Channel Audio
Connector(s)		
	Connector A	DisplayPort (20 pin)
	Connector B	HDMI (19 pin)
Special Notes / Requirements		
	Note	This video adapter is not compatible with cables that use RedMere technology.
Environmental		
	Operating Temperature	5C to 35C (41F to 95F)
	Storage Temperature	-25C to 70C (13F to 149F)
	Humidity	-25C to 85C (77F to 185F) at 80% - 95%
Physical Characteristics		
	Color	Black
	Material	Plastic
	Cable Length	4.2 in [10.8 cm]



	Included in Package	DisplayPort to HDMI adapter
What's in the Box		
	Shipping (Package) Weight	1.2 oz [33.0 g]
	Package Height	0.6 in [14.0 mm]
	Package Width	7.9 in [20.0 cm]
	Package Length	8.7 in [22.0 cm]
Packaging Information		
	Weight of Product	0.8 oz [24.0 g]
	Product Height	0.4 in [10.0 mm]
	Product Width	7.7 in [19.5 cm]
	Product Length	8.5 in [21.5 cm]

*Product appearance and specifications are subject to change without notice.

