

Product data sheet

Specifications



APC NetShelter Rack PDU Advanced, Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APDU10350MO

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Metered outlet

Cord length 5.9 ft (1.8 m)

Complementary

Input Voltage 415 V 3 phase
400 V 3 phase

Height 70.08 in (178.0 cm)

Width 2.2 in (5.6 cm)

Output Voltage 240 V

Depth 3.0 in (7.5 cm)

Net Weight 21.2 lb(US) (9.6 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type IEC 60309 30 A 3P+N+PE

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Communication Port Protocol 1000BASE-T
10/100BASE-T

Line Rated Current 24 A

Acceptable Input Voltage 200...240 V
346...415 V

Input current limits 30 A

Load Capacity 17300 VA

Input Frequency 50/60 Hz

Outlet type and quantity 24 C13/C15/C19/C21
24C13/C15

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|----------------------------------------------|---------------------------------------------------------------------------------|
| Product Certifications | UKCA TAA compliance |
| Standards | UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1 |
| IP Degree of Protection | IP44 |
| Ambient Air Temperature for Operation | 23...140 °F (-5...60 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|-------------|--------------|
| GTIN | 731304439738 |
|-------------|--------------|

Packing Units

| | |
|-------------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 78.0 in (198 cm) |
| Package 1 Width | 5.2 in (13.2 cm) |
| Package 1 Length | 10.3 in (26.2 cm) |
| Package 1 Weight | 27.8 lb(US) (12.6 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 3 years repair or replace |
|-----------------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)



RoHS/REACH

Well-being performance

 Reach Free Of Svhc

 Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)