

## Cisco SGE2000 24-Port Gigabit Switch Cisco Small Business Managed Switches



High-Performance, Reliable, Stacking Switch for Small Businesses

### Highlights

- 24 high-speed ports optimized for the network core or to support bandwidth-intensive applications
- Resilient clustering provides the ability to manage several switches as a single switch to support growing businesses
- Basic QoS helps ensure a consistent network experience and supports networked applications including voice, video, and data storage
- Strong security protects network traffic to keep unauthorized users off the network
- Limited lifetime warranty

**Figure 1.** Cisco SGE2000 24-Port Gigabit Switch



### Product Overview

The Cisco SGE2000 24-Port Gigabit Switch (Figure 1) helps maximize system availability, with fully redundant stacking and dual images for resilient firmware upgrades. The switch helps secure the network through IEEE 802.1Q VLANs, IEEE 802.1X port authentication, access control lists (ACLs), denial-of-service (DoS) prevention, and MAC-based filtering. The enhanced quality of service (QoS) and traffic-management features help ensure clear and reliable voice and video communications.

The Cisco SGE2000 includes an intuitive, secure management interface, enabling you to take advantage of the comprehensive feature set for a better-optimized, more secure network.

### Features

- Twenty-four 10/100/1000 Ethernet ports
- Four Small Form-Factor Pluggable (SFP) slots (shared with four copper ports) for fiber Gigabit Ethernet expansion
- Dual images for resilient firmware upgrades
- Up to 48-Gbps, nonblocking, store-and-forward switching capacity

- Simplified QoS management using 802.1p, differentiated services (DiffServ), or (ToS) traffic prioritization specifications
- Fully resilient stacking for optimized growth with simplified management
- ACLs for granular security and QoS implementation
- Can be configured and monitored from a standard web browser
- Secure remote management of the switch via Secure Shell (SSH) and SSL encryption
- 802.1Q-based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge (PVE) for simplified network isolation of guest connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP)
- User/network port-level security via 802.1X authentication and MAC-based filtering
- Increased bandwidth and added link redundancy with link aggregation
- Enhanced rate-limiting capabilities, including back pressure, multicast, and broadcast flood control
- Port mirroring for noninvasive monitoring of switch traffic
- Jumbo frame support up to 10KB
- Simple Network Management Protocol (SNMP) versions 1, 2c, and 3 and Remote Monitoring (RMON) support
- Fully rack mountable using the included rack-mounting hardware
- Simple, one-step automated installation and initial configuration

## Specifications

Table 1 contains the specifications, package contents, and minimum requirements for the Cisco SGE2000 24-Port Gigabit Switch.

**Table 1.** Specifications for the Cisco SGE2000 24-Port Gigabit Switch

Feature	Description
<b>Specifications</b>	
<b>Ports</b>	<ul style="list-style-type: none"> <li>• 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T with 4 shared Gigabit SFP slots</li> <li>• Console port</li> <li>• Auto medium dependent interface (MDI) and MDI crossover (MDI-X)</li> <li>• Auto negotiate/manual setting</li> <li>• RPS port for connecting to redundant power supply unit</li> </ul>
<b>Buttons</b>	Reset button
<b>Cabling type</b>	<ul style="list-style-type: none"> <li>• Unshielded twisted pair (UTP) Category 5 or better for 10BASE-T/100BASE-TX</li> <li>• UTP Category 5 Ethernet or better for 1000BASE-T</li> </ul>
<b>LEDs</b>	PWR, Fan, Link/Act, Speed, RPS, Master, Stack ID 1 through 8
<b>Performance</b>	
<b>Switching capacity</b>	Up to 48 Gbps, nonblocking
<b>Forwarding rate (based on 64-byte packets)</b>	Up to 35.7 mpps
<b>Stacking</b>	
<b>Stack operation</b>	<ul style="list-style-type: none"> <li>• Up to 8 units in a stack (192 ports)</li> <li>• Hot insertion and removal</li> <li>• Ring and chain stacking options</li> <li>• Master and backup master for resilient stack control</li> <li>• Auto-numbering or manual configuration of units in stack</li> </ul>
<b>Layer 2</b>	
<b>MAC table size</b>	8000

Feature	Description
<b>Number of VLANs</b>	256 active VLANs (4096 range)
<b>VLAN</b>	<ul style="list-style-type: none"> <li>• Port-based and 802.1Q tag-based VLANs</li> <li>• Protocol-based VLAN</li> <li>• Management VLAN</li> <li>• Private VLAN Edge (PVE)</li> <li>• GVRP</li> </ul>
<b>Head-of-line (HOL) blocking</b>	HOL blocking prevention
<b>Layer 3</b>	
<b>Layer 3 options</b>	<ul style="list-style-type: none"> <li>• Static routing</li> <li>• Classless interdomain routing (CIDR)</li> <li>• 128 static routes</li> <li>• IPv4</li> <li>• Forwarding in silicon – wire-speed forwarding of Layer 3 traffic</li> </ul>
<b>IPv6</b>	
<b>IPv6</b>	IPv6 Host Mode IPv6 over Ethernet Dual IPv6/IPv4 stack IPv6 Neighbor and Router Discovery (ND) IPv6 Stateless Address Autoconfiguration Path MTU Discovery Duplicate Address Detection (DAD) ICMPv6 IPv6 over IPv4 network with ISATAP tunnel support
<b>IPv6 QoS</b>	Prioritize IPv6 packets in hardware
<b>IPv6 ACL</b>	Drop or Rate Limit IPv6 packets in hardware
<b>MLD Snooping</b>	Deliver IPv6 multicast packets only to the required receivers
<b>IPv6 Applications</b>	Web/SSL, Telnet Server/SSH, Ping, Traceroute, SNMP, TFTP, Radius, Syslog, DNS Client
<b>IPv6 RFCs Supported</b>	RFC2463 – ICMPv6 RFC3513 – IPv6 Address architecture RFC 4291 – IP Version 6 Addressing Architecture RFC 2460 – Internet Protocol v6 (IPv6) Specification RFC 2461 – Neighbor Discovery for IPv6 RFC 2462 – IPv6 Stateless Address Auto-configuration RFC 1981 – Path MTU Discovery RFC 4007 – IPv6 Scoped Address Architecture RFC3484 – Default address selection mechanism is described by RFC3484 RFC4214 – ISATAP tunneling RFC4293 – MIB IPv6: Textual Conventions and General Group RFC 3595 – Textual Conventions for IPv6 Flow Label
<b>Management</b>	
<b>Web user interface</b>	Built-in web user interface for easy browser-based configuration (HTTP/HTTPS)
<b>SNMP</b>	SNMP versions 1, 2c, and 3 with support for traps
<b>SNMP MIBs</b>	RFC1213 MIB-2, RFC2863 interface MIB, RFC2665 Ether-like MIB, RFC1493 bridge MIB, RFC2674 extended bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1, 2, 3, and 9 only), RFC2737 entity MIB, RFC3621 Power Ethernet MIB, RFC 2618 RADIUS client MIB, RFC 1215 traps
<b>RMON</b>	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis
<b>Firmware upgrade</b>	<ul style="list-style-type: none"> <li>• Web browser upgrade (HTTP) and Trivial File Transfer Protocol (TFTP)</li> <li>• Dual images for resilient firmware upgrades</li> </ul>
<b>Port mirroring</b>	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe

Feature	Description
<b>Other management</b>	<ul style="list-style-type: none"> <li>• Traceroute</li> <li>• Single IP management</li> <li>• SSL security for web user interface</li> <li>• SSH</li> <li>• RADIUS</li> <li>• Port mirroring</li> <li>• TFTP upgrade</li> <li>• DHCP client</li> <li>• BOOTP</li> <li>• Simple Network Time Protocol (SNTP)</li> <li>• Xmodem upgrade</li> <li>• Cable diagnostics</li> <li>• Ping</li> <li>• Syslog</li> <li>• Telnet client (SSH secure support)</li> </ul>
<b>Security</b>	
<b>IEEE 802.1X</b>	<ul style="list-style-type: none"> <li>• 802.1X – RADIUS authentication; MD5 hash</li> <li>• Guest VLAN</li> <li>• Single/multiple host mode</li> </ul>
<b>Access control</b>	<p>ACLs – drop or rate limit based on:</p> <ul style="list-style-type: none"> <li>• Source and destination MAC-based</li> <li>• Source and destination IP address</li> <li>• Protocol</li> <li>• Port</li> <li>• VLAN</li> <li>• Differentiated services code point (DSCP)/IP precedence</li> <li>• TCP/User Datagram Protocol (UDP) source and destination ports</li> <li>• 802.1p priority</li> <li>• Ethernet type</li> <li>• Internet Control Message Protocol (ICMP) packets</li> <li>• Internet Group Management Protocol (IGMP) packets</li> <li>• Up to 1018 rules</li> </ul>
<b>Availability</b>	
<b>Link aggregation</b>	<ul style="list-style-type: none"> <li>• Link aggregation using IEEE 802.3ad Link Aggregation Control Protocol (LACP)</li> <li>• Up to 8 ports in up to 8 groups</li> </ul>
<b>Storm control</b>	Broadcast and multicast storm protection
<b>DoS prevention</b>	DoS attack prevention
<b>Spanning Tree</b>	<ul style="list-style-type: none"> <li>• IEEE 802.1D Spanning Tree</li> <li>• IEEE 802.1w Rapid Spanning Tree</li> <li>• IEEE 802.1s Multiple Spanning Tree, Fast Linkover</li> </ul>
<b>IGMP snooping</b>	IGMP (versions 1 and 2) snooping limits bandwidth-intensive video traffic to only the requestors. Supports 256 multicast groups.
<b>QoS</b>	
<b>Priority levels</b>	4 hardware queues
<b>Scheduling</b>	Priority queuing and weighted round-robin (WRR)
<b>Class of service</b>	<ul style="list-style-type: none"> <li>• Port based</li> <li>• 802.1p VLAN priority based</li> <li>• IPv4 IP precedence/ToS/DSCP based</li> <li>• DiffServ</li> <li>• Classification and re-marking ACLs</li> </ul>
<b>Rate limiting</b>	<ul style="list-style-type: none"> <li>• Ingress policer</li> <li>• Egress rate control</li> </ul>
<b>Standards</b>	802.3 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet, 802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3x flow control, 802.3ad LACP, 802.1d Spanning Tree Protocol (STP), 802.1Q/p VLAN, 802.1w Rapid STP, 802.1s Multiple STP, 802.1x port access authentication

Feature	Description
<b>Environmental</b>	
<b>Dimensions W x D x H</b>	17.32 x 14.70 x 1.73 in. (440 x 375 x 44 mm)
<b>Unit weight</b>	14.09 lb (6.39 kg)
<b>Certification</b>	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
<b>Operating temperature</b>	32° to 104°F (0° to 40°C)
<b>Storage temperature</b>	−4° to 158°F (−20° to 70°C)
<b>Operating humidity</b>	10% to 90% relative humidity, noncondensing
<b>Storage humidity</b>	10% to 95% relative humidity, noncondensing
<b>Number of fans</b>	2
<b>Acoustic noise</b>	55 dB max.
<b>Power</b>	100–240V AC, 50–60Hz, internal, universal; also equipped with redundant power supply connector for external power supply 48V DC
<b>Power consumption</b>	12V at 7.5A (90W)
<b>Package Contents</b>	
<ul style="list-style-type: none"> <li>• Cisco SGE2000 24-Port Gigabit Switch</li> <li>• Console cable</li> <li>• AC power cord</li> <li>• Rack-mounting kit</li> <li>• Quick installation guide</li> </ul>	
<b>Minimum Requirements</b>	
<ul style="list-style-type: none"> <li>• Web browser: Mozilla Firefox 1.5 or later, Internet Explorer 5.5 or later, Netscape 7.01 or later</li> <li>• Category 5 Ethernet network cable</li> <li>• TCP/IP installed on each computer within the network</li> <li>• Network adapter installed in each computer</li> <li>• Network operating system</li> </ul>	
<b>Product Warranty</b>	
Limited lifetime warranty with return to factory replacement, one year telephone support and software fixes for the warranty term.	

## Service & Support

Cisco Small Business switches are backed by the Cisco Small Business Support Service, which provides affordable peace-of-mind coverage. This subscription-based service helps you protect your investment and derive maximum value from Cisco Small Business products. Delivered by Cisco and backed by your trusted partner, this comprehensive service includes software updates, access to the Cisco Small Business Support Center, and expedited hardware replacement.

Cisco Small Business products are supported by professionals in Cisco Small Business Support Center locations worldwide who are specifically trained to understand your needs. The Cisco Small Business Support Community, an online forum, enables you to collaborate with your peers and reach Cisco technical experts for support information.

## Cisco Limited Lifetime Hardware Warranty

This Cisco Small Business product offers a limited lifetime hardware warranty with return to factory replacement and a 1-year limited warranty for fans and power supplies. In addition, Cisco offers telephone technical support at no charge for the first 12 months following the date of purchase and software bug fixes for the warranty term. To download software updates, go to: <http://www.cisco.com/cisco/web/download/index.html>.

Product warranty terms and other information applicable to Cisco products are available at <http://www.cisco.com/go/warranty>.

## For More Information

For more information on Cisco Small Business products and solutions, visit: <http://www.cisco.com/smallbusiness>.



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)