

GWAVRC

Wireless Mobile and PC to HDTV Screen Sharing Receiver

- Wirelessly display your favorite content from your Windows 10 device
- Connect a desktop, laptop, tablet or Android smartphone or tablet to your HDTV, projector or display
- Send video and audio wirelessly up to 50 ft. (15 m)
- Full HD 1080p video resolution playback support
- Ideal solution for sharing PC content wirelessly at home, at the office, and in the classroom



Wirelessly Mirror Your Windows® 10 PC or Android(TM) Device's Display

IOGEAR's Wireless Mobile and PC to HDTV Screen Sharing Receiver is the perfect solution for wirelessly streaming video and audio from your Windows 10 PC or Android device to an HDTV, HD Projector or Display. Enjoy all your favorite content such as movies, videos, photos, applications and online sites including YouTube®, Hulu®, and Netflix® in Full HD without the hassle of connecting cables.

The Screen Sharing Receiver makes it easier than ever to stream or cast content directly to an HDTV from your Windows or Android devices through its support for Miracast, the wireless display standard already built into your Windows 10 (OEM installations only) and Android 4.2+ operating systems.

Full HD 1080p Playback Support

Never compromise the viewing experience from your Windows 10 PC or Android 4.2+ phone or tablet with the Wireless Mobile and PC to HDTV Screen Sharing Receiver. Stream audio and video in Full HD 1080p resolution ensuring your content playback looks as sharp on your HDTV or projector as it does on your device's display.

- · Wirelessly display your favorite content from your Windows 10 device
- Connect a desktop, laptop, tablet or Android smartphone or tablet to your HDTV, projector or display
- Send video and audio wirelessly up to 50 ft. (15 m)
- Full HD 1080p video resolution playback support
- Ideal solution for sharing PC content wirelessly at home, at the office, and in the classroom











Requirements

Package Contents

- PC (Minimum
- Intel® 2.4GHz dual-
- core
- 4GB or more of system memory (RAM)
- Windows® 10
- •
- Display
 HDTV or Projector with HDMI port
- •
- Smartphones/Tablet s
- Wi-Fi Miracast[™] certified
- Android 4.2 or higher
- Windows® 10 or higher

- 1 x GWAVRC
- 1 x Power Adapter
- 1 x USB-A male to
- USB Micro male cable
- 1 x Quick Start Guide
 1 x
- Warranty/Registration Card



Specifications

FundaminOWARCDemainsOWARCVacionancians1 × DMAIndiansOupui1 × DMAHelpin2.02Frequency Band2.0401/20140000.022.02Vacionation0.010000000000000000000000000000000000				
Oppendix Findement Hardian Hardian Oupul 14DM Hardian 625 FrequencyBani 0x0 1080 Longha 3x5 Video Sensation 0x01 stancy Interactions 3x5 Audio Oupula Alanary Hardian 5x5 Audio Oupula 0x1ancy Hardian 5x5 Audio Oupula 0x1ancy Hardian 5x5 Audio Oupula 0x1x1 101 5x5 Audio Oupula 0x1x1 102 5x5 Audio Stansmitter: Internal antenna Bord Macearen Bord Macearen Bord 102 5x5 Audio Stansmitter: Internal antenna Bord Macearen Bord 102 5x5 Audio Stansmitter: Internal antenna Bord Macearen Bord 102 5x5 Autor Stanany 102 102	Function	GWAVRC	Dimensions	GWAVRC
Frequency Band 2.48Hz/ SGHZ Dual Band Deph 0.625* Video Resolution Up 10 100p Longh 3.73* Video Straaming Ooms Latency With Accage Dimensions 6.75* Audio Output Channel 16-bit AAC Height 0.92* Sample Rate Oth STA Straamine: internal antenna. For AV Receiver Base: internal antenna. For Avande Avande	Video connections		Unit Dimensions	
Ndeo Resultionlog 1080plog 1080plog 1080plog 1080pAdio00000 LanopVath Reage DimensionsAvid NationAvid NationAudo Output0.2010ml 10-100 ACCHeight ConstantAvid NationAvid NationSender State0.1010ml 10-1000 ConstantBeiler ConstantAvid NationAvid NationAnnan TypeSor USB transmitter: internal antenna. Both are conditioned constantMarce ConstantAvid NationAvid NationPower Adapter OSor Adapter State National Avid NationAvid NationAvid NationAvid NationPower Adapter OBueSor ConstantBeiler ConstantAvid NationPower Adapter OBueSor ConstantAvid NationAvid NationPower Adapter OBueSor ConstantBieler ConstantAvid NationPower Adapter OBueSor ConstantAvid NationAvid NationPower Adapter OBueSor ConstantBieler ConstantAvid NationPower Adapter OBueSor ConstantAvid NationAvid NationPower Adapter OBueSor ConstantSor ConstantAvid NationPower Adapter OBueSor ConstantSor ConstantSor ConstantPower Adapter OSor ConstantSor Constant	Output	1 x HDMI	Height	2.625"
Video Streaming Joins Latercy Matrix Package Dimensions Audio 2 Channel 16-bit AAC Widh Acage Dimensions 6.375 Audio Output 2 Channel 16-bit AAC Peep Aca 9.125* Sample Rate 48KHz, 16-bit from HDM connector Deph Aca 2.5* Antena Type Sort USB transmitter: internal antenna. For V Receiver Base: internal antenna. Both are omindirectional. Master Carton 16* Power Adapter USB transmitter: internal antenna. Both are omindirectional. Master Carton 16.25* Power Adapter USB transmitter: internal antenna. Both are omindirectional. Master Carton Que 16.25* Power Adapter Bue Master Carton Que 16.25* Power Adapter Bue Soft ISM Master Carton Que 24.05* Power Adapter Bue Soft ISM Master Carton Que 24.05* Power Adapter Master Carton Que 3.05* 3.05* Power Adapter Master Carton Que 3.05* 3.05* Power Adapter Mindowi So 0.10* 3.05* Power Adapter Mindowi So 1.0** Yes	Frequency Band	2.4GHz / 5GHz Dual Band	Depth	0.625"
Audio Mudio 6.375* Audio Output 2 Channel 16-bit AAC Height 9.125* Sample Ratu 48KHz, 16-bit from HDM connector Depth 2.5* Attenna Type For USE transmitter: internal antenna. For Var Receiver Passe: internal antenna. Both are omnidirectional. Maser Carton 1* Forwer Adapter USB A Adapter 5U1 A output Height 16.25* Forwor On USB A Cadapter 5U1 A output Depth 16.75* Forwor On Blue Maser Carton Output 16.75* Forwor On Blue Master Carton Output 16.75* Forwor On Blue Master Carton Output 24.05* Formating System Requirements Up to 50 feet (15m) Master Carton Output 24.05* Android 4.20 retter Unit Pasce Multi Content Sum 4.05* Formant Unit Pasce Multi Content Sum 1.5* 5* Forder Formant Nones Carton Output 0.80* 5* Android 4.20 retter Unit Pasce Multi Content Sum 5* Formant Unit Pasce Multi Content Sum 1.5* 5* Formant Unit Pasce Multi Content Sum 1.5* 5* Formant Unit Pasce Multi Content Sum 1.5* 5*	Video Resolution	Up to 1080p	Length	3.375"
Audo Ouput2 Chanel 9bit AQCHeight9.120Sample Rate40KH2 16bit MIM BunometorDeph2.57Antona TypeSole Starsmitter: internal antenna, For Needer Starsmitter: internal antenna, For 	Video Streaming	200ms Latency	Unit Package Dimensions	
Sample Rate 48H2, 16-bit from HDM connector Deph 25° Anena Type Sar Sustamitter: internal antenna. Bob are ominifiedional. Master Carton Yue op	Audio		Width	6.375"
Anema Type For USB transmitter: internal antenna. Boh AV Receiver Base: internal antenna. Boh are omnidirectional. Master Carton Fower Adapter USB AC Adapter SV1 A output Height 16.2° Fower Adapter USB AC Adapter SV1 A output Deph 16.7° Fower Adapter Bule Master Carton Oty. 24.0° Power On Bue Master Carton Oty. 24.0° Operating System Requirements Up to 50 feet (15m) Master Carton Oty. 24.0° Android A or beter Master Carton Oty. 24.0° Mindows Vindows Nindows 0.80 0.0° Forrage Temperature Vindows 1.4158°F (-10-70°C) Vindow 1.50 Hunidity 10% to 85% RH (No Condensation) Vindow Vindow Vindow Operation Temperature 2-04°F (-04°C) Vindow Vindow Vindow Operation Temperature 2-104°F (-04°C) Vindow Vindow Vindow Operation Temperature Vindow Vindow Vindow Vindow Operation Temperature Vindow<	Audio Output	2 Channel 16-bit AAC	Height	9.125"
Ar Receiver Base: internal antenna. Both are omnidirectional.Widh16°Power AdapterUS BA Cdapter SV A outputHeight16.25°ForeDeph06.75°16.75°Power OnBueMater Carton Qu.24°Operating RangeUo 50 feet (15m)Mater Carton Qu.24°Operating System Requirements100 feet (15m)Mater Carton Qu.40.050Android4.20 returnMater Carton Qu.0.8030.06MindowsVindows 10Mit Nach Carton Qu.0.15010.150ForiormentVindows 10Not Soft R1 (No Condensation)Vindows 10Vindows 10AndroidMater Carton Qu.Vindows 10Vindows 10Vindows 10AndroidMater Carton Qu.Vindows 10Vindows 10Vindows 10AndroidSoft R1 (No Condensation)Vindows 10Vindows 10Vindows 10AnarayNo Soft R1 (No Condensation)Vindows 10Vindows 10Vindows 10Anara	Sample Rate	48KHz, 16-bit from HDMI connector	Depth	2.25"
I de ominieccionalWath16°Pover AdapterUS BA Calapter SV1 A outputHeipfu6.25°IEDSDephDeph6.7°Pover OnBluMater Caron Qu2.4°Operating RangeUs Do Sofe (15m)Mater Caron Qu2.40°Operating System RequirementsMater Caron Qu2.40°Android4.20° betr Garon QuMater Caron Qu3.60°NindowsVindowsNindows0.150°FuriomentVindowsNindows1.50°Grader Temperature1.61°Set Set Mu1.50°AndroidSet Set Mu Condensation (15m)Set Set Set Set Set Set Set Set Set Set	Antenna Type		Master Carton	
LEDsDepth16.75Power OnBlueMaster Carton Qty.24Operating RangeUp to 50 feet (15m)WeightOperating System RequirementsMaster Carton Wt.24.051bAndroid4.2 or betterMaster Carton Wt.0.81bWindowsWindows 10Unit Wt.0.151bEnvironment14-158°F (10-70°C)Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes			Width	16"
Power OnBlueMaster Carton Qty.24Operating RangeUp 50 field (15m)WeightOperating System RequirementsValor South Carton Wt.24.05BAndroid4.2 or betterMaster Carton Wt.0.8BVindowsWindows 10Unit Vac.0.15BEnvironmentValor South Carton Carton Wt.0.15BStorage Temperature1.4158° f.10-70°C)Valor South Carton Carton Carton Carton Wt.Valor South Carton Car	Power Adapter	USB AC Adapter 5V 1A output	Height	16.25"
Android Up to 50 feet (15m) Weigh Operating System Requirements Maker Carton Wt. 4.05lb Android 4.2 or better Unit Pack Wt. 0.8lb Windows Windows 10 Unit Wt. 0.15lb Environment 14-158°F (-10-70°C) Yea Yea Kindigt 0% to 85% RH (No Condensation) Yea Yea Operation Temperature 12-04°F (-0-40°C) Yea Yea Marranty 1-Year Limited Yea Yea Hunidity 1-Year Limited Yea Yea Marranty 1-Year Limited Yea Yea	LEDs		Depth	16.75"
Operating System RequirementsMaster Carton Wt.24.05lbAndroid4.2 or betterUnit Pack Wt.0.8lbWindowsWindows 10Unit Wt.0.15lbEnvironment14-158°F (-10-70°C)Starge Temperature14-158°F (-10-70°C)Humidity10% to 85% RH (No Condensation)Starge TemperatureStarge TemperatureOperation Temperature12-104°F (0-40°C)Starge TemperatureStarge TemperatureHumidity1.Year LimitedStarge TemperatureStarge TemperatureHumidity1.Year LimitedStarge TemperatureHumidity1.Year LimitedStarge TemperatureHumidity1.Year LimitedStarge TemperatureHumidity1.Year LimitedHumidity1.Year LimitedHumidity1.Yea	Power On	Blue	Master Carton Qty.	24
Android4.2 or betterUnit Pack Wt.0.8 bWindowsWindows 10Unit Wt.0.15 bEnvironmentIIIStorage Temperature14-158°F (-10-70°C)IIHumidity10% to 85% RH (No Condensation)IIOperation Temperature22-104°F (0-40°C)IIWarranty1-Year LimitedIIHumidity1-Year Limited <t< td=""><td>Operating Range</td><td>Up to 50 feet (15m)</td><td>Weight</td><td></td></t<>	Operating Range	Up to 50 feet (15m)	Weight	
WindowsWindows 10Unit Will.0.15lbEnvironment14-158°F (-10-70°C)	Operating System Requirements		Master Carton Wt.	24.05lb
EnvironmentStorage Temperature14-158°F (-10-70°C)Humidity10% to 85% RH (No Condensation)Operation Temperature32-104°F (0-40°C)Warranty1-Year LimitedHousing	Android	4.2 or better	Unit Pack Wt.	0.8lb
Storage Temperature14-158°F (-10-70°C)Humidity10% to 85% RH (No Condensation)Operation Temperature32-104°F (0-40°C)Warranty1-Year LimitedHousing	Windows	Windows 10	Unit Wt.	0.15lb
Humidity10% to 85% RH (No Condensation)Operation Temperature32-104°F (0-40°C)Warranty1-Year LimitedHousingL	Environment			
Operation Temperature32-104°F (0-40°C)Warranty1-Year LimitedHousing	Storage Temperature	14~158°F (-10~70°C)		
Warranty 1-Year Limited Housing 1-Year Limited	Humidity	10% to 85% RH (No Condensation)		
Housing	Operation Temperature	32~104°F (0~40°C)		
	Warranty	1-Year Limited		
Case Plastic	Housing			
	Case	Plastic		