









# **SPECIFICATION**

Model Name	Radeon <sup>™</sup> RX 5700 EVOKE OC
Graphics Processing Unit	Radeon <sup>™</sup> RX 5700
Interface	PCI Express 4.0
Core Name	NAVI 10 XL
Cores	2304 units (36CU)
Core Clocks	Boost: UP to 1750 MHz
	Game: 1700 MHz
	Base: 1540 MHz
	(Game Clock is the expected GPU clock when running
	typical gaming applications, set to typical TGP (Total
	Graphics Power). Actual individual game clock results may
Mamanu Cuand	vary.)
Memory Speed	14Gbps
lemory	8GB GDDR6
lemory Bus	256-bit
Dutput	DisplayPort x 3 (v1.4) / HDMI 2.0b x 1
IDCP Support	2.2
Power consumption	225 W
ower connectors	8-pin x1
Recommended PSU	750 W
Card Dimension(mm)	254 x 129 x 51 mm
Weight (Card / Package)	892g / 1339g
Afterburner OC	Y
DirectX Version Support	12
OpenGL Version Support	4.5
Iulti-GPU Technology	Crossfire™, 2-Way (Bridgeless)(DX12)
Aaximum Displays	4
/R Ready	Y
Digital Maximum	7680x4320
Resolution	

# **CONNECTIONS**



1. DisplayPort 2. HDMI

# **FEATURE**



#### TORX FAN 3.0

Award-winning fan design combining two different fin designs for cool & quiet gaming.

## SOLID BACKPLATE

Increases toughness of the card to prevent bending while complementing the design.

## **OC PERFORMANCE**

MSI OC graphics cards are equipped with higher clock speeds out of the box for increased performance.

## **RDNA Architecture**

**VR Ready** 

A D E O N Engineered from the ground up with superior performance and power efficiency, RDNA is the architecture powering AMD's 7nm gaming GPU, delivering 1.25 performance per clock compared to previous 14nm processors. MSI Afterburner

The ultimate overclocking software with advanced control

Certified to provide the performance required for a smooth

options and real-time hardware monitor.

experience in your VR adventures.





AMD FreeSync™ Puts an end to choppy gameplay and broken frames with fluid, artifact-free performance at virtually any framerate.

hange without notice

