

## Protect It! 7-Outlet Surge Protector, 6 Right-Angle Outlets, 4 ft. (1.22 m) Cord, 1080 Joules, Diagnostic LED, Black Housing

MODEL NUMBER: TLP74RB



Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise. Recommended for any desktop, network or home application requiring AC line protection.

### Features

**1080-Joule Surge Protection for Home or Office Electronics** Protects your computer, printer, scanner, router, modem and other small home electronics against surges and spikes Recommended for any desktop, network or home electronics application requiring AC line protection Full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss Exceeds IEEE 587 Category A and B surge suppression specifications

**7 Outlets Accept Wide Range of Electronic Devices** 6 NEMA 5-15R AC outlets placed at a right angle to simplify cord management Special end outlet designed for bulky transformers without blocking other outlets

**Premium Safety Features** Lighted on/off switch provides one-touch control over connected equipment Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required Diagnostic LED confirms protection status at a glance Conforms to current UL 1449 3rd Edition safety standards

**Fits Effortlessly Into Your Workstation** 4-ft. (1.22 m) AC power cord with NEMA 5-15P plug reaches nearby outlets Keyhole slots on bottom panel provide convenient wall or desk mounting options Black plastic housing designed for long life

**Backed by Ultimate Lifetime Insurance** \$25,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

### Highlights

- 6 right-angle NEMA 5-15R outlets (7 total)
- 1080-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 4 ft. AC power cord with NEMA 5-15P plug

### Package Includes

- TLP74RB Protect It! 7-Outlet Surge Protector, Black Housing
- Owner's manual

## Specifications

### OVERVIEW

UPC Code

037332155665



Powering Business Worldwide

TRIPP LITE  
SERIES

| INPUT                              |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| Nominal Input Voltage(s) Supported | 120V AC                                                                      |
| Recommended Electrical Service     | 120V (110-125V)                                                              |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                |
| Input Cord Gauge (AWG)             | 14                                                                           |
| Voltage Compatibility (VAC)        | 120                                                                          |
| Maximum Surge Amps                 | 36000                                                                        |
| Input Plug Type                    | NEMA 5-15P                                                                   |
| Input Cord Details                 | SJT                                                                          |
| Input Cord Length (ft.)            | 4                                                                            |
| Right-Angle Plug                   | No                                                                           |
| Input Cord Length (m)              | 1.22                                                                         |
| Integrated Cord Clip               | No                                                                           |
| OUTPUT                             |                                                                              |
| Frequency Compatibility            | 60 Hz                                                                        |
| Output (Watts)                     | 1800                                                                         |
| Output Receptacles                 | (7) 5-15R                                                                    |
| Circuit Breaker (amps)             | 15                                                                           |
| Transformer Accommodation          | (4) Yes                                                                      |
| Outlet Orientation                 | Single row                                                                   |
| Right-Angle Outlets                | Yes                                                                          |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                              |
| Diagnostic LED(s)                  | Yes                                                                          |
| Switches                           | Combination AC circuit breaker and 2 position on/off power switch            |
| Diagnostic LED Details             | Built-in LED confirms suppressor "protection present" (green) status         |
| SURGE / NOISE SUPPRESSION          |                                                                              |
| AC Suppression Joule Rating        | 1080                                                                         |
| AC Suppression Response Time       | < 1 ns                                                                       |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating          | 400V                                                                         |
| EMI / RFI Filtering                | Yes                                                                          |
| Automatic Shut-Off                 | Yes                                                                          |
| DATALINE SURGE SUPPRESSION         |                                                                              |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                            |                                                                                                                                    |
|------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Cable (Coax) Protection                                    | No                                                                                                                                 |
| Network (Ethernet) Protection                              | No                                                                                                                                 |
| Telephone/DSL Protection                                   | No                                                                                                                                 |
| <b>PHYSICAL</b>                                            |                                                                                                                                    |
| Material of Construction                                   | Plastic                                                                                                                            |
| Power Cord Color                                           | Black                                                                                                                              |
| Housing Color                                              | Black                                                                                                                              |
| Mounting Holes or Slots                                    | No                                                                                                                                 |
| Slot or Hole Mount Measurement (Center to Center)          | 300 mm                                                                                                                             |
| Outlets Measurement (Center to Center)                     | 28.5mm                                                                                                                             |
| Receptacle Color                                           | Black                                                                                                                              |
| Shipping Dimensions (hwd / in.)                            | 14.00 x 1.75 x 4.50                                                                                                                |
| Shipping Dimensions (hwd / cm)                             | 35.56 x 4.44 x 11.43                                                                                                               |
| Shipping Weight (lbs.)                                     | 1.20                                                                                                                               |
| Shipping Weight (kg)                                       | 0.54                                                                                                                               |
| Unit Dimensions (hwd / in.)                                | 1.330 x 2.040 x 12.400                                                                                                             |
| Unit Dimensions (hwd / cm)                                 | 3.38 x 5.18 x 31.50                                                                                                                |
| Unit Weight (lbs.)                                         | 1.04                                                                                                                               |
| Unit Weight (kg)                                           | 0.47                                                                                                                               |
| Input Cord Color                                           | Black                                                                                                                              |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |                                                                                                                                    |
| Rotatable Outlets                                          | No                                                                                                                                 |
| Antimicrobial                                              | No                                                                                                                                 |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |                                                                                                                                    |
| Product Certifications                                     | CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed            |
| Product Compliance                                         | RoHS                                                                                                                               |
| <b>WARRANTY &amp; SUPPORT</b>                              |                                                                                                                                    |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                                          |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000&nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |



*Powering Business Worldwide*

TRIPP LITE  
SERIES

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.