

## USB-A to RJ45 Serial Rollover Cable (M/M) - Cisco Compatible, 250 Kbps, 6 ft. (1.83 m), Gray

MODEL NUMBER: U209-006-RJ45-X



Connects your computer or laptop's USB port to your Cisco modem, router, firewall, switch or other serial-based Cisco device with a console port.

### Features

**Connects Computer's USB Port to Cisco Device** Connect computer or laptop to Cisco modem, router, firewall, switch or other serial-based Cisco device with a console port  
 Works with older and new Cisco models  
 6 ft. long

**Top-of-the-Line Performance** Supports data transfer rates up to 250 Kbps  
 Supports remote wake-up and power management  
 Utilizes FTDI chipset.

**Easy to Use** No other cables or adapters needed  
 No external power required  
 Driver CD included (drivers also available online for download if your computer has no CD drive)

### Highlights

- Supports data transfer rates up to 250 Kbps
- Supports remote wake-up and power management
- Compatible with Windows, Mac and Linux
- No cables, adapters or external power required

### System Requirements

- Computer with available USB port
- Cisco device with available RJ45 console port
- Windows, Mac or Linux operating system

### Package Includes

- U209-006-RJ45-X USB to RJ45 Cisco Serial Rollover Cable
- Driver CD
- Owner's manual

## Specifications

OVERVIEW	
UPC Code	037332190017
Technology	USB
PHYSICAL	
Color	Gray
Cable Outer Diameter (OD)	2.5 mm
Cable Jacket Material	PVC
Wire Gauge (AWG)	26
Cable Length (ft.)	6
Cable Length (m)	1.8



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

Cable Length (in.)	72
Material of Construction	PVC
Shipping Dimensions (hwd / cm)	3.05 x 11.94 x 10.41
Shipping Dimensions (hwd / in.)	1.20 x 4.70 x 4.10
Shipping Weight (kg)	0.11
Shipping Weight (lbs.)	0.24
Unit Packaging Type	Box
Unit Weight (kg)	0.11
Unit Weight (lbs.)	0.2425
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32 to 104°F (0 to 40°C)
Storage Temperature Range	-4 to 140°F (-20 to 60°C)
Relative Humidity	0% to 90% RH (Non-Condensing)
<b>CONNECTIONS</b>	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	RJ45 (MALE)
Connector Plating	Gold
<b>FEATURES &amp; SPECIFICATIONS</b>	
Driver Required	Yes
<b>STANDARDS &amp; COMPLIANCE</b>	
Certifications	CE, FCC, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>