

Spec Sheet

50 ft High Speed HDMI® Cable - Ultra HD 4k x 2k HDMI Cable - HDMI to HDMI M/M

StarTech ID: HDMM50



The HDMM50 High Speed HDMI® cable (50 ft.) features 2 gold-plated HDMI (male) connectors and durable high quality construction to provide a dependable HDMI to HDMI connection between devices such as Blu-Ray Disc[™] players, HDTVs, DVD Players, stereo receivers, projectors and more at a distance of up to 50-feet without the need of a signal booster.

This high quality HDMI cable fully supports 1080p+ resolutions at up to 120Hz refresh rate, with life-like color. To accommodate the demands of future high definition devices, such as increased resolutions and higher frame rates, this Ultra HD cable supports resolutions up to 4k x 2k.

The HDMM50 50-foot HDMI cable is backed by StarTech.com's Lifetime Warranty.

About StarTech.com HDMI to HDMI Cables:

StarTech.com High Speed HDMI digital video and audio cables are expertly designed and constructed of only top quality materials to ensure high quality, high definition performance. The HDMI standard combines high bandwidth video and multi-channel digital audio into a single cable, and provides crystal clear image resolution.

Applications

Connecting high-definition A/V devices such as Blu-Ray Disc[™] players, HDTVs, DVD Players, DVRs, game consoles, projectors etc.

Features

- 2x HDMI® Male Connectors
- Gold-plated HDMI connectors
- High quality construction
- Supports Ultra HD Resolutions up to 4k x 2k



Hard-to-find made easy*

Technical Specifications

Warranty	Lifetime
Connector Plating	Gold
Cable Jacket Type	PVC - Polyvinyl Chloride
Cable Shield Type	Aluminum-Mylar Foil with Braid
Connector A	1 - HDMI (19 pin) Male
Connector B	1 - HDMI (19 pin) Male
Color	Black
Connector Style	Straight
Wire Gauge	24 AWG
Cable Length	50 ft [15.2 m]
Product Length	50 ft [15.2 m]
Product Weight	3.7 lb [1.7 kg]
Package Quantity	1
Shipping (Package) Weight 3.8 lb [1.7 kg]	
Included in Package	1 - 50ft High Speed HDMI® Cable - HDMI - M/M

Certifications, Reports and Compatibility

