

Overview

Aruba 370EX Series Hazardous Location Access Points

High-performance 802.11ac Wave 2 for hazardous locations and harsh outdoor environments

In outdoor and environmentally challenging locations such as oil rigs, mining facilities, and industrial plants, networks need to be protected from extreme temperatures, flammable gas, vapor, and dust concentrations. With Class 1 Division 2 and ATEX Zone 2 certifications, the Aruba 370EX Series Access Points deliver hardened multi-gigabit Wi-Fi to hazardous locations.

The 370EX series provides a maximum aggregate data rate of over 2 Gbps (2.4GHz: 300Mbps; 5GHz: 1,733 Mbps) as well as multi-user MIMO (MU-MIMO), 4 spatial streams (4SS), and optional 160MHz channel bandwidth (VHT160) to quickly add performance and capacity to existing or new wireless networks.

Purpose-built to survive in the harshest environments, the 370EX Series have undergone extensive certification testing (Class 1 Division 2 and ATEX Zone 2, and IP66/67) to demonstrate the ability to withstand exposure to high and low temperature extremes, windspeeds up to 165 mph, and tolerate persistent moisture, precipitation, and dust and salt sprays for extended periods of time. All electrical interfaces include industrial strength surge protection.



Aruba 370EX Series – Front View

Overview

Key Features

- Deliver gigabit Wi-Fi to outdoor and extreme environments.
 - 2 Gbps of maximum throughput.
 - WPA3 and Enhanced Open security.
 - Patented ClientMatch technology resolves sticky client issues and optimizes Wave 2 performance.
 - AI-powered AirMatch automates RF optimization.
 - IoT-ready with integrated Bluetooth Low Energy (BLE).
 - Participates in Aruba's Dynamic Segmentation solution.
-



Standard Features

MU-MIMO-aware Client Optimization

The 370EX Series includes Aruba's patented ClientMatch technology to eliminate sticky client issues while optimizing 802.11ac Wave 2 performance. These APs continuously gather session performance metrics to steer mobile devices to the best-available AP – even while users roam. With MU-MIMO awareness, ClientMatch can group MU-MIMO capable devices together to increase network capacity and efficiency. ClientMatch also participates in Aruba's AI-powered Mobility solution.

IoT-Ready

Like all Aruba Wi-Fi 6 APs, the 370EX Series includes an integrated Bluetooth Low Energy radio to simplify the deployment and management of location services, asset tracking services, security solutions and IoT sensors. This allows organizations to leverage the 360 Series as an IoT platform, which eliminates the need for an overlay infrastructure and additional IT resources.

Simple and Secure Access

To simplify policy enforcement, the Aruba 370EX Series uses Aruba's policy enforcement firewall (PEF) feature to encapsulate all traffic from the AP to the Mobility Controller (or Gateway) for end-to-end encryption and inspection. Policies are applied based on user role, device type, applications, and location. This reduces the manual configuration of SSIDs, VLANs and ACLs. PEF also serves as the underlying technology for Aruba Dynamic Segmentation.

Unique Features:

- WPA3 and Enhanced Open
 - Support for stronger encryption and authentication is provided via the latest version of WPA for enterprise protected networks.
 - Enhanced Open offers seamless new protection for users connecting to open networks where each session is automatically encrypted to protect user passwords and data on guest networks.
 - WPA2-MPSK
 - MPSK enables simpler passkey management for WPA2 devices – should the Wi-Fi password on one device or device type change, no additional changes are needed for other devices. Requires ClearPass Policy Manager.
 - VPN Tunnels
 - In Remote AP (RAP) and IAP-VPN deployments, the Aruba 318 Series can be used to establish a secure SSL/IPSec VPN tunnel to a Mobility Controller that is acting as a VPN concentrator.
 - Trusted Platform Module (TPM)
 - For enhanced device assurance, all Aruba APs have an installed TPM for secure storage of credentials and keys, and boot code.
 - Flexible operations and management
 - Controller-less (Instant) mode - For enhanced device assurance, all Aruba APs have an installed TPM for secure storage of credentials and keys, and boot code.
https://www.arubanetworks.com/assets/tg/TB_Aruba-Instant-Mode.pdf
 - Mobility Controller mode - For optimized network performance, roaming and security, APs tunnel all traffic to a mobility controller for centrally managed traffic forwarding and segmentation, data encryption, and policy enforcement.
https://www.arubanetworks.com/assets/ds/DS_ArubaOS.pdf
 - Other management options - Aruba offers two network management options: cloud-based Aruba Central or Aruba AirWave for on-prem deployments. For organizations with the need for more flexible services, higher scale and performance, learn about the next generation management capabilities of Aruba Central
https://www.arubanetworks.com/assets/ds/DS_ArubaCentral.pdf, an AI powered network operations solution.
-



Standard Features

Additional Features

- Zero Touch Provisioning - APs can be factory-shipped and zero-touch provisioned through Aruba Central or AirWave using a cloud-based service to reduce deployment time, centralize configuration, and manage inventory.
 - Advanced Cellular Coexistence - Minimizes interference from 3G/4G LTE cellular networks, distributed antenna systems (DAS), and commercial small cell or femtocell equipment.
 - Hardened, industrial design - Extends the temperature range capabilities of indoor access points for environments that lack heating and cooling. It also provides sealed connector interfaces to protect against dust and moisture.
-

Warranty

- **Limited lifetime warranty**
-



Configuration Information

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

BTO Models

Remarks	Description	SKU
	Unified Outdoor Access Points	
6	Aruba AP-375EX (US) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R3P69A
6	Aruba AP-375EX (RW) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R3P70A
6	Aruba AP-375EX (JP) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R3P71A
6	Aruba AP-375EX (IL) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R3P72A
6	Aruba AP-375EX (EG) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R3P73A
6	Aruba AP-377EX (US) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Directional Ant Otdr HazLoc AP	R3P90A
6	Aruba AP-377EX (RW) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Directional Ant Otdr HazLoc AP	R3P93A
6	Aruba AP-377EX (JP) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Directional Ant Otdr HazLoc AP	R3P94A
6	Aruba AP-377EX (IL) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Directional Ant Otdr HazLoc AP	R3P95A
6	Aruba AP-377EX (EG) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Directional Ant Otdr HazLoc AP	R3P96A
7	Aruba AP-375ATEX (US) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R7J11A
7	Aruba AP-375ATEX (RW) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R7J10A
7	Aruba AP-375ATEX (JP) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R7J09A
7	Aruba AP-375ATEX (IL) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor HazLoc AP	R7J08A
7	Aruba AP-375ATEX (EG) 802.11n/ac Dual 2x2:2/4x4:4 Radio Int Omni Antenna Outdoor Hazloc AP	R7J07A

Notes: [OCA Only Model Selection Form - Aruba > Wireless > Access Points > Outdoor / Rugged > 370EX Series](#)

Configuration Rules

- 6 The EX APs should be used in Class 1 Div 2 required locations (C1D2)
- 7 The ATEX APs should be used in ATEX Zone 2 required locations (ATEX Zone 2)

Mounting Accessories

AP Mount Kits

Std (Min 0 // max 1) User Selection (min 0 // max 1)

Aruba AP-OUT-MNT-V1A Outdoor AP Pole/Wall Long Mount Kit v2	R9H97A
AP-270-MNT-V2 AP-270 Series Outdoor Pole/Wall Short Mount Kit	JW053A
AP-270-MNT-H1 AP-270 Series Outdoor AP Hanging or Tilt Install Mount Kit	JW054A
AP-270-MNT-H2 AP-270 Series Access Flush Wall or Ceiling Mount	JW055A
AP-270-MNT-H3 AP-270 Series Outdoor AP Hanging or Dual-Tilt Install Mount Kit	R6W11A

- Notes:**
- For 375EX:
 - o V1A bracket most often used for pole mount.
 - o V2 bracket most often used for wall mount.
 - o H1 bracket most often used for hanging from inclined or horizontal structure.
 - o The AP-375EX chassis does not ship with bracket
 - For 377EX:
 - o H1 bracket most often with AP-377 for mounting to a wall. Allows chassis tilt in single axis.
 - o H3 bracket most often with AP-377 for mounting to a wall. Allows chassis dual-tilt in two axes.
 - o V1A and V2 brackets can be used but will result in the AP-377 pointing down.
 - o The AP-377EX chassis does not ship with bracket.



Configuration Information

Transceivers

SFP

Std (Min 0 // max 2) User Selection (min 0 // max 2)

SFP-LX Extended Temperature 1000BASE-LX SFP 1310nm LC Connector Pluggable GbE XCVR Q8N52A

SFP-SX Extended Temperature 1000BASE-SX SFP 850nm LC Connector Pluggable GbE XCVR Q8N53A

CKIT-EX-OD-SFP Outdoor HazLoc SFP Fiber Strain Relief R7L09A

- Notes:**
- Add Qty 1 of Q8N54A if this XCVR is selected.
 - R7L09A is a mandatory item if an SFP will be used.

Power Options

Remarks	Description	SKU
---------	-------------	-----

PoE Power Options

Std (Min 0 // max 1) User Selection (min 0 // max 1)

PD-9501-5GCO-AC 60W 802.3bt Smart Rate Outdoor Surge Protection Midspan Injector R7T40A

PD-9501-5GCO-DC 60W 802.3bt Smart Rate Outdoor Surge Protection Midspan Injector R7T41A

Aruba PD-9001GO-NA 30W 802.3at PoE+ 10/100/1000 Otdr Surge Prot NA Power Cord Mdspan Injector JW700A

Aruba PD-9001GO-INTL 30W 802.3at PoE+ 10/100/1000 Outdoor Surge Prot Intl Power Cord Injector JW701A

Aruba PD-9001GO-DC 30W 802.3at PoE+ 10/100/1000 12-24V DC in Outdoor Surge Prot Midspan Injector JW630A

AP-POE-ATSR 1-Port Smart Rate 802.3at 30W midspan injector R6P67A

- Notes:**
- If this Power Injector is selected, bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu
 - These devices are not HAZLOC rated so must be installed in a non rated area.
 - Indoor Injector provides no surge protection.
 - Indoor injector requires indoor AC power cord
 - AP-37x may be powered by PoE Only.
 - Power cord for JW630A, R7T40A, R7T41A should be provided by installer
 - R7T40A and R7T41A do not include a power cord, power cord must be constructed by installer using the included power connector parts and assembled per the user guide by a certified installer

AC Power Cord for Indoor PoE Injector

PC-AC-ARG AC Power Cord (Argentina) 250V/10A 1.8m C13 to IRAM 2073 JW113A

PC-AC-AUS AC Power Cord (Australia) 250V/10A 1.8m C13 to AS3112 JW114A

PC-AC-BR AC Power Cord (Brazil) 250V/10A 1.8m C13 to NBR 14136 JW115A

PC-AC-CHN AC Power Cord (China) 250V/10A 1.8m C13 to GB2099 JW116A

PC-AC-DEN AC Power Cord (Denmark) 250V/10A 1.8m C13 to AFSNIT 107-2-D1 JW117A

PC-AC-EC AC Power Cord (Europe) 250V/10A 1.8m C13 to CEE7/7 JW118A

PC-AC-IN AC Power Cord (India) 250V/6A 1.8m C13 to IS1293 JW119A

PC-AC-IL AC Power Cord (Israel) 250V/10A 1.8m C13 to SI32 JW120A

PC-AC-IT AC Power Cord (Italy) 250V/10A 1.8m C13 to CEI 23-50 JW121A

PC-AC-JPN AC Power Cord (Japan) 125V/12A 1.8m C13 to JISC 8303 JW122A

PC-AC-KOR AC Power Cord (Korea) 250V/7A 1.8m C13 to KSC 8305 JW123A

PC-AC-NA AC Power Cord (North America) 125V/10A 1.8m C13 to NEMA 5-15P JW124A

PC-AC-SWI AC Power Cord (Switzerland) 220V/10A 1.8m C13 to SEV 1011 JW125A

PC-AC-TW AC Power Cord (Taiwan) 125V/7A 1.8m C13 to CNS 10917 JW126A

PC-AC-UK AC Power Cord (United Kingdom) 250V/10A 1.8m C13 to BS1363 JW127A

PC-AC-ZA AC Power Cord (South Africa) 250V/10A 1.8m C13 to SANS 164-1 JW128A



Configuration Information

Power Injector Mounts

Std (Min 0 // max 1) User Selection (min 0 // max 1)

Aruba PD-MOUNT-OD Outdoor PoE Midspan Injectors Pole/Mast Mount Kit

JW620A

Notes: This is optional but recommended for outdoor injectors

Spares

Spare Items

Std (Min 0 // max 99) User Selection (min 0 // max 99)

Aruba 9004-MNT-19 9004 Series 19-inch Rack Mount Kit

R1B30A

Notes:

- Bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu
- Qty 1 Power Adapter is included with Aruba Gateway

Accessories

Remarks Description

SKU

Spare Items

Std (Min 0 // max 99) User Selection (min 0 // max 99)

Outdoor AP Covers and Glands 1-pk M25/5-pk M20 Cover/2-pk M16 Cover/5-pk M20 Gland/2-pk Ground Kit

Q8N47A

Notes: This is a collection of extra covers and cabling glands, replicating what is in the shipping box

Outdoor AP Metric to Standard M20 to 1/2 inch NPT 5-pk Thread Adapter

Q8N48A

Notes:

- This is a thread adapter normally used to allow direct interface for 1/2" NPT conduit.
- Spares of items that are shipped with the AP-370 chassis

Step 8: Add Software (Optional)

Compatible with the 304/305 AP

Remarks Description

SKU

Aruba Central AP Foundation 1 year Subscription E-STU

Q9Y58AAE

Aruba Central AP Foundation 3 year Subscription E-STU

Q9Y59AAE

Aruba Central AP Foundation 5 year Subscription E-STU

Q9Y60AAE

Aruba Central AP Foundation 7 year Subscription E-STU

Q9Y61AAE

Aruba Central AP Foundation 10 year Subscription E-STU

Q9Y62AAE

Aruba Central AP Advanced 1yr Subscription E-STU

Q9Y63AAE

Aruba Central AP Advanced 3yr Subscription E-STU

Q9Y64AAE

Aruba Central AP Advanced 5yr Subscription E-STU

Q9Y65AAE

Aruba Central AP Advanced 7yr Subscription E-STU

Q9Y66AAE

Aruba Central AP Advanced 10yr Subscription E-STU

Q9Y67AAE

Notes: Add the Central Cloud Skus to the Aruba Catalog as Standalone:
Aruba > Network Management > Central > Cloud Services

Aruba Central On-Premises AP Foundation 1 year Subscription E-STU

R6U63AAE

Aruba Central On-Premises AP Foundation 3 year Subscription E-STU

R6U64AAE

Aruba Central On-Premises AP Foundation 5 year Subscription E-STU

R6U65AAE

Aruba Central On-Premises AP Foundation 7 year Subscription E-STU

R6U66AAE

Aruba Central On-Premises AP Foundation 10 year Subscription E-STU

R6U67AAE

Notes: Add the Central On-Prem Skus to the Aruba Catalog as Standalone:
Aruba > Network Management > Central > On-Prem Services



Technical Specifications

RF Performance Table		
Band, rate	Maximum transmit power (dBm) per transmit chain ⁶	Receiver sensitivity (dBm) per receive chain ⁶
802.11b 2.4 GHz		
1Mbps	25	-95
2Mbps	25	-93
5.5Mbps	25	-90
11Mbps	25	-88
802.11g 2.4 GHz		
6Mbps	25	-93
54Mbps	19	-75
802.11n HT20 2.4 GHz		
MCS0/8	25	-93
MCS7/15	18	-71
802.11n HT40 2.4 GHz		
MCS0/8	22	-90
MCS11/15	18	-68
802.11a 5 GHz		
6Mbps	22	-93
54Mbps	19	-75
802.11n HT20 5 GHz		
MCS0/8	22	-93
MCS7/15	18	-71
802.11n HT40 5 GHz		
MCS0/8	22	-90
MCS7/15	18	-68
802.11ac VHT20 5 GHz		
MCS0	22	-93
MCS9	16	-68
802.11ac VHT40 5 GHz		
MCS0	22	-90
MCS9	15	-63
802.11ac VHT80 5 GHz		
MCS0	22	-87
MCS9	15	-61
802.11ac VHT80 5 GHz		
MCS0	22	-86
MCS9	15	-57



Technical Specifications

Wi-Fi radio specifications

- AP type: Outdoor hardened, dual radio, 5 GHz 802.11ac 4x4 MIMO and 2.4 GHz 802.11n 2x2 MIMO
- Software-configurable dual radio supports 5 GHz (Radio 0) and 2.4 GHz (Radio 1)
- 5GHz: Four spatial stream Multi User (MU) MIMO for up to 1,733 Mbps wireless data rate to up to three MU-MIMO capable client devices simultaneously
- 5GHz: Four spatial stream Single User (SU) MIMO for up to 1,733 Mbps wireless data rate to individual 4x4 VHT80 or 2x2 VHT160 client devices
- 2.4GHz radio: Two spatial stream Single User (SU) MIMO for up to 300 Mbps wireless data rate to individual 2x2 HT40 client devices
- Support for up to 256 associated client devices per radio, and up to 16 BSSIDs per radio
- Supported frequency bands (country-specific restrictions apply):
 - 2.400 to 2.4835GHz
 - 5.150 to 5.250GHz
 - 5.250 to 5.350GHz
 - 5.470 to 5.725GHz
 - 5.725 to 5.850GHz
- Available channels: Dependent on configured regulatory domain
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM (proprietary extension)
- Transmit power: Configurable in increments of 0.5 dBm
- Maximum (conducted) transmit power (limited by local regulatory requirements):
 - 2.4GHz band: +25 dBm per chain, +28dBm aggregate (2x2)
 - 5GHz band: +22 dBm per chain, +28dBm aggregate (4x4)
- **Notes: Conducted transmit power levels exclude antenna gain**
- Maximum EIRP (limited by local regulatory requirements):
 - 2.4 GHz band:
 - 375EX: 32.0 dBm EIRP
 - 375ATEX: 25.6dBm EIRP
 - 377EX: 34.4 dBm EIRP
 - 5 GHz band:
 - 375EX: 35.6 dBm EIRP
 - 375ATEX: 32dBm EIRP
 - 377EX: 36 dBm EIRP
- Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
- Maximum ratio combining (MRC) for improved receiver performance
- Cyclic delay/shift diversity (CDD/CSD) for improved downlink RF performance
- Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz channels
- Space-time block coding (STBC) for increased range and improved reception
- Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
- Transmit beam-forming (TxBF) for increased signal reliability and range
- Supported data rates (Mbps):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
 - 802.11n (2.4GHz): 6.5 to 300 (MCS0 to MCS15)
 - 802.11n (5GHz): 6.5 to 600 (MCS0 to MCS31)
 - 802.11ac: 6.5 to 1,733 (MCS0 to MCS9, NSS = 1 to 4 for VHT20/40/80, NSS = 1 to 2 for VHT160)
- 802.11n high-throughput (HT) support: HT 20/40

Technical Specifications

- 802.11ac very high throughput (VHT) support: VHT 20/40/80/160
 - 802.11n/ac packet aggregation: A-MPDU, A-MSDU
-

Series specifications

- AP-375EX
 - 5GHz 802.11ac 4x4 MU-MIMO (1,733 Mbps max rate)
 - Internal Omni Antennas 4.6 dBi
 - 2.4 GHz 802.11n 2x2 MIMO (300 Mbps max rate) radios
 - Internal Omni Antennas 4.0 dBi
 - AP-377EXEX
 - 5GHz 802.11ac 4x4 MUMIMO (1,733 Mbps max rate)
 - Internal 80°H x 80°V Directional Antennas 6.3 dBi
 - 2.4 GHz 802.11n 2x2 MIMO (300 Mbps max rate) radios
 - Internal 80°H x 80°V Directional Antennas 6.4 dBi
-

Power

- Worst-case power consumption from the AP: 23W
 - Power sources sold separately
 - Power over Ethernet (PoE+): 802.3at-compliant
-

Other interfaces

- One 10/100/1000BASE-T Ethernet network interfaces (RJ-45)
 - Autosensing link speed and MDI/MDX
 - 802.3az Energy Efficient Ethernet (EEE)
 - One 1000BASE-X SFP port
 - Bluetooth Low Energy (BLE) radio
 - Up to 4dBm transmit power (class 2) and 91 dBm receive sensitivity
 - Visual indicator (multi-color LED): For system and radio status
 - Reset button: Factory reset (during device power up)
 - Micro USB console interface
 - Kensington security slot
-

Mounting

- AP-270-MNT-V1
 - AP-270-MNT-V2
 - AP-270-MNT-H1
 - AP-270-MNT-H2
 - AP-270-MNT-H3
-

Minimum operating system software versions

- ArubaOS and Aruba InstantOS 8.3.0.0
-

Mechanical specifications

- AP-375EX/375ATEX Dimensions/weight (excluding mount bracket):
 - 23 cm (W) x 24 cm (D) x 27 cm (H)
 - 9.0" (W) x 9.4" (D) x 10.6" (H)
 - 2.4 kg/5.3 lbs
 - AP-377EX Dimensions/weight (excluding mount bracket):
 - 23 cm (W) x 22 cm (D) x 13 cm (H)
 - 9.0" (W) x 8.7" (D) x 5.1" (H)
 - 2.1 kg/4.6 lbs
-



Technical Specifications

Environmental specifications

- Operating conditions
 - Temperature: -40° C to +65° C / -40° F to +149° F
 - Humidity: 5% to 95% non-condensing
 - Storage and transportation conditions
 - Temperature: -40° C to +70° C / -40° F to +158° F
 - Operating Altitude: 3,000 m
 - Water and Dust
 - IP66/67
 - Salt Tolerance
 - Tested to ASTM B117-07A Salt Spray 200hrs
 - Wind Survival: Up to 165 Mph
 - Shock and Vibration ETSI 300-19-2-4
-

Regulatory compliance

- FCC/ISED
 - CE Marked
 - RED Directive 2014/53/EU
 - EMC Directive 2014/30/EU
 - Low Voltage Directive 2014/35/EU
 - UL/IEC/EN 60950
 - EN 60601-1-1, EN60601-1-2
-

For more country-specific regulatory information and approvals, please see your Aruba representative.

Regulatory model numbers

- AP-375EX: APEX0375
 - AP-375ATEX: APEX0375
 - AP-377EX: APEX0377
-

Certifications

- CB Scheme Safety, cTUVus
- UL2043 plenum rating
- Wi-Fi Alliance certified 802.11a/b/g/n
- Wi-Fi CERTIFIED™ ac (with wave 2 features)
- Passpoint® (Release 2) with ArubaOS and Instant 8.3+
- Class 1 Division 2 certified
- ATEX Zone 2 certified*

Notes: *Pending completion from certification lab.






Summary of Changes

Date	Version History	Action	Description of Change
21-Nov-2022	Version 8	Changed	Configuration Information section was updated.
06-Dec-2021	Version 7	Changed	SKUs were added in Configuration Information section.
15-Mar-2021	Version 6	Changed	SKUs were added in Configuration Information section.
07-Dec-2020	Version 5	Changed	Standard Features, Configuration Information, and Technical Specifications sections were updated. New SKUs were added. SKUs were removed.
02-Nov-2020	Version 4	Changed	Configuration Information section was updated. New SKUs were added.
08-Sep-2020	Version 3	Changed	Configuration Information section was updated. New SKUs were added.
09-Dec-2019	Version 2	Changed	Overview and Standard Features
05-Aug-2019	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00067746enw - 16432 - Worldwide - V8 - 21-November-2022