# **RealCam PTZ Camera**

Give everyone the best view in the room

Part #: INA-PTZ-3

Add the InFocus RealCam pan/tilt/zoom professional-quality HD camera bundle to your Mondopad (or any other PC) to make your video conferencing meetings shine.

The RealCam, which features a full HD wide-angle video camera, delivers intricately detailed, full HD 1080p video to capture everyone and everything you want to show.

Make applications like Microsoft Lync, Skype, and GoToMeeting come alive with realistic video quality.

Plug it directly into a Mondopad or other PC with USB 3.0 or HDMI, without a separate capture device.



INFOCUS

- Full HD 1080p resolution
- Pan, tilt and zoom
- 72.5-degree wide-angle lens
- USB3.0 ultra-high speed interface
- H.265 support enables Full HD images at ultra-low bandwidth
- 12x optical zoom and 32x digital zoom
- Use any PC with any software or OS via USB
- Pan angle of -170° to +170°
- Tilt angle of -30° to +90°

## Broad Range, Flexible Control, Vivid Images

**Quiet pan/tilt action** covers a wide range, ideal for capturing extensive areas when face-to-face discussions are critical.

**225 position presets** make it quick and easy to access the precise settings you use most for pan, tilt, and zoom, focus position, exposure mode, and white balance mode.

Many options to connect to your device. With HDMI, USB3.0 and Network Stream this camera can fit most needs. Plus the RealCam can multicast to all at once.

Control over your network with RS232, RS485 or USB UVC compatibility.





## Specifications\*

opoomoationo	
Video System	HD: 1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30,
	1080p/25, 720p/60, 720p/50, 720p/30, 720p/25
	SD: 480i, 576i
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Zoom Minimal III unitation	12x optical, 32x digital
Minimal Illumination	0.05 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual Support
Backlight Compensation Digital Noise Reduction	
Video S/N	2D&3D Digital Noise Reduction ≥55dB
Horizontal Angle of View	72.5° to 6.9°
Vertical Angle of View	44.8° to 3.9°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30° to +90°
Pan Speed Range	1.7° to 100°/s
Tilt Speed Range	1.7° to 69.9°/s
H & V Flip	Support
Image Freeze	Support
Number of Preset	255
Preset Accuracy	0.1°
USB 3.0 Featured	
Operating System	Windows XP, Windows Vista, Windows 7, Windows 8, Mac OS
	X, Linux
Color System	YUV 4:2:2
Video format	USB3.0 : 1080p/60, 1080p/50, 1080p/30, 1080p/25,
	720p/60, 720p/50, 720p/30, 720p/25
	USB2.0 : 960x540p/30, 960x540p/25, 640x360p/60,
	640x360p/50,1280x720p/25
USB video communication protocol	UVC1.0
UVC PTZ	Support
IPC Features	
Video Compression	H.265/H.264/MJEPG
Video Stream	Main Stream, Sub Stream
Main Stream Resolution	1920x1080, 1280x720, 1024x576
Main Stream Resolution Sub Stream Resolution	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240
Main Stream Resolution Sub Stream Resolution Video Bit Rate	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps
Main Stream Resolution Sub Stream Resolution Video Bit Rate Bit Rate Type	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate
Main Stream Resolution Sub Stream Resolution Video Bit Rate	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps,
Main Stream Resolution Sub Stream Resolution Video Bit Rate Bit Rate Type Frame Rate	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps AAC
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps AAC 96Kbps, 128Kbps, 256Kbps
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps AAC
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps AAC 96Kbps, 128Kbps, 256Kbps
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps AAC 96Kbps, 128Kbps, 256Kbps TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output	1920x1080, 1280x720, 1024x576 720x576, 720x480, 320x240 128Kbps ~ 8192Kbps Variable Rate, Fixed Rate 50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps AAC 96Kbps, 128Kbps, 256Kbps TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output	1920x1080, 1280x720, 1024x576           720x576, 720x480, 320x240           128Kbps ~ 8192Kbps           Variable Rate, Fixed Rate           50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps           AAC           96Kbps, 128Kbps, 256Kbps           TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.           1xHDMI: Version 1.3           1xCVBS: RCA jack, 1Vp-p, 75Ω
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface	1920x1080, 1280x720, 1024x576         720x576, 720x480, 320x240         128Kbps ~ 8192Kbps         Variable Rate, Fixed Rate         50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps         AAC         96Kbps, 128Kbps, 256Kbps         TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.         1xHDMI: Version 1.3         1xCVBS: RCA jack, 1Vp-p, 75Ω         1xRJ45: 10/100/1000M Adaptive Ethernet ports
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input	1920x1080, 1280x720, 1024x576         720x576, 720x480, 320x240         128Kbps ~ 8192Kbps         Variable Rate, Fixed Rate         50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps         AAC         96Kbps, 128Kbps, 256Kbps         TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.         1xHDMI: Version 1.3         1xCVBS: RCA jack, 1Vp-p, 75Ω         1xRJ45: 10/100/1000M Adaptive Ethernet ports         1-ch: 3.5mm Audio Interface, Line In         1xUSB3.0: Type B female jack         1xUSB2.0: Type A female jack
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input	1920x1080, 1280x720, 1024x576           720x576, 720x480, 320x240           128Kbps ~ 8192Kbps           Variable Rate, Fixed Rate           50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps           AAC           96Kbps, 128Kbps, 256Kbps           TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.           1xHDMI: Version 1.3           1xCVBS: RCA jack, 1Vp-p, 75Ω           1xRJ45: 10/100/1000M Adaptive Ethernet ports           1-ch: 3.5mm Audio Interface, Line In           1xUSB3.0: Type B female jack
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input	1920x1080, 1280x720, 1024x576           720x576, 720x480, 320x240           128Kbps ~ 8192Kbps           Variable Rate, Fixed Rate           50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps           AAC           96Kbps, 128Kbps, 256Kbps           TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.           1xHDMI: Version 1.3           1xCVBS: RCA jack, 1Vp-p, 75Ω           1xRJ45: 10/100/1000M Adaptive Ethernet ports           1-ch: 3.5mm Audio Interface, Line In           1xUSB2.0: Type B female jack           1xUSS2.0: Type A female jack           1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input	1920x1080, 1280x720, 1024x576           720x576, 720x480, 320x240           128Kbps ~ 8192Kbps           Variable Rate, Fixed Rate           50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps           AAC           96Kbps, 128Kbps, 256Kbps           TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.           1xHDMI: Version 1.3           1xCVBS: RCA jack, 1Vp-p, 75Ω           1xRJ45: 10/100/1000M Adaptive Ethernet ports           1-ch: 3.5mm Audio Interface, Line In           1xUSB3.0: Type B female jack           1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P           1xRS-232 OUT: 8pin Min DIN, Max Distance: 30m, Protocol:
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/ Pelco-D/Pelco-P1xRS-232 OUT: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA network use only
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps,640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P1xRS-232 OUT: 8pin Min DIN, Max Distance: 30m, Protocol:VISCA network use only1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol:
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps,640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol:VISCA/Pelco-D/Pelco-P
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps,640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P1xRS-232 OUT: 8pin Min DIN, Max Distance: 30m, Protocol:VISCA network use only1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol:
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications	1920x1080, 1280x720, 1024x576         720x576, 720x480, 320x240         128Kbps ~ 8192Kbps         Variable Rate, Fixed Rate         50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps         AAC         96Kbps, 128Kbps, 256Kbps         TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.         1xHDMI: Version 1.3         1xCVBS: RCA jack, 1Vp-p, 75Ω         1xRJ45: 10/100/1000M Adaptive Ethernet ports         1-ch: 3.5mm Audio Interface, Line In         1xUSB3.0: Type B female jack         1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/         Pelco-D/Pelco-P         VRS-432: 20IT: 8pin Min DIN, Max Distance: 1200m, Protocol: VISCA/         Vars-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-P         JEITA type (DC IN 12V)
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications         Input Voltage	1920x1080, 1280x720, 1024x576         720x576, 720x480, 320x240         128Kbps ~ 8192Kbps         Variable Rate, Fixed Rate         50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps         AAC         96Kbps, 128Kbps, 256Kbps         TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.         1xHDMI: Version 1.3         1xCVBS: RCA jack, 1Vp-p, 75Ω         1xRJ45: 10/100/1000M Adaptive Ethernet ports         1-ch: 3.5mm Audio Interface, Line In         1xUSB3.0: Type B female jack         1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/         Pelco-D/Pelco-P         1xRS-435: 2pin phoenix port, Max Distance: 1200m, Protocol:         VISCA network use only         1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol:         VISCA/Pelco-D/Pelco-P         JEITA type (DC IN 12V)
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications         Input Voltage         Current Consumption	1920x1080, 1280x720, 1024x576         720x576, 720x480, 320x240         128Kbps ~ 8192Kbps         Variable Rate, Fixed Rate         50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fps         AAC         96Kbps, 128Kbps, 256Kbps         TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.         1xHDMI: Version 1.3         1xCVBS: RCA jack, 1Vp-p, 75Ω         1xRJ45: 10/100/1000M Adaptive Ethernet ports         1-ch: 3.5mm Audio Interface, Line In         1xUSB3.0: Type B female jack         1xUSB2.0: Type A female jack         1xRS-232 Bpin Min DIN, Max Distance: 30m, Protocol: VISCA/         Pelco-D/Pelco-P         1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol:         VISCA network use only         1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol:         VISCA/Pelco-D/Pelco-P         JEITA type (DC IN 12V)
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications         Input Voltage         Current Consumption         Operating Temperature	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xUSB2.0: Type A female jack1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/ Pelco-D/Pelco-P1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA/network use only1xR-445: 2pin Dhoenix port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-PJEITA type (DC IN 12V)DC 12V1.0A (Max)-5°C ~ 40°C
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications         Input Voltage         Current Consumption         Operating Temperature         Storage Temperature	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xUSB2.0: Type A female jack1xRS-232 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/ Pelco-D/Pelco-P1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA network use only1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-PJEITA type (DC IN 12V)DC 12V1.0A (Max)-5°C ~ 40°C-20°C ~ 60°C
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications         Input Voltage         Current Consumption         Operating Temperature         Storage Temperature         Power Consumption	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xUSB2.0: Type A female jack1xRS-232: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/ Pelco-D/Pelco-P1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA network use only1xR-485: 2pin Dhoenix port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-PJEITA type (DC IN 12V)DC 12V1.0A (Max)-5°C ~ 40°C-20°C ~ 60°C12W (Max)
Main Stream Resolution         Sub Stream Resolution         Video Bit Rate         Bit Rate Type         Frame Rate         Audio Compression         Audio Bit Rate         Support protocols         Input/Output Interface         HD Output         SD Output         Network interface         Audio Input         USB         Control Input/Output         Power Connector         Operational Specifications         Input Voltage         Current Consumption         Operating Temperature         Storage Temperature	1920x1080, 1280x720, 1024x576720x576, 720x480, 320x240128Kbps ~ 8192KbpsVariable Rate, Fixed Rate50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps, 720p: 120fps, 640x480p: 240fpsAAC96Kbps, 128Kbps, 256KbpsTCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.1xHDMI: Version 1.31xCVBS: RCA jack, 1Vp-p, 75 $\Omega$ 1xRJ45: 10/100/1000M Adaptive Ethernet ports1-ch: 3.5mm Audio Interface, Line In1xUSB3.0: Type B female jack1xUSB2.0: Type A female jack1xRS-232 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/ Pelco-D/Pelco-P1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA network use only1xRS-485: 2pin phoenix port, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-PJEITA type (DC IN 12V)DC 12V1.0A (Max)-5°C ~ 40°C-20°C ~ 60°C

\*Product specifications, terms, and offerings are subject to change at any time without notice.



#### INA-PTZ-3

### Compatible with Major Video Platforms

(up to 1080p if allowed by that service) including Microsoft Skype for Business Adobe Connect, Citrix GoToMeeting, LifeSize ClearSea, Avistar C3, Cisco Jabber, Skype, Polycom Real Presence Desktop, Radvision Scopia Desktop, and Google Hangout.

Also works with InFocus Mondopad, 121, BigConnect, and ConX.





©2016 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Collaboration That Works are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. InFocus-RealCam3-INA-PTZ-3-Datasheet-EN-28JAN16