

SL-91

SMALL FOOTPRINT WITH EPOXY KEYCAPS



iKey's innovative SL-91 mobile keyboard was designed to accommodate rugged applications in manufacturing, material handling and remote data entry. Its unique epoxy-coated keys are arranged for convenient gloved-hand use. It features a small-footprint design, mounting holes in its case and a 10-key numeric pad. Like other keyboards in the iKey line, the SL-91 is constructed using a robust polycarbonate case and industrial silicone keypad, sealing it from dust, liquids and corrosives. Features: 24 Function Keys Built-In Mounting Holes Integrated 10-Key Numeric Pad Integrated Backlighting Lightweight ABS Polycarbonate Case USB and PS/2 configurations available

Product Code SL-91

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 ft coiled (1.2m) DESIGN: PS/2 or USB Cable
KEY SWITCH	MATERIAL: Epoxy-Coated Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz +/- 0.70 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: KEYBOARD: 200mA@5V (Keyboard port) USB: 200mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	11.40" x 6.30" x 1.90" (w-h-d) 289.6mm x 160.0mm x 48.3mm
MODEL NUMBERS	SL-91-PS2: With PS/2 cable SL-91-USB: With USB cable