Product data sheet

Specifications



Overview

Presentation	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)5-15. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
Lead time	Usually in Stock

Main

Mann		
Colour	Black	
product or component type	PDU	
PDU type	Switched	
Cord length	12 ft (3.7 m)	
Number of cables	1	
provided equipment	vided equipment Cord retention bracket(s) Horizontal mounting brackets User manual Installation guide	

Complementary

Input Voltage	100 V 120 V	
Height	1.7 in (4.4 cm)	
Width	17.5 in (44.5 cm)	
Output Voltage	120 V	
Depth	4.3 in (10.8 cm)	
net weight	5.004 lb(US) (2.27 kg)	
mounting location	Front Rear	
Mounting preference	No preference	
Input Plug Type	NEMA 5-15P	
mounting mode	Rack-mounted	
Rack units	1U	
Mounting position	Horizontal	
[In] rated current	12 A	

Permissible voltage	100120 V
Input current limits	15 A
Load capacity	1440 VA
Network frequency	50/60 Hz
Outlet type and quantity	8 NEMA 5-15R

Environment

Product certifications	cUL listed UL listed	
Standards	FCC part 15 class A ICES-003	
Ambient air temperature for operation	32.000000000113.0000000000 °F (045 °C)	
Relative humidity	095 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-13.000000000149.000000000 °F (-2565 °C)	
Storage Relative Humidity	095 %	
Storage altitude	050000 ft (0.00000000015240.000000000 m)	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7 cm)
Package 1 Width	13.5 in (34.3 cm)
Package 1 Length	18.5 in (47 cm)
Package 1 Weight	7.61 lb(US) (3.45 kg)

Contractual warranty

Warranty

2 years repair or replace

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Yes