

# Product data sheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, 42U, Shock Packaging, 2000 lbs, Black, 2124H x 750W x 1070D mm

AR3150SP

### Overview

**Presentation** NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 2000 lbs (907 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).

**Lead time** Usually in Stock

### Main

**Product or Component Type** Rack enclosure

**Number of rack unit** 42U

**Provided equipment** Baying hardware  
Documentation CD  
Key(s)  
Keyed-alike doors and side panels  
Leveling feet  
Mounting Hardware  
Pre-installed casters  
Side Panels

### Physical

**Height** 78.4 in (199.1 cm)

**Width** 29.5 in (75 cm)

**Depth** 42.1 in (107 cm)

**Net Weight** 343.83 lb(US) (155.96 kg)

**Color** Black

**Mounting preference** No preference

**Mounting Mode** Not rack-mountable

**Maximum Mounting Depth** 36.02 in (91.49 cm)

**minimum mounting depth** 10.31 in (26.19 cm)

**rack width** 19"

**Marking** 14 gauge EIA mounting rail  
16 gauge front door  
16 gauge post  
16 gauge rear door  
18 gauge roof  
18 gauge side panels

**Permanent permissible load** 2250 lb(US) (1020.6 kg) dynamic  
3750 lb(US) (1701.0 kg) static

### Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Standards</b>	UL 2416 UL 60950-1 EIA-310E
------------------	-----------------------------------

## Ordering and shipping details

---

<b>GTIN</b>	731304309888
<b>Country of origin</b>	CN

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	85.8 in (217.9 cm)
<b>Package 1 Width</b>	52.008 in (132.1 cm)
<b>Package 1 Length</b>	43.5 in (110.5 cm)
<b>Package 1 Weight</b>	598.004 lb(US) (271.25 kg)

---

## Contractual warranty

---

<b>Warranty</b>	5 year repair or replace
-----------------	--------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Take-back Transparency RoHS/REACH

## Resource performance

 Take-Back Program Available

---

## Well-being performance

 Reach Free Of Svhc

---

 Toxic Heavy Metal Free

---

 Mercury Free

---

 Rohs Exemption Information Yes

---

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Pro-active compliance (Product out of EU RoHS legal scope)  
[EU RoHS Declaration](#)

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

**Circularity Profile** [End of Life Information](#)

---