## **VA1703wb**

17" VALUE SERIES WIDESCREEN LCD

WITH 8MS VIDEO RESPONSE

#### Affordable performance.

ViewSonic's 17" VA1703wb LCD brings panoramic widescreen performance to budget-conscious users. The 16:10 wide aspect ratio and high 1440x900 resolution provide AMPLE SPACE FOR MULTIPLE DOCUMENT WINDOWS, side-by-side full-page layouts, and immersive gaming that virtually surrounds the gamer. With ClearMotiv® video response, you'll get extreme clarity, amazing color and stunning brightness. The VA1703wb delivers on ViewSonic's tradition of BRILLIANT IMAGE QUALITY AND RELIABLE PERFORMANCE all at an attractive price point. It's the easy choice for gamers, home/small office users and corporate professionals.



### LIFESTYLE ENJOYMENT WORKPLACE PRODUCTIVITY

- > Fast 8ms video response delivers superior picture clarity
- > Full 17" viewable widescreen
  Displays a full, flat 17" viewable area with crisp detail and fully saturated color.
- > 1440x900 native resolution Incredible image detail for sharp text and graphics.
- > High brightness and contrast 250-nit brightness (typ) and 500:1 contrast ratio (typ) for rich, detailed images.
- > Stylish slim-bezel design

  An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- OSD/power lock secures your settings
   Prevents changes to monitor settings and maintains an optimized image.
- OnView® controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Windows Vista approved
- > ViewSonic Wizard included User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > PC and Mac® compatible
- > MPR II and ENERGY STAR® qualified





# **VA1703wb**

#### 17" VALUE SERIES WIDESCREEN LCD WITH 8MS VIDEO RESPONSE





| LCD              | Туре                   | 17" color TFT active matrix SXGA LCD                           |
|------------------|------------------------|--|
|                  | Display Area           | 14.4" horizontal x 9.0" vertical; 17.0" diagonal               |
|                  | Optimum Resolution     | 1440x900   |
|                  | Contrast Ratio         | 500:1 (typ)  |
|                  | Viewing Angles         | 160° horizontal, 160° vertical @ contrast ratio > 5:1          |
|                  | Response Time          | 8ms (typ)  |
|                  | Light Source           | Long life, 30,000 hrs. (typ)                                   |
|                  | Brightness             | 250 cd/m2 (typ)  |
|                  | Panel Surface          | Anti-glare   |
| VIDEO INPUT      | Analog                 | RGB analog (75 ohms, 0.7 Vp-p)                                 |
|                  | Frequency              | F <sub>h</sub> : 24~70kHz, F <sub>v</sub> : 50~75Hz            |
|                  | Sync                   | H/V separated (TTL)  |
| COMPATIBILITY    | PC                     | VGA up to 1440x900 non-interlaced                              |
|                  | Mac®*                  | Power Mac™ G3/G4/G5 up to 1440x900                             |
| CONNECTOR        | Analog                 | 15-pin mini D-sub  |
|                  | Power                  | 3-pin AC plug (CEE22)  |
| POWER            | Voltage                | AC 100–240V (universal), 50/60Hz (auto switch)                 |
|                  | Consumption            | 21W (typ)  |
| CONTROLS         | Basic                  | Power, 1, down, up, 2  |
|                  | OnView®                | Auto image adjust, contrast, brightness, ViewMatch® color      |
|                  |                        | adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information |
|                  |                        | (resolution, H-freq, V-freq, pixel clock, model number, serial |
|                  |                        | number, web site), manual image adjust (H. size, H. position,  |
|                  |                        | V. position, fine tune, sharpness), setup menu (language,      |
|                  |                        | resolution notice, OSD position, OSD timeout, OSD back-        |
|                  |                        | ground), memory recall   |
| OPERATING        | Temperature            | 32–104°F (0–40°C)  |
| CONDITIONS       | Humidity               | 10–90% (non-condensing)  |
| DIMENSIONS       | Physical with stand    | 16.0" x 14.7" x 8.3" (407mm x 375mm x 210mm)                   |
| (W x H x D)      | Physical without stand | 16.0" x 11.5" x 2.5" (407mm x 293mm x 63mm)                    |
| WEIGHT           | Net with stand         | 8.2 lb. (3.7 kg)   |
|                  | Net without stand      | 6.38 lb. (2.9 kg)  |
|                  | Gross with stand       | 11.2 lb. (5.1 kg)  |
| REGULATIONS      |                        | UL, cUL, FCC-B, CB, CE, NOM, TUV/GS, TUV/ERGO                  |
|                  |                        | (covers ISO13406-2), MPR II, BSMI, CCC, ENERGY STAR,®          |
|                  |                        | PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO                    |
| RECYCLE/DISPOSAL |                        | The lamp in this product contains mercury. Please dispose of   |
|                  |                        | in accordance with local, state and federal laws.              |
| POWER MANAGEMENT |                        | Meets MPR II and ENERGY STAR® standards                        |
| PACKAGE CONTENTS |                        | LCD display, video cable, power cable, Quick Start Guide,      |
|                  |                        | ViewSonic Wizard   |
| WARRANTY         |                        | Three-year limited warranty on parts, labor and backlight.     |
|                  |                        |  |









ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13346-00B-01/07] VA1703wb-1