

# Product data sheet

Specifications



## APC Rack PDU 9000 Switched, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

APDU9981EU3

### Overview

Lead time Usually in Stock

### Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	6 ft (1.8 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

### Complementary

Input Voltage	400 V 3 phase
Height	70.6 in (179.2 cm)
Width	2.2 in (5.5 cm)
Output Voltage	230 V
Depth	1.8 in (4.6 cm)
Net Weight	15.4 lb(US) (7 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 3P+N+PE
Mounting Mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	16 A
Max line current	16 A
Input current limits	16 A
Load Capacity	11000 VA
Input Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Outlet type and quantity</b>	21 IEC 60320 C13 3 IEC 60320 C19
<b>Communication Network Type</b>	10/100/1000BASE-T

## Environment

<b>Product Certifications</b>	cUL Listed FCC part 15 class A UL Listed VDE
<b>Standards</b>	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003
<b>Ambient Air Temperature for Operation</b>	23...140 °F (-5...60 °C)
<b>Relative Humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304404262
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	78.8 in (200.2 cm)
<b>Package 1 Width</b>	4.5 in (11.4 cm)
<b>Package 1 Length</b>	6.5 in (16.5 cm)
<b>Package 1 Weight</b>	19.73 lb(US) (8.95 kg)

## Contractual warranty

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)