

4XEM's 65W Wall Charger Triple Output w/ display

4XEM Part- 4XGAN00265WB



4XEM's 65W USB Charger offers amazing charging power and speed with three USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming the new standard for charging devices, allowing for up to 65W of charging power. This device features 2x USB-C ports and 1x USB-A port. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C and A Charger.

Problem it solves: Charge one to three USB devices with reliable power and speed using 4XEM's 65W GaN Charger.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features:

- 65-Watt power budget
- 2x USB-C port
- 1x USB-A port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging
- Power Output Display Hub

Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging



4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s)	2x USB Type-C Female 1x USB Type-A Female
	Power Source	Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Retractable Prongs
Performance	Industry Standards Certifications	USB-PD 3.0 CE ROHS ETL
Physical Characteristics	Colour	Black
	Display	Yes
	LED Indicator(s)	None
	Power Cable Length	N/A
	Product Height	2.06 in [52.3 mm]
	Product Width	1.17 in [29.8 mm]
	Product Length	2.23 in [56.6 mm]
	Weight of Product	2.86 in [72.6 mm] (with power prongs out) 4.02 oz [114 g]
Power	Total Power Budget	65W
	Power Delivery	65W Max
	Input Voltage	100-240VAC, 50Hz-60Hz @ 1.5A
	Output Voltage (C1/C2)	65W: 5/9/12/15V 3A, 20V 3.25A
	Output Voltage (USB-A)	60W: 3.4-5.5V 3A, 5/9/12/20V 3A
	Output Voltage (C1) + (C2)	65W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 20W:
	Output Voltage (C1) + (USB-A)	5V 3A, 9V 2.22A, 12V 1.66A
	Output Voltage (C2 + USB-A)	63W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 18W:
Output Voltage (C1) + (C2 + USB-A)	5V 3A, 9V 2A, 12V 1.5A 24W MAX - 24W: 5V 4.8A (Shared) 60W MAX - 45W: 5/9/12/15V 3A, 20V 2.25A + 15W: 5V 3A (Shared)	
Environmental	Operating Temperature	32°F to 104°F [0°C to 40°C]
	Storage Temperature	-4°F to 176°F [-20°C to 80°C]
	Humidity	5% to 90% (non-condensing)
Packaging Information	Package Type	Poly-Bag
	Package Height	6.00 in [152.4 mm]
	Package Width	4.00 in [101.6 mm]
	Package Length	1.18 in [30.0 mm]
	Shipping (Package) Weight	4.09 oz [116 g]
What's in the Box	Included in Package	1x 65W Dual USB-C + USB-A GaN Charger
Notes	Notes	

* Product appearance and specifications are subject to change without notice.
 * Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com

