



XA75 XA70

		XA75	XA70	XA55	XF405	XA35
Sensor	Sensor size	1.0-inch				1/2.84-inch HD CMOS PRO sensor
	Effective pixels	Approx. 8.29 million (total pixels: 13.40 million)				2.91 million pixels
Lens	Magnification, focal length	15x optical zoom, 25.5 - 382.5 mm f/2.8-4.5 4K UHD (with Dynamic IS OFF/Standard IS ON)				20x optical zoom, 26.8 (IS off)/ 28.8 (IS on) - 576mm
	ND filter	3 steps (turret switchable)				Gradation ND
	Image stabilization	Optical + electronic correction				Optical (Powered IS/Dynamic Mode), Multi-scene IS
Focus		Dual Pixel CMOS AF, Contrast AF				Instant AF/Medium AF
Infrared camera supported		YES				
LCD Monitor		3.5-inch (approx. 2.76 million dots), LCD, Capacitive touch panel		3.0 inch (approx. 0.46 million dots), capacitive touch panel	3.5 inch (approx. 1.56 million dots), capacitive touch panel	3.5 inch (approx. 1.23 million dots), OLED, capacitive touch panel
EVF		0.36-inch (approx. 1.77 million dots), OLED, articulating		0.24-inch (approx. 1.56 million dots), tiltable		
Looks		Standard, Wide DR (800%), Neutral, Monochrome			Standard, Wide DR (800%), Monochrome	Standard, Wide DR (800%), Highlight Priority
Recording media	Memory card	SD card (UHS-I U3 support) x 2 slots				



XA75 XA70

		XA75	XA70	XA55	XF405	XA35
Movie recording	XF-AVC (MXF)	3840 x 2160 29.97p / 23.98p 1920 x 1080 59.94p / 59.94i / 29.97p / 23.98p			3840 x 2160 59.94p / 29.97p / 23.98p 1920 x 1080 59.94p / 29.97p / 23.98p 1280 x 720 59.94p / 29.97p	NO
	MP4	3840 x 2160 29.97p / 23.98p 1920 x 1080 59.94p / 29.97p / 23.98p 1280 x 720 59.94p			3840 x 2160 59.94p / 29.97p / 23.98p 1920 x 1080 59.94p / 29.97p / 23.98p 1280 x 720 59.94p / 29.97p	1920 x 1080 59.94p / 29.97p / 23.98p 1280 x 720 59.94p / 29.97p 640 x 360 29.97p / 23.98p
	Audio	During MP4 recording: AAC 2ch, LPCM 4ch/ During XF-AVC recording: LPCM 4ch			During MP4 re- cording: AAC 2ch, LPCM 4ch During XF-AVC recording: LPCM 4ch	During AVCHD recording: LPCM 2ch, Dolby Digital During MP4 re- cording: AAC 2ch
	Slow and Fast (S&F) Motion Recording	x0.4 and up (60 fps/Full HD 29.97p playback)			x0.25 and up (120 fps/full HD 29.97p playback)	x0.4 and up (60 fps/full HD 29.97p playback)
	Color sample / bit depth	4:2:0 8 bit				
	Professional use terminals	3G-SDI terminal	YES	NO	NO	YES
XLR terminal		YES	NO	NO	YES x2	NO (Accessories supported)
Other terminals		HDMI, separate headphones, USB (USB Type-C), DC IN (USB Type-C), remote and MIC terminal (supports plug-in power)		HDMI, headphone, MIC (supports plug-in power), USB, remote	HDMI, headphone, MIC, USB, remote	HDMI, headphone, MIC, USB



XA75 XA70

	XA75	XA70	XA55	XF405	XA35
Detachable handle	YES				NO (Accessories supported)
Wi-Fi	NO			YES (5GHz/2.4GHz)	
Wired LAN	NO			YES	NO
Included battery	BP-820			BP-828	BP-820
Power consumption	Approx. 5.3W			Approx. 9.0W	Approx. 4.8W
Dimensions (body only)	Approx. 4.3 x 3.6 x 8.4 in. / 110 x 91 x 214 mm		Approx. 4.3 x 3.6 x 8.4 in. / 109 x 91 x 214 mm	Approx. 5.3 x 3.8 x 8.4 in. / 135 x 97 x 214 mm	Approx. 4.3 x 3.3 x 7.2 in. / 109 x 84 x 182 mm
Weight (body only)	Approx. 2.2 lbs. / 990 g	Approx. 2.2 lbs. / 985 g	Approx. 2.1 lbs. / 975 g	Approx. 2.5 lbs. / 1150 g	Approx. 1.7 lb. / 765 g