

# Lexmark X642e

Simply *In Touch* with your Business Needs.

uncomplicate  
the way you  
work.



**Fast! 43 ppm** Print speed improves productivity by reducing wait times



**Fast Automatic Document Feeder (ADF)** Fast, reliable and robust document feeder



**Mono Touch Screen** Adjustable and customisable e-Task touch screen



**Embedded Solutions** Extends the MFP capabilities without additional server and software infrastructure

Mono Laser Multifunction Printer



# Big advantages without a big price!

Ultra fast, network-ready and equipped with a rich range of functions – including standard fax and scan-to-email – the Lexmark X642e MFP offers more capabilities than you'd ever expect from such an affordable device.

## Productivity, just a touch away

No complicated buttons, icons or messages to interpret. The Lexmark X642e is equipped with an intuitive and adjustable black-and-white touch screen, which simplifies operation for the end-user and helps minimise downtime. A real first for an MFP in this price range!



## Scan straight to email

Because it integrates seamlessly with your company directory via LDAP, the Lexmark X642e remembers thousands of email addresses so you don't have to. Just place your originals in the 50-page feeder, touch the screen, select your addresses and go. It's that easy!



Lexmark supports the environment by reducing paper wastage. As one of the many environmental initiatives Lexmark does not pre-print brochures.



In Australia Lexmark partners with Planet Ark to collect and recycle toner and ink cartridges. Visit [www.lexmark.com.au](http://www.lexmark.com.au) for more details.



Lexmark and Lexmark with diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Operating speeds may vary according to document complexity, software application & system configuration.

### Cost saving & environmental features

Energy Star compliant, Taiwan Green Mark, WEEE, RoHS

## Technical Specifications

<b>Print technology</b>	Monochrome Laser
<b>Function</b>	Colour Scanning, Copying, Faxing, Printing, Network Scanning
<b>Print speed</b>	A4 - up to 43 ppm, Letter - up to 45 ppm
<b>Time to first page</b>	8.5 seconds
<b>Scan speed</b>	A4 - up to 33 spm mono, up to 16 spm colour
<b>ADF type</b>	Single Pass Simplex ADF with C-Path
<b>Copy speed</b>	A4 - up to 43 cpm
<b>Time to first copy</b>	7.5 seconds
<b>Processor</b>	514 MHz
<b>Memory</b>	Standard - 128 MB, Maximum - 640 MB, Optional - Yes
<b>Print resolution</b>	1200 Image Quality, 2400 Image Quality, 1200 x 1200 dpi, 600 x 600 dpi
<b>Scan resolution</b>	Colour - 300 x 300 dpi, Mono - 600 x 600 dpi
<b>Duty cycle</b>	200,000 pages per month
<b>Input</b>	Standard - 600 sheets, Maximum - 4,100 sheets
<b>Output</b>	Standard - 500 sheets, Maximum - 500 sheets
<b>Paper input capacity</b>	50 pages
<b>Copy/Fax/Scan (ADF)</b>	
<b>Number of paper inputs</b>	Standard - 2, Maximum - 6
<b>Reduce / Enlarge</b>	25 - 400%
<b>Scan area</b>	216 x 355.6 mm
<b>Modem speed</b>	33.6 Kbps
<b>Media supported</b>	Card Stock, Vinyl Labels, Transparencies, Polyester Labels, Plain Paper, Paper Labels, Integrated Labels, Envelopes, Dual Web Labels
<b>Media weight supported</b>	Paper: 60 - 135 gsm, Vinyl: 300 gsm
<b>Paper size</b>	A4, A5, Executive, Folio, JIS-B5, Legal, Letter, Statement, Envelope, 10, 7 <sup>3/4</sup> , 9, B5, C5, DL
<b>Paper Handling Standard</b>	Standard - 500-Sheet Output Bin, 500-Sheet Input Tray, 100-Sheet Multipurpose Feeder; Optional - 250-Sheet Universally Adjustable Tray with Drawer, 2,000-Sheet High-capacity Feeder, Optional furniture required, 500-Sheet Duplex Unit, Envelope Feeder, 250-Sheet Drawer, 400-Sheet Universally Adjustable Tray with Drawer, 500-Sheet Drawer
<b>Connectivity standard</b>	Standard - Ethernet 10/100BaseTX (RJ-45), USB Compatible with USB 2.0 Specification, One Internal Card Slot, USB Direct interface on Operator Panel; Optional - Internal Fiber 100Basefx, Lexmark N8050 802.11g Wireless Print Server (Print Only), Internal Gigabit Ethernet, Internal 802.11g Wireless, External 802.11g Wireless
<b>Compatibility</b>	PCL 6, PostScript 3 & PPDS Migration Tool, PDF 1.5
<b>Operating systems supported</b>	Microsoft Windows: 2000, NT, ME, XP, Server 2003, 98 2nd Edition, XP Professional x64; Novell Netware: 3.2, 4.2, 5.x and 6.x; UNIX: Sun Solaris 7, 8, 9, 10, HP-UX 11.00, 11.11, IBM AIX 5.1, 5.2, 5.3; Linux: Red Hat Linux 7.3, 8.0, 9.0, other systems; Mac OS: 9.x, X; IBM: AS/400R Systems with TCP/IP with OS/400R V3R1 or later using OS/400 Host Print Transform; Citrix MetaFrame: Citrix MetaFrame XP, Citrix MetaFrame Presentation Server 3.0., Citrix Presentation Server 4.0.
<b>Font Selection</b>	PCL - 89 scalable, 2 bitmapped, Includes - OCR-A, OCR-B and Code 3 of 9 bar codes; PostScript - 158 scalable; PPDS - 39 scalable, 5 bitmapped
<b>Security features</b>	SSL Enabled Embedded Web Server, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec, SNMPv3
<b>Warranty</b>	Two Years Onsite Warranty <sup>1</sup>
<b>Size (H x W x D)</b>	831 x 560 x 645 mm
<b>Acoustics</b>	26 dB(A) ready Print - 56 dB(A) operating; Copy - 57 dB(A) operating; Scan - 52 dB(A) operating
<b>Weight</b>	36.3 kg
<b>Power</b>	Average power in Standby with Power Saver on is 30 Watts. Average Power while printing is 800 Watts
<b>Product Certification</b>	Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, ECMA-74, CE Class A, CB IEC 60950 1, IEC 61000-3-2, -3, EN 55022, EN 55024, CISPIR 22 Class A, GS (TÜV)-EN 60950-1, SEMKO, UL AR, CS, TÜV Rh, N Mark, C-tick Class A, CCC Class A, RPC, PSB, MIC, EK - K60950 Duty Cycle
<b>Part numbers</b>	X642e - 22G0601, 250-Sheet Drawer - 20G0889, 500-Sheet Drawer - 20G0890, 250-Sheet Tray - 20G0879, 500-Sheet Tray - 20G0884, 2000-Sheet Drawer (A4) - 20G0893, 500-Sheet Duplex Unit - 20G0888, Envelope Feeder 20G0891, 250-Sheet Universally Adjustable Drawer - 20G1223, 250-Sheet Universally Adjustable Tray - 20G1224, 400-Sheet Universally Adjustable Drawer - 20G1218, 400-Sheet Universally Adjustable Tray - 20G1217
<b>Supplies</b>	Ships with 10K* pages Return Programme toner cartridge Aftermarket Supplies: 10K pages Regular toner cartridge - X644A21P 21K pages High Yield toner cartridge - X644H21P 10K pages Return Program toner cartridge - X644A11P 21K pages High Yield Return Program toner cartridge - X644H11P 21K pages High Yield Return Program toner cartridge for Label Applications - X644H01P

<sup>1</sup>Local warranty conditions apply. For further details please contact your nearest office.

\*Average cartridge yield. Declared yield value in accordance with ISO/IEC 19752.

[www.lexmark.com.au](http://www.lexmark.com.au)

# LEXMARK