

# Product data sheet

Specifications



## APC Essential SurgeArrest, 6 outlet

P6B

⚠ Discontinued on: Jul 30, 2024

⚠ To be end-of-service on: Sep 30, 2024

⚠ Discontinued - Service only

Product availability: Stock - Normally stocked in distribution facility

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	120 V
Product or Component Type	Surge protection device
Main Output Voltage	120 V
Kw Rating	0 W
Rated power in VA	0 VA
Input Connection Type	NEMA 5-15P
Cable length	6 ft (1.8 m)
Number of cables	1
Provided equipment	User Manual

## Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0

## Physical

Color	Charcoal
Height	11.5 in (29.2 cm)
Width	2.2 in (5.7 cm)
Depth	1.5 in (3.8 cm)
Net Weight	0.99 lb(US) (0.45 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
-----------------	--------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Output

Max Configurable Power (Watts)	0 W
--------------------------------	-----

## Conformance

Product Certifications	CSA
Standards	UL 1449
Equipment protection policy	Lifetime : \$25000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Surge Protection and Filtering

Surge energy rating	840 J
---------------------	-------

## Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304211020
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.3 in (33.8 cm)
Package 1 Width	1.5 in (3.8 cm)
Package 1 Length	5.8 in (14.7 cm)
Package 1 Weight	1.3 lb(US) (0.6 kg)
SCC14	10731304211027

## Contractual warranty

Warranty	Limited Lifetime
----------	------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Circularity Profile [End of Life Information](#)

**California Proposition 65** WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)