

PowerLite® 84

Multimedia Projector









Smart choice. Amazing audio performance.

- Bright, brilliant presentations 2600 lumens color light output, 2600 lumens white light output*
- Razor-sharp detail native XGA resolution
- Powerful sound and communication features, no added cost
 built-in 10 W speaker, closed captioning decoder
- Convenient microphone input saves both money and the presenter's voice by using the projector's speaker
- Energy-efficient E-TORL® lamp up to 6000-hour lamp life**
- Plug 'n Play, no-hassle setup instantly projects images from a PC via the USB connection
- Easy network monitoring and control RJ-45 connectivity and included software

- Easy picture adjustments and greater positioning flexibility — automatic keystone correction, 1.6x optical zoom
- Quick, convenient control direct power on/off, AV Mute/Sleep Mode, Instant Off®/On
- Rich, vibrant color and reliable performance 3LCD, 3-chip optical engine
- Filters to protect your investment with easy side access for hassle-free maintenance
- Added security in any environment convenient metal anchor bar
- Carrying case included for easy portability and protection when stored









0 **EPSON**

Audio L/R

FLPMBP01

ELPMBP02

FLPMRP03

Composite Video



PowerLite 84

Multimedia Projector

ORDERING INFORMATION

Product Name	Product Code	UPC
PowerLite 84	V11H294020	010343 87303 2
Replacement Lamp	V13H010L50	010343 87322 3
Replacement Air Filter Set	V13H134A22	010343 87323 0

SPECIFICATIONS

Projection System

Epson 3LCD, 3-chip optical engine

Projection Method

Front/rear/ceiling mount

Driving Method

Epson Poly-silicon TFT Active Matrix

Pixel Number

786,432 dots (1024 x 768) x 3

White Light Output*

2600 lumens (ISO 21118 Standard)

Color Light Output*

2600 lumens

Aspect Ratio

Native Resolution

1024 x 768 (XGA)

Resize

640 x 480 (VGA), 800 x 600 (SVGA), 1152 x 864 (SXGA), 1280x768 (WXGA 60-1), 1360x768 (WXGA 60-2), 1280x960 (SXGA2), 1280x1024 (SXGA3), 1280 x 800 (WXGA), 1440 x 900 (WSXGA), 1400 x 1050 (SXGA+), 1600 x 1200 (UXGA)

Lamp Type

E-TORL 200 W UHE

Lamp Life**

Up to 6000 hours (Low Light Output Mode) Up to 5000 hours (High Light Output Mode)

Throw Ratio Range

1.39 - 2.26 (4:3)

Size (projected distance)

30" - 300" (2.7' - 45.5')

Keystone Correction Automatic

Vertical: ± 30 degrees

Plug 'n Play

Projector is Mac® compatible via DVI to VGA adapter (not included)

Contrast Ratio

Up to 2000:1

Color Reproduction

PROJECTION LENS

Type Manual focus/(optical) zoom

F-number

149 - 194

Focal Length

18.2 mm - 29.2 mm

Zoom Ratio

Optical zoom 1.0 - 1.6

OTHER

Display Performance

NTSC: 480 lines PAL: 560 lines

(Depends on observation of the multi-burst

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/ SECAM/SDTV/HDTV

Interfaces

Computer/component video: D-sub 15 pin x 2 S-video: Mini DIN x 1

Composite video: RCA x 1

Audio in x 3 (RCA (L&R) x 1, mini stereo x 2) Variable Audio Out: mini stereo x 1

USB connector: Type B x 1 (USB display and mouse/keyboard control)

Serial: RS-232c x 1

LAN Networking: RJ-45 x 1 Monitor Out: Mini D-sub 15 pin x 1

Microphone: stereo mini jack x 1 Speaker

10 W (mono)

Operating Temperature

41 ° to 95 °F (5 ° to 35 °C)

Power Supply Voltage 100 - 240 V ±10%, 50/60 Hz

Power Consumption

Communication on: 7.9 W standby Communication off: 1.9 W standby

Fan Noise

35 dB (High Light Output Mode) 28 dB (Low Light Output Mode)

USB (TypeB)

IAN

RS-232C

Kensington®-style lock provision, security anchor bar

DIMENSIONS (W x D x H)

Including feet: 12.9" x 9.8" x 4.3" Excluding feet: 12.9" x 9.8" x 3.7" Weight: 6.9 lb/3.1 kg

REMOTE CONTROL

Features

Search, Comp, Video, USB, LAN, power, aspect, color mode, volume, e-zoom, AV mute, freeze, menu, page up and down, help, auto, mouse functions, user, num, pointer, esc, enter

Operating Angle

Right/left: ± 30 degrees Upper/lower: ± 30 degrees

Operating Distance

19' (6 m)

SUPPORT — THE EPSON CONNECTIONS

Pre-sales Support

U.S. and Canada 800-463-7766 Internet website www.epson.com

Service Programs

Two-year projector limited warranty, Epson Road Service program, Epson PrivateLine® dedicated toll-free support and 90-day lamp limited warranty

What's In The Box

Power cord, computer cable (VGA), USB cable, soft carrying case, projector remote control, batteries, user manual CD, Projector Software CD, Quick Setup Sheet, PrivateLine support card, registration card and password protection sticker

ACCESSORY PART NUMBERS

Universal projector ceiling mount ELPMBPJF Advanced projector ceiling mount ELPMBPRG High Security projector ceiling mount

Adjustable suspended ceiling channel kit False ceiling plate kit

Monitor Out

Computer 2/Component 2

Computer 1/Component 1 -S-video

Structural Round ceiling plate Adjustable Extension Column (pipe) 8" – 11"

ELPMBC01 Component to VGA video cable ELPKC19 S-video cable ELPSV01 ELPKS63

Audio Out

SwissGear® backpack Wheeled soft case ELPKS62 Soft shoulder case for

FLPKS61 projector and laptop FLPKS58 Molded hardshell case ELPSC06 50" portable screen 60" portable pop-up screen FLPSC07 80" portable pop-up screen ELPSC08

Duet™ screen ELPSC80 Epson DC-10s document camera ELPDC10S Epson DC-06 document camera

V12H321001 (ELPDC06) Kensington security lock ELPSL01

FI PDA01 Distribution amplifier Image presentation camera (ELPDC05) V12H162020

PACKAGING SPECIFICATIONS

PowerLite 84 Dimensions 16.3" x 14.6" x 7.2" (W x D x H) Weight 12.7 lb

Replacement Lamp

Dimensions 6.3" x 5.6" x 5.6" (W x D x H) Weight 0.7 lb

Master Carton Dimensions 28.4" x 13.1" x 6.8" (W x D x H) Weight 8.6 lb

Units Per Master Carton 10

Replacement Air Filter Set Dimensions 4.9" x 3.9" x 1.2" (W x D x H)

Weight 0.02 lb

Master Carton Dimensions 12.8" x 5.3" x 4.7" (W x D x H) Weight 0.2 lb

Units Per Master Carton 10

* Light output varies depending on modes (color and white light output). White light output measured using ISO 21118 standard.

** Lamp life results will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Better Products for a Better Future™

www.epson.com/environment

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Specifications and terms are subject to change without notice. Epson, Instant Off and E-TORL are registered trademarks, Epson Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PowerLite and PrivateLine are registered trademarks, Duet is a trademark and Epson Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2009 Epson America, Inc. CPD-26962R1 7/09 PDF