# Poly Edge E500 IP Phone and PoE-enabled with Power Supply

# Designed for the new way you work

This desk phone makes work easy. Built for hot-desking or the home office, these phones offer the perfect user experience. Two displays and 12-line keys give you more ways to connect, plus quality audio, in a seriously sharp package.



\*Product image may differ from actual product

## Built to grow

This workhorse phone is outfitted with a big 5-inch color display and is designed to handle up to 48 lines. What's more, the Poly Edge E500 Series can take on two additional expansion modules, supporting up to 66 more contacts each.

# Integrated protection

Rest assured that your devices, enhanced with Microban® antimicrobial product protection, stay cleaner, fresher, and more durable for longer. Protection that lasts the life of the product, actively reducing the growth of bacteria 24/7 <sup>1</sup>.

## Enterprise-quality sound

The Poly E400 Series offer quality audio with Poly HD voice and bass frequency enhancing speaker design. They reduce noise and distractions with Poly NoiseBlockAl and Acoustic Fence technologies.

**Datasheet** 



# Poly Edge E500 IP Phone and PoE-enabled with Power Supply

# **Specifications**







Display

Aspect ratio: 9:16

Native resolution: 800 x 480 Panel technology: Color IPS LCD

Display size (diagonal): 5"

Display size (diagonal, metric): 12.7 cm (5")

#### Connectivity and communications

External I/O ports:

1USB 2.0 Type-C° (for media, storage applications, headset, expansion module)

2 RJ-45 (10/100/1000BASE-TX Mbps)

Wireless technologies:

NFC<sup>3</sup>

#### **Battery** Power features:

13 W (maximum)

Built-in auto-sensing IEEE 802.3af Power over Ethernet (Class 4)2.4

#### User interface features

Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Password login Portuguese: Romanian: Russian: Slovenian: Spanish: Swedish

#### Audio

#### Audio features

Poly HD Voice

Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise

Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset

Poly NoiseBlockAI technology removes most background noise when using the speakerphone

Poly Computer Audio Connector app installed on your PC (Windows only) enables selecting your phone for PC audio

in/out to use the phones handset, optional headset and handsfree speakerphone with PC applications

Bass frequency enhancing design

TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)

Individual volume settings with visual feedback for each audio path

Voice activity detection Comfort noise generation

DTMF tone generation (RFC 2833 and in-band)

Low delay audio packet transmission

Adaptive jitter buffers

Frequency response (microphone):  $150\,\mathrm{Hz}$  to  $14\,\mathrm{kHz}$ 

## Audio codecs:

G.711 (A-law and  $\mu$ -law)

G.729AB iLBC

OPUS

#### Environmental

Certifications and compliances: AS/NZS 609501; AS/NZS 623681; Australia RCM; Brazil ANATEL; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EN55024; EN55032 Class B; EN 60950-1-& EN 62368-1; EN 61000-3-2, EN 61000-3-3; FCC Part 15 (CFR 47) Class B; IEC 609501 & IEC 62368-1; ICES-003 Class B; NZ Telepermit; ROHS compliant; Saudi Arabia CITC; So. Africa ICASA; So. Korea KC; UAE TRA; UL 62368-1; VCCI Class B; Eurasian Customs Union EAC; Indonesia SDPPI; Mexico NOM ANCE; TAA; UK - UKCA

Operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit):  $0 \text{ to } 40^{\circ}\text{C} / 32 \text{ to } 104^{\circ}\text{F}$ Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -40 to 70°C / -40 to 160°F

Energy star certified: ENERGY STAR® certified

#### Certifications

Special feature

Unicode UTF-8 character support Adjustable desk stand (2 positions)5

#### Applications supported

Management software:

Poly Zero Touch Provisionina

Poly Lens

Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management

#### Display features

Lightbar status indicator (RGB with color mixing)

#### Security

#### Security management:

8021X Authentication and EAPOL Media encryption via SRTP

Digest guthentication

Encrypted configuration files

HTTPS secure provisioning

Support for signed software executables

Support for URL syntax with password

Transport Layer Security (TLS)

SRTP media encryption using AES 256 bits

#### Network

#### Supported network protocols

DHCP VLAN discovery

LLDP-MED for VLAN discovery

FTP/TFTP/HTTP/HTTPS server-based central provisioning

Hardware diganostics

Manual or dynamic host configuration protocol (DHCP) network setup

Network address translation support for static configuration and Keep-Alive QoS Support - IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP

Status and statistics reporting

Syslog Event Logging

Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment

Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation

Time and date synchronization using SNTP

RTCP and RTP support

IPv6

Provisioning and call server redundancy support

DNS-SRV

UDP

SIP protocol support

IETF SIP (RFC 3261 and companion RFCs)

#### VoIP features:

12 line keys supporting up to 34 SIP lines with pagination

# Poly Edge E500 IP Phone and PoE-enabled with Power Supply

# **Specifications**







#### Headset and handset compatibility

#### Headset ports:

. . . . .

1 Electronic Hook Switch (EHS) port for optional APP-51 adapter

#### Headset and handset compatibility:

Compatible with commercially available TTY adapter equipment

Compliant with ADA Section 508 Subpart B 1194.23 (all)

Hearing aid compatibility to ITU-TP.370 and TIA 504A standards

Hearing aid compatible (HAC) hand set for magnetic coupling to hearing aids

USB Type-C® headset support

# **Telephony and call handling features**Telephony and call handling features:

4 context-sensitive soft keys

4 way navigation key cluster with center Select key

 $Bundled\ with\ Polycom\ UC\ Software: Corporate\ Directory\ Access\ using\ LDAP$ 

Busy Lamp Field (BLF)

Call timer and call waiting

Call transfer, hold, divert (forward), park, pickup

Called, calling, connected party information

Calling Party Identification (RFC8225 classifications - Trusted, Unknown, SPAM)

Distinctive incoming call treatment/call waiting

Do not disturb function

Electronic hook switch capable

Enhanced Feature Keys make powerful feature shortcuts online key appearances or soft keys

Headset select key (illuminated when selected)

Hold and transfer keys

Home and back feature keys

Local three-way audio conferencing

Local configurable digit map/dial plan

Mute key (illuminated when muted)

One-touch speed dial, redial

Pagination key for additional lines/contacts

Remote missed call notification

Reverse number lookup via LDAP

Shared call/bridged line appearance

Speakerphone select key (illuminated when selected)

Supports Polycom Apps SDK and API for third-party business and personal application

Visual Conference Management

Voicemail key

Volume +/- control keys

Flexible line appearance (one or more line keys can be assigned for each line extension)

12 line keys supporting up to 48 line key assignments for lines, contacts, and features with pagination 1

#### Weight and dimensions

Product Primary Color: Black

Package dimensions (imperial):  $10 \times 13.3 \times 3.5$  in Package dimensions (metric):  $25.6 \times 33.8 \times 8.9$  cm

Package weight (imperial): 24 lb Package Weight (metric): 1080 g UPC number: 196188444474 Product number: 89B56AA

#### Country of origin

Country of origin: Made in China

#### Warranty

Poly standard one-year limited warranty

#### What is in the box

Setup sheet

Network (LAN) cable-CAT-5E

Desk stand

Console with Microban® Antimicrobial protection

Handset with Microban® Antimicrobial protection

Handset cord

#### Key Selling Points Footnotes

<sup>1</sup>Microban antimicrobial product protection available for the PolyEdge E Series phones protects the entire phone except for the handset cord. Microban antimicrobial product protection is a built-in active ingredient that enables products to resist the growth of microbes such as bacteria, mold, and mildew. Microban protection helps products stay cleaner, fresher, and last longer than products with untreated surfaces.

#### Technical Specifications Footnotes

<sup>1</sup>Most software-enabled features must be supported by the service provider platform. Please contact your IP PEX/softswitch vendor or service provider for a list of supported features. <sup>2</sup> External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately). Power supply unit (PSU) sold separately, <sup>3</sup> NFC-enabled Edge E series phones allow third-party applications to read-serial number and other device information that can be useful in application development such as guest login for phone hoteling. <sup>4</sup> Ordering an optional power supply unit will be necessary if not powered over ethernet with PDE (i.e. using Wi-Fi for network). <sup>5</sup> Optional wall mount kit can be ordered separately.



