

Product data sheet

Specifications



17" Rack LCD Console with Integrated 8 Port Analog KVM Switch

AP5808

Overview

Presentation	The Rack LCD Console with Integrated KVM Switch combines the functionality of Rack LCD Console and Analog KVM switches in one convenient package optimizing U space in the rack environment, eliminating cable clutter, and offering a value of two products functionality in one package. Keyboard is a US English keyboard layout.
Lead time	Usually in Stock

Main

Main Input Voltage	120 V 240 V
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Cable length	6 ft (1.8 m)
Number of cables	1
Provided equipment	USB KVM cable Single user rack mount kit PS2 KVM cable NEMA 5-15 power cord Installation guide Firmware upgrade cable Documentation CD C13-C14 power cord

Physical

Color	Black
Height	1.7 in (4.3 cm)
Width	19.02 in (48.3 cm)
Depth	28.0 in (71.1 cm)
Net Weight	30.36 lb(US) (13.77 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Maximum Mounting Depth	41.33 in (104.98 cm)
minimum mounting depth	26.8 in (68 cm)

Input

Input Frequency	50/60 Hz
------------------------	----------

Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product Certifications	cUL Listed C-tick CE Industry Canada KCC UL Listed VDE TAA compliance
-------------------------------	--

Standards	EN 60950 FCC Part 15 class A IEC 60950
------------------	--

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
--	-------------------------

Supported Hardware

Display colour	16 colours
-----------------------	------------

display size	337.9 (H) x 270.3 (V) 17 inch
---------------------	----------------------------------

Trackball Type	PS/2 Touchpad USB mouse
-----------------------	----------------------------

Display Type	LCD display
---------------------	-------------

Ordering and shipping details

GTIN	731304278801
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	5.1 in (13 cm)
-------------------------	----------------

Package 1 Width	32.7 in (83 cm)
------------------------	-----------------

Package 1 Length	26.2 in (66.5 cm)
-------------------------	-------------------

Package 1 Weight	43.78 lb(US) (19.86 kg)
-------------------------	-------------------------

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Reach Free Of Svhc

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov