

Product data sheet

Specifications



APC Smart-UPS On-Line, 3kVA, Tower, 208V, 2x L6-20R+1x L6-30R NEMA outlets, SmartSlot, Extended runtime, W/O rail kit

SRT3000XLT

Overview

Lead time Usually in Stock

Main

Main Input Voltage	208 V
product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	240 V
Main Output Voltage	208 V
Other Output Voltage	240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Input Connection Type	NEMA L6-20P
output connection type	2 NEMA L6-20R 1 NEMA L6-30R
Cable length	10 ft (3.05 m)
Number of cables	1
Provided equipment	CD with software Documentation CD Installation guide Removable support feet USB cable Warranty card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery type	Lead-acid battery
Number of battery filled slots	1
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery voltage	96 V
Battery charger power	165 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBC152
Extended runtime	1

General

UPS type	Double conversion online
product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	17.008 in (43.2 cm)
Width	3.3 in (8.5 cm)
Depth	25.0000000000 in (63.5 cm)
net weight	69.005 lb(US) (31.3 kg)
mounting location	Front
Mounting preference	Lower
mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	100...275 V adjustable (half load)

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 2 %
Crest factor	3 : 1
Bypass type	Internal bypass (automatic and manual)
Additional information	Configurable for 208 or 240 nominal output voltage

Conformance

Product certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

Environmental

Ambient air temperature for operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft

Ambient air temperature for storage	5.0000000000...113.0000000000 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	55 dBA
heat dissipation	773 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.7 in (24.6 cm)
Package 1 Width	34.3 in (87.1 cm)
Package 1 Length	23.6 in (59.9 cm)
Package 1 Weight	81.00 lb(US) (36.74 kg)

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Environmental Certifications

 Energy Star® [ENERGY STAR UPS V2.0 \(USA\)](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant with Exemptions](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)